

BENZ OIL INC -- PETRAULIC -- 9150-00-966-8831

=====
Product Identification
=====

Product ID:PETRAULIC
MSDS Date:10/14/1993
FSC:9150
NIIN:00-966-8831
MSDS Number: BVBHP
=== Responsible Party ===
Company Name:BENZ OIL INC
Address:2724 W. HAMPTON AVE
City:MILWAUKEE
State:WI
ZIP:53209-5401
Country:US
Info Phone Num:414-442-2900
Emergency Phone Num:414-442-2900
CAGE:8F260

=== Contractor Identification

===
Company Name:BENZ OIL INC
Address:2724 W HAMPTON AVE
Box:City:MILWAUKEE
State:WI
ZIP:53209-5401
Country:US
Phone:414-442-2900
CAGE:8F260
Company Name:SALATHE OIL CO INC
Address:2226 PETERS RD
Box:City:HARVEY
State:LA
ZIP:70058
Country:US
Phone:504-366-4542
CAGE:0T5C6

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL
CAS:8012-95-1
RTECS #:PY8030000
Fraction by Wt: >95%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3 (MIST); 93

Ingred Name: PROPRIETARY ADDITIVE

Fraction by Wt: 400F, >204C

Lower Limits: 1

Upper Limits: 1

Extinguishing Media: CARBON DIOXIDE, WATER SPRAY, FOAM, DRY CHEMICAL.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS IN FIGHTING FIRE IN CONFINED/ENCLOSED SPACE. WATER MAY CAUSE FROTHING AND SPREADING OF FIRE.

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures: RECOVER FREE PRODUCT. ADD SAND, EARTH, OR

OTHER ABSORBENT TO SPILL. MINIMIZE SKIN CONTACT. KEEP PRODUCT OUT OF SEWERS AND WATERWAYS. ADVISE AUTHORITIES OF LARGE SPILLS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions: STORE AWAY FROM SOURCES OF IGNITION AND STRONG OXIDIZING AGENTS. DO NOT PRESSURIZE, CUT, WELD, SOLDER, DRILL, GRIND DRUMS.

Other Precautions: "EMPTY" CONTAINERS CONTAIN RESIDUAL OIL; TREAT AS IF FULL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE NORMALLY REQUIRED. IF EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.

Ventilation: USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves: NITRILE

Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic

Practices: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS PROVIDED BY CAGE 0T5C6 FOR CONTRACT NUMBER SPO451-94-MR-795.

===== Physical/Chemical Properties =====

HCC: V6

Boiling Pt: B.P. Text: >500F, >260C

Vapor Pres: 0.01 MM HG

Vapor Density: 5

Spec Gravity: 0.9

Evaporation Rate & Reference: NIL (N-BUTYL ACETATE=1)

Solubility in Water: SLIGHT

Appearance and Odor: LIQUID

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: FUMES, SMOKE, OXIDES OF CARBON/SULFUR/NITROGEN WHEN COMBUSTED.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF MATERIAL IN A LICENSED LANDFILL OR INCINERATION FACILITY IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.