

SUNOX INC -- DRY ICE -- 6830-01-165-6174

=====  
Product Identification  
=====

Product ID:DRY ICE  
MSDS Date:10/10/1988  
FSC:6830  
NIIN:01-165-6174  
MSDS Number: BVBLZ  
=== Responsible Party ===  
Company Name:SUNOX INC  
Address:4236 STATESVILLE RD  
Box:33871  
City:CHARLOTTE  
State:NC  
ZIP:28233  
Country:US  
Info Phone Num:704-596-6262  
Emergency Phone Num:704-596-6262  
CAGE:6Z872  
=== Contractor Identification ===  
Company Name:SUNOX INC  
Address:4236 STATESVILLE RD  
Box:33871  
City:CHARLOTTE  
State:NC  
ZIP:28233  
Country:US  
Phone:704-596-6262  
CAGE:6Z872

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CARBON DIOXIDE  
CAS:124-38-9  
RTECS #:FF6400000  
OSHA PEL:10000PPM; 30000 STEL  
ACGIH TLV:5000 PPM; 30000 STEL

Ingred Name:MATLS TO AVOID:MAGNESIUM, ALUMINUM, TITANIUM/ZIRCONIUM),  
THEIR HYDRIDES & MATLS LIKE DIETHYL MAGNESIUM, MOIST (ING 3)  
RTECS #:9999999ZZ

Ingred Name:ING 2:CE

SIUM OXIDE/LITHIUM ACETYLIDE W/AMMONIA CAN IGNITE  
IN CO\*2 ATM. DRY ICE CAN FORM SHOCK SENSITIVE MIX WITH (ING 4)  
RTECS #:9999999ZZ

Ingred Name:ING 3:SODIUM, POTASSIUM OR SODIUM-POTASSIUM ALLOY.  
RTECS #:9999999ZZ

Ingred Name:EFTS OF OVEREXP:COULD RSLT IN FROSTBT/CRYOGENIC (FREEZE)  
"BURNS." CNTCT W/LIQ/SOLID CAN PRDCE FROSTBT & FREEZE (ING 5)  
RTECS #:9999999ZZ

Ingred Name:ING 5:BURNS. EFTS ARE CHANGE IN COLOR OF SKIN TO GRAY/WHITE  
POSS FOLLOWED BY BLISTERING. CO\*2 IS MOST POWERFUL (  
ING 7)  
RTECS #:9999999ZZ

Ingred Name:ING 6:CEREBRAL VASODIALTOR KNOWN. INHAL LG CONC CAUSES  
RAPID CIRCULATORY INSUFFICIENCY LEADING TO COMA & DEATH. (ING 8)  
RTECS #:9999999ZZ

Ingred Name:ING 7:CHRONIC, HARMFUL EFTS ARE NOT KNOWN FROM RPTD INHAL  
OF LOW (3-5 MOLAR %) CONC.  
RTECS #:9999999ZZ

Ingred Name:FIRST AID PROC:MED ASSISTANCE SHOULD BE SOUGHT IMMED.  
SKIN:FROSTBT:FLUSH AFFECTED AREAS W/LUKEWARM WATER. DO (ING 10)  
RTECS #:9999999ZZ

Ingred Name:ING 9:NOT USE HOT WATER. MD SHOULD  
SEE PROMPTLY IF  
CRYOGENIC "BURN" HAS RSLTD IN BLISTERING OF DERMAL SURF/DEEP (ING  
11)  
RTECS #:9999999ZZ

Ingred Name:ING 10:TISS FREEZING. PROMPT MED ATTN MANDATORY IN ALL  
CASES OF OVEREXP. RESCUE PERS SHOULD BE EQUIPPED WITH (ING 12)  
RTECS #:9999999ZZ

Ingred Name:ING 11:NIOSH/MSHA SELF-CONTAINED BREATHING APPARATUS.  
RTECS #:9999999ZZ

Ingred Name:WASTE DISP METH:HVR/AIR. DO NOT PUT DRY ICE IN CLSD CNTNR  
WHERE EVOLVED GAS CANNOT ESCAPE! REMOVE SCRAP SOLID (ING 14)  
RTECS #:9999

999ZZ

Ingred Name:ING 13:("SNOW" OR "DRY ICE") TO HOOD W/FORCED VENT OR TO A  
REMOTE OUTSIDE AREA. ALLOW SOLID TO SUBLIME.

RTECS #:9999999ZZ

Ingred Name:HNDLG/STOR PREC:WHICH OPEN FROM TOP HAVING LOOSE-FITTING  
LIDS SO CO\*2 VAPOR FROM SUBLIMATION OF SOLID MAY BE (ING 16)

RTECS #:9999999ZZ

Ingred Name:ING 15:ALLOWED TO ESCAPE INTO ATM. FOR ADDNL HNDLG & STOR  
RECOM SEE CGA PAMPHLETS P-1 & G-6.

RTECS #:9999999ZZ

Ingred Name:OTHER PREC:W/MOST PLASTICS & ELASTOMERS. ALSO SEE CGA  
PAM

PHLET G-6.3.

RTECS #:9999999ZZ

Ingred Name:OTHER PROT EQUIP:TEMP) TO PVNT FREEZE BURNS & FROSTBT IF  
MORE THAN MOMENTARY CNTCT W/CO\*2 AT LOW TEMP IS POSS.

RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NERVOUS SYS CONTROL OF RESP IS  
DEPENDENT ON CO\*2 LEVEL B

REATHED IN AIR. BY REDUCING O\*2 LEVEL IN

AIR, CO\*2 CAN CAUSE SUFFOCATION. SYMP OF OVEREXP INCL HDCH, DIZZ,  
SHORTNESS OF BREATH, MUSC WEAK, DROW & RINGING IN EARS. INHAL:LOW  
CONC (3-5 MOLAR %) CAUSE INCR RESP & HDCH. 8-15 MOLAR % CONC CAUSE  
HDCH, (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:NAUS & VOMIT WHICH MAY LEAD TO UNCON  
IF NOT MOVED TO OPEN AIR/GIVEN O\*2. HIGH CONC CAUSE RAPID  
CIRCULATORY INSUFFICIENCY LEADING TO CO

MA & DEATH. WHEN

REFRIGERATED LIQ CO\*2 IS VAPORIZED THRU AN ORIFICE, IT CAN FORM  
SOLID PARTICLES OF CO\*2 ("SNOW"/"DRY ICE" PWDR). CONTINUOUS DERMAL  
CNTCT W/COLD SNOW (ING 5)

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INGEST:CALL MD IMMED. EYES:IMMED FLUSH W/POTABLE WATER FOR  
MIN OF 15 MIN, SEEK ASSISTANCE FROM MD. INHAL:IF CONSCIOUS, ASSIST  
TO UNCONTAMD AREA & INHALE FRES

H AIR. QUICK REMOVAL FROM AREA IS MOST IMPORTANT. IF UNCON, MOVE TO UNCONTAMD AREA, GIVE MOUTH-TO-MOUTH RESUSCITATION & SUPPLEMENTAL O\*2. ASSURE THAT VOMITED MATL DOES NOT OBSTRUCT AIRWAY BY USE OF POSITIONAL DRAINAGE. (ING 9)

===== Fire Fighting Measures =====

Extinguishing Media:NONFLAMMABLE, INERT GAS.

Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP.

USE WATER SPRAY TO COOL FIRE-EXPOS CNTNRS TO PVNT RUPTURE. MATL IS

NON-COMBUST. IT CAN BE USED AS (SUPDAT)

Unusual Fire/Explosion Hazard:WATER SPRAY IS NOT EFTIVE FOR USE ON

FIRES INVOLVING CHEM THAT HAVE THEIR OWN O\*2 SUPPLY (I.E. CELLULOSE NITRATE)/ON FIRES INVOLVING REACTIVE METALS (SUPDAT)

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA OF MAJOR SPILL/RELS OF CO\*2.

NOTIFY SFTY PERS. PROVIDE VENT. CLEAN-UP PERS NEED SPECIAL TRAINING & PROT AGAINST CNTCT W/VERY COLD MATL/EXCESS

IVE INHAL OF GASEOUS

CO\*2.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:SOLID CO\*2 GENERALLY DELIVERED IN KRAFT-PAPER-WRAPPED BLOCKS WEIGHING APPROX 50 LBS & APPROX 1/2 CUBIC FT IN VOL. STORE IN INSULATED CNTNRS (ING 15)

Other Precautions:DRY CO\*2 CAN BE HNDL W/MOST COMMON STRUCTURAL MATLS. MOIST CO\*2 IS CORR BY ITS FORM OF CARBONIC ACID. FOR APPLICATNS 316,309 & 310 S

TAINLESS STEELS MAY BE USED AS WELL AS HASTELLOY A, B & C & MONEL. A T NORM TEMP, CO\*2 IS COMPATIBLE (ING 17)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:PROVIDE NIOSH/MSHA APPRVD SUPPLIED-AIR OR SELF-CONTAINED RESP FOR USE IN NON-ROUTINE/EMER SITUATIONS W/EXPOS ABOVE TLV. FULL FACEPIECE IS REQD FOR CONC > 10%. PROVIDE STANDBY PERSON(S) W/RESCUE EQUIP IF WORK REQD AT > 15% CO\*2 IN AIR.

Ventilation:GENERAL AND LOCAL EXHAUST VENTILA

TION TO MEET TLV  
REQUIREMENTS.

Protective Gloves: LOOSE FITTING, INSULATED GLOVES.

Eye Protection: ANSI APPROVED CHEM WORK GOGGLES (SUP DATA)

Other Protective Equipment: SFTY SHOES, SOLID CO<sup>2</sup> HNDLG "TONGS." MAY  
REQ ADDNL PROT CLTHG (APRON, FSHLD, ETC WHICH ARE RESISTANT TO LOW  
(ING 18)

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRE FIGHT PROC: FIRE EXTING AGENT PRIMARILY FOR ITS SMOTHERING EFT  
(REDUCTION OF O<sup>2</sup> CONC TO PT WHERE IMMEDIATE ATM CA

NOT SUPPORT

COMBUST). EXPLO HAZ: (SUCH AS POTASSIUM, SODIUM, MAGNESIUM,  
ALUMINUM, TITANIUM & ZIRCONIUM) OR THEIR HYDRIDES AS THESE MATLS  
CAN DECOMPOSE CARBON DIOXIDE. EYE PROT: W/FULL LENGTH FCSHIELD .

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: -109F, -79C

Melt/Freeze Pt: M.P/F.P Text: -70F, -57C

Vapor Pres: 844.7 PSIA

Vapor Density: 0.1144

Solubility in Water: COEFFICIENT = 0.8704

Appearance and Odor: WHITE OPAQUE SOLID; COLORLESS, ODORLESS GAS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

EXPLO CAN OCCUR WHEN CONTACTS MIX OF SODIUM PEROXIDE

W/ALUMINUM/MAGNESIUM. REACTIVE METALS (SUCH AS ALKALI METALS (ING  
2)

Stability Condition to Avoid: DECOMPOSES TO CO & O<sup>2</sup> WHEN HEATED ABOVE  
1700C. WILL REACT W/ALKALINE MATLS TO FORM CARBONATES &  
BICARBONATES.

Hazardous Decomposition Products: CARBON MONOXIDE. FORMS CARBONIC ACID  
IN THE PRESENCE OF WATER.

=====

===== Disposal Considerations =====

Waste Disposal Methods: DISP MUST BE I/A/W FED, STATE & LOCAL REGS.

ALLOW GAS TO BLEED OFF AT MOD RATE/SOLID TO SUBLIME TO WELL VENT  
AREA. INSULATED STOR CNTNR SHOULD BE IN AREA W/ADEQ VENT TO PREVENT  
ACCUM OF CO<sup>2</sup> VAP ABOVE TWA. CO<sup>2</sup> VAP ARE APPROX 1 1/2 TIMES (ING  
13)

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense

se. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.