View NSN Online: https://aerobasegroup.com/nsn/8010-01-374-4337

MCGEAN-ROHCO INC,CEE-BEE CHEMICAL DIV -- CEE-BEE A-477 -- 8010-01-374-4337

Product ID:CEE-BEE A-477 MSDS Date:03/16/1994 FSC:8010 NIIN:01-374-4337 MSDS Number: BVBST === Responsible Party === Company Name: MCGEAN-ROHCO INC, CEE-BEE CHEMICAL DIV Address:9520 E CEE BEE DR **City:DOWNEY** State:CA ZIP:90241-5501 Country:US Info Phone Num:216-441-4900 **Emergency Phone Num:** 216-441-4900/ 800-424-9300 Preparer's Name: GLENN T CARNINE CAGE:71361 === Contractor Identification === Company Name: MCGEAN-ROHCO INC Address:9520 E CEE BEE DR Box:City:DOWNEY State:CA ZIP:90241-5501 Country:US Phone:562-803-4311/FAX: 562-803-6701 CAGE:71361 Ingred Name: MONOETHANOLAMINE CAS:141-43-5 RTECS #:KJ5775000 Fraction by Wt: 42% Other REC Limits: TWA:8 MG/CUBIC METER

Ingred Name:VOC: 844 GM/LITER RTECS #:9999999VO Oth er REC Limits:NONE RECOMMENDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE EFFECTS: CORROSIVE TO SKIN AND EYES. IRRITATING TO RESPIRATORY SYSTEM. CHRONIC EFFECTS: AFFECT TARGET ORGANS. (TARGET ORGANS: SKIN, EYES, LIVER, KIDNEYS) Effects of Overexposure: EYE: BURNING SENSATION. SKIN: STINGING OR BURNING SENSATION. INHALATION: DIZZINESS, HEADACHE. EXPOSURE OF THIS N ATURE UNLIKELY BECAUSE OF ODOR. INGESTION: IRRITATION OR BURNING OF MOUTH AND THROAT. Medical Cond Aggravated by Exposure: DERMATITIS. First Aid: EYE: FLUSH WITH WATER FOR 15 MIN. GET MEDICAL ATTENTION. SKIN: FLUSH WITH WATER FOR 15 MIN. REMOVE CONTAMINATED CLOTHING. IF ANY SYMPTOMS OCCUR, GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIF RESPIRATION. IF BREATHING DIFFICULT , GIVE OXYGEN. GET MEDICAL ATTENTION. INGESTION: IF CONSCIOUS, GIVE TWO GLASSES OF WATER TO DILUTE. DON'T INDUCE VOMITING. GET MED AID. Flash Point:NONE Extinguishing Media:WHATEVER IS APPLICABLE TO TYPE OF FIRE. Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR SHOULD BE WORN. Unusual Fire/Explosion Hazard:NONE KNOWN. \_\_\_\_\_ Spill Release Procedures: SOAK UP WITH SAWDUST, SAND, OIL DRY, OR OTHER ABSORBENT MATERIAL, FLUSH AREA WITH WATER Handling and Storage Precautions: STORE INSIDE @ 32-90F IN WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED. Respiratory Protection: IF TWA IS EXCEEDED, MUST BE NIOSH OR MSHA APPROVED. Ventilation:SUFFICIENT TO KEEP BELOW TW

A LIMIT. Protective Gloves: NEOPRENE OR POLYETHYLENE Eye Protection: CHEMICAL GOGGLES Other Protective Equipment: SUFFICIENT TO PREVENT SKIN CONTACT. EYE WASH. SAFETY SHOWER. Supplemental Safety and Health \* PHYSICAL DATA CONT'D: THIS IS FOR THE LOWER LAYER, PAINT REMOVER, AND NOT THE INERT OIL SEAL. HCC:B2 Boiling Pt:B.P. Text:149F,65C \* Melt/Freeze Pt:M.P/F.P Text:-4F,-20C\* Vapor Pres:0.2-0.3 \* Vapor Density:>1 Spec Gr avity:1.05 \* pH:12-13\* Evaporation Rate & amp; Reference: < BUTYL ACETATE Solubility in Water:COMPLETE \* Appearance and Odor:2-PHASE STRAW COLORED LIQUID, AMINE ODOR Corrosion Rate:NONE Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS, ACIDS. Hazardous Decomposition Products: OXIDES OF CARBON AND NITROGEN. Waste Disposal Methods:SEND TO AN APPROVED W ASTE DISPSOAL FACILITY, OR INCINERATE. FOLLOW ALL LOCAL, STATE, AND FEDERAL REGULATIONS. RCRA # (IF DISPOSED AS RECEIVED): D002.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should se ek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.