

INTERNATIOAL LUBRICANTS CO INC -- LUBRICATING OIL, GENERAL PURPOSE -- 9150-00-965-2400

===== Product Identification =====

Product ID:LUBRICATING OIL, GENERAL PURPOSE

MSDS Date:03/01/1997

FSC:9150

NIIN:00-965-2400

MSDS Number: BVFYD

=== Responsible Party ===

Company Name:INTERNATIOAL LUBRICANTS CO INC

Address:10363 AIRLINE HIGHWAY

City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Info Phone Num:504-46

9-0940/800-424-9300(CHEMTREC)

Emergency Phone Num:504-469-0940/800-424-9300(CHEMTREC)

CAGE:JO811

=== Contractor Identification ===

Company Name:INTERNATIONAL LUBRICANTS INC

Address:10363 W AIRLINE HWY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940(504-471-0104FAX)

CAGE:0W1H4

Company Name:INTERNATIONAL LUBRICATES INC

Address:10363 AIRLINE HIGHWAY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940

CAGE:JO811

Company Name:SALATHE OIL CO INC

Address:2226 PETER

S RD
Box:City:HARVEY
State:LA
ZIP:70058
Country:US
Phone:504-366-4542
CAGE:0T5C6
Company Name:SDB CONSULTANTS LTD
Address:401 WHITNEY AVE SUITE 120
Box:City:GRETNA
State:LA
ZIP:70056
Country:US
Phone:504-366-9105
CAGE:0PGK2

=====
Composition/Information on Ingredients
=====

Ingred Name:SEVERLY HYDROTREATED HEAVY NAPHTHENIC DISTILLATE
CAS:64742-52-5
RTECS #:PY8035000
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes

of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE-THIS PRODUCT IS PRACTICALLY NON-IRRITATING TO THE EYES UPON CONTACT. SKIN-AVOID SKIN CONTACT. THIS PRODUCT MIGHT CAUSE LIGHT SKIN IRRITATION UPON DIRECT CONTACT. INHALATION-THIS PRODUCT HAS A LOW VAPOR PRESSURE & IS NOT EXPCETD TO PRESENT AN INHALATION HAZARD. INGESTION-DO NOT INGEST. THIS PRODUCT IS NON-TOXIC.

Explanation of Carcinogenic

ity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:ON RARE OCASSIONS, PROLONGED AND REPEATED EXPOSURE TO OIL MIST POSES A RISK OF PULMONARY DISEASE SUCH AS CHRONIC LUNG INFALAMMATION. THE CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGH ARE THE MOST COMMON SYMPTOMS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY

MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYE-FLUSH EYES WITH LARGE AMOUNTS OF WATER & CONTINUE FLUSHING UNTIL IRRITATION SUBSIDES. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS & TAKE VICTIM TO HOSPITAL IMMEDIATELY. SKIN-REMOVE CONTAMINATED CLOTHING. WASH AREA THOROUGHLY WITH SOAP & WATER. IF MATERIAL IS HOT, SUBMERGE INJURED AREA IN COLD WATER. INGESTION-DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:500F,260C
Autoignition Temp:Autoignition Temp Text:600F
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:USE DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM AS FROTHING MAY OCCUR
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OF COMBUSTION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:NOTIFY APPROPRIATE AUTHORITIES OF SPILL. CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL TO ENTER SEWERS OR WATER COURSES. REMOVE ALL SOURCES OF IGNITION. ABSORB RELEASED OR WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAMES.
Other Precautions:THIS PRODUCT IS NOT CONSIDERED HAZARDOUS UNDER D.O.T. REGULATIONS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF VAPOR MISTS IS GENERATED WHEN THE

MATERIAL IS HEATED

OR HANDLED, USE AN ORGANIC VAPOR RESPIRATOR WITH A DUST MIST FILTER.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:USE PROTECTIVE GLOVES.

Eye Protection:WEAR PLASTIC FACE SHIELD.

Other Protective Equipment:FOR PROLONGED OR REPEATED HANDLING USE PROTECTIVE CLOTHING (BOOTS, GLOVES, APRONS, ECT.)

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

N

ONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>500F,>260C

Melt/Freeze Pt:M.P/F.P Text:POUR PT 30F

Decomp Temp:Decomp Text:NOT GIVEN

Vapor Pres:NOT GIVEN

Vapor Density:NOT GIVEN

Spec Gravity:0.93

Evaporation Rate & Reference:NOT GIVEN

Solubility in Water:NOT GIVEN

Appearance and Odor:MEDIUM AMBER LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:

d:YES

MAY REACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:ALL DISPOSALS MUST COMPLY WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The U

nited States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.