

NATIONAL DIAGNOSTICS, INC. -- OPTICLEAR E, PRODUCT #:OE-104 -- 6850-01-393-9061
===== Product Identification =====

Product ID:OPTICLEAR E, PRODUCT #:OE-104

MSDS Date:05/10/1992

FSC:6850

NIIN:01-393-9061

MSDS Number: BVGBD

=== Responsible Party ===

Company Name:NATIONAL DIAGNOSTICS, INC.

Address:305 PATTON DRIVE

City:ATLANTA

State:GA

ZIP:30336

Country:US

Info Phone Num:404-699-2121

Emergency Phone

Num:800-424-9300(CHEMTREC)

CAGE:0TMT2

=== Contractor Identification ===

Company Name:NATIONAL DIAGNOSTICS INC

Address:305 PATTON DRIVE

Box:City:ATLANTA

State:GA

ZIP:30336

Country:US

Phone:404-699-2121

CAGE:0TMT2

===== Composition/Information on Ingredients =====

Ingred Name:ALKYL HYDROCARBONS

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:TLV:400PPM TOT HYDROCARBON BASED ON COMP

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: EYE: SLIGHTLY IRRIT BUT DOES NOT INJURE
EYE TISSUE. SKIN: LOW ORDER OF TOXICITY. FREQ/PROL CONTACT MAY
IRRIT. INHAL: HIGH VAP/AEROSOL CONCEN(>1000PPM) IRRIT EYE & RESP
TRACT, CNS EFFECTS INCLUDING DEATH. I NGEST: SM AMTS ASPIRATED INTO
RESP SYS DURING INGEST/VOMIT MAY CAUSE MILD--SEVERE PULM
INJURY, POSSIBLE DEATH. MIN TOXICITY

Effects of Over

exposure: EYE: IRRIT. SKIN: DERMATITIS. INHAL: IRRIT TO EYES
& RESP TRACT, CAUSING HEADACHES, DIZZINESS, ANESTHESIA, DROWSINESS,
UNCONSCIOUSNESS, & OTHER CNS EFFECTS INCLUDING DEATH. INGEST: MILD
TO SEVERE PULMONAR Y INJURY POSSIBLY PROGRESSING TO DEATH.

Medical Cond Aggravated by Exposure: SKIN CONTACT MAY AGGRAVATE AN
EXISTING DERMATITIS CONDITON.

=====
First Aid Measures
=====

First Aid: EYE: FLUSH W/LG AMTS OF WATER. USE SOAP IF AVAILABLE. REMO
VE

GROSSLY CONTAMIN CLOTHING & SHOES. INHAL: USING PROPER RESP
PROTECTION IMMED REMOVE VICTIM FROM EXPOSURE. GIVE ART RES IF
BREATHING STOPPED. KEEP AT REST. CALL FOR PROMTP MED
ATTN. INGEST: DO NOT INDUCE VOMIT. KEEP AT REST. GET PROMPT MED ATTN.

=====
Fire Fighting Measures
=====

Flash Point Method: TCC

Flash Point: =7.2C, 45.F

Autoignition Temp: =382.2C, 720.F

Lower Limits: 1.3

Upper Limits: 10.2 @ 77F

Extinguishing Media: FOAM, DRY CHEMICAL OR WATER

. AVOID SPRAYING WATER

DIRECTLY INTO STORAGE CONTAINERS DUE TO DANGER OF BOIL OVER.

Fire Fighting Procedures: FLAMMABLE LIQUID. KEEP AWAY FROM HEAT, SPARKS
& OPEN FLAME.

Unusual Fire/Explosion Hazard: NOT APPLICABLE.

=====
Accidental Release Measures
=====

Spill Release Procedures: REMOVE IGN SOURCES. STOP LEAK W/O RISK. BEGIN
CLEANUP PROCDURES. KEEP PUBLIC AWAY. ADVISE AUTHORITIES. PREVENT FROM
ENTERING SEWERS/WATERCOURSES/LOW AREAS. CONTAIN SPILL
W/SAND

,EARTH(AVOID COMBUST MATL LIKE SAWDUST).RECOVER W/EXPLOSION
PROOF PUMP.SEE SUPPL

Neutralizing Agent:NONE SPECIFIED BY MFG.

=====
===== Handling and Storage =====

Handling and Storage Precautions:USUAL PRECAUTIONS FOR FLAMMABLE
LIQUIDS.

Other Precautions:ALL HANDLING EQUIPMENT SHOULD BE ELECTRICALLY
GROUNDED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED BUT IF VAPOR CONCENTRATION

BECOMES HIGH, USE SELF-CONTAINED AIR MASK.

Ventilation:LOCAL EXHAUST SHOULD BE ADEQUATE.

Protective Gloves:POLYETHYLENE, NEOPRENE, PVC, PVA.

Eye Protection:CHEMICAL SPLASH GOGGLES, FACE SHIELD.

Other Protective Equipment:USUALLY NOT NEEDED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING. LAUNDER CONTAMINATED
CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WATER SPILL:REMOVE FROM SURFACE BY SKIMMING OR W/SUITABLE ADSORBENTS.

IF ALLOWED BY LOCAL AUTHORITIES & ENVIRONMENTAL AGENCY

SINKING

&/OR USITABLE DISPERSANT MAY BE USED IN NON-CONFINED WATERS. CONS
ULT AN EXPERT ON DISPOSAL OF RECOVERED MATL & ENSURE CONFORMITY TO
LOCAL DISPOSAL REGS.

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=117.8C, 244.F

Vapor Pres:36 @68F

Spec Gravity:0.72 @60F

Viscosity:1CST @ 77F

Evaporation Rate & Reference:1.6, NBU ACETATE=1.

Solubility in Water:NEGLIGIBLE,