

CHEMENCE, INC -- GASKET SEALANT #3, CDA 147 -- 8030-00-656-1426

=====
Product Identification
=====

Product ID:GASKET SEALANT #3, CDA 147

MSDS Date:11/12/1993

FSC:8030

NIIN:00-656-1426

MSDS Number: BVGLQ

=== Responsible Party ===

Company Name:CHEMENCE, INC

Address:6425 INDUSTRIAL WAY

City:ALPHARETTA

State:GA

ZIP:30201

Country:US

Info Phone Num:404-664-6624

Emergency Phone Num:404-664-6624

Preparer

's Name:JAY TATE

CAGE:CLEME

=== Contractor Identification ===

Company Name:CHEMENCE, INC

Address:6425 INDUSTRIAL WAY

City:ALPHARETTA

State:GA

ZIP:30201

Country:US

Phone:404-664-6624

CAGE:CLEME

Company Name:VERSATILE INDUSTRIAL PRODUCTS, INC

CAGE:6Z186

=====
Composition/Information on Ingredients
=====

Ingred Name:VEGETABLE OIL

CAS:68439-93-0

Fraction by Wt: 35-40%

Other REC Limits:* 5 MG/M3(MIST RESP)

OSHA PEL:15 MG/M3(MIST DUST)*

ACGIH TLV:10 MG/M3 (MIST)

Ingred Name:ROSIN

CAS:8050-09-7
Fraction by Wt: 20-25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ISOPROPYL ALCOHOL
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 20-25%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM;STEL 500 PPM
ACGIH TLV:400 PPM;STEL 500 PPM

Ingred Name:TALC
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 15-20%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3 (RESP DUST)
ACGIH TLV:2 MG/M3 (RESP DUST)

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 1-3%
Other REC L
imits:NONE RECOMMENDED

Ingred Name:CLAY
CAS:1332-58-7
RTECS #:GF1670500
Other REC Limits:* 5 MG/M3 RESP
OSHA PEL:10 MG/M3 DUST *
ACGIH TLV:2 MG/M3 DUST

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Other REC Limits:5 PPM
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3

Ingred Name:VOLATILE ORGANIC COMPOUND (EPA METHOD 24): 274 GRAMS PER LITER
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalat

ion:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MODERATELY TOXIC BY INGESTION. EYE
IRRITANT.
Effects of Overexposure:VAPOR ABOVE TLV IS IRRITATING TO EYES, NOSE,
AND THROAT AND CAN CAUSE HEADACHE, DIZZINESS, NAUSEA.
Medical Cond Aggravated by Exposure:SKIN, EYE, AND RESPIRATORY
DISORDERS

===== First Aid Measures =====

First Aid:INGESTION: INDUCE VOMITING. OBTAIN MEDICAL ATTE
NTION.
INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, OBTAIN
MEDICAL ATTENTION. SKIN CONTACT: WASAH WITH SOAP AND WATER. EYE
CONTACT: FLUSH AT LEA ST 15 MINUTES WITH WATER. OBTAIN MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:60.0F,15.6C
Lower Limits:2
Upper Limits:12
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL
Unusual Fire/Explosion Hazard:FORMS IRRITATING ORGANIC VAPORS BY FIRE
OR THERMAL DECOMPOSITION.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION. MAINTAIN ADEQUATE
VENTILATION. SCRAPE UP AS MUCH AS POSSIBLE AND STORE IN A COSED
CONTAINER UNTIL DISPOSAL. RESIDUES MAY BE CLEANED WITH ISOPROPYL
ALCOHOL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT AND FLAME.
Other Precautions:AVOID PROLONGED BREATHING OF V

APORS. KEEP AWAY FROM
EYES. AVOID PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Ventilation:MUST BE ADEQUATE TO AVOID EXCEEDING TLV.
Protective Gloves:RUBBER OR PLASTIC GLOVES
Eye Protection:SAFETY GLASSES OR GOGGLES.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:180F,82C
Vapor Pres:33 @ 68F
Vapor Density:2.07
Spec Gravity:1.1 @ 77F
Evaporation Rate & Refer
ence:7.7 (ETHER=1)
Solubility in Water:PARTIAL
Appearance and Odor:DARK BROWN LIQUID, ALCOHOLIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE FOLLOWING EPA AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information
is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.