View NSN Online: https://aerobasegroup.com/nsn/8010-01-350-2071

CRAWFORD LABORATORIES, INC. -- MIL-C-22750E ACTIVATOR, PART B, P/N UO-135 8010-01-350-2071

Product ID:MIL-C-22750E ACTIVATOR, PART B, P/N UO-135 MSDS Date:05/18/1994 FSC:8010 NIIN:01-350-2071 Kit Part:Y MSDS Number: BVGTD === Responsible Party === Company Name: CRAWFORD LABORATORIES, INC. Address:4165 SOUTH EMERALD AVENUE City:CHICAGO State:IL ZIP:60609 Countr v:US Info Phone Num:312-376-7132 Emergency Phone Num:800-424-9300 CHEMTREC Preparer's Name: DAVID SCHMETTERER CAGE:DO165 === Contractor Identification === Company Name: CRAWFORD LABORATIES, INC Address:4165 SOUTH EMERALD AVENUE City:CHICAGO State:IL ZIP:60609 Phone:800-424-9300 CHEMTREC CAGE:DO165 Company Name: CRAWFORD LABORATORIES, INC Address:4165 SOUTH EMERALD AVENUE Box:City:CHICAGO State:IL ZIP:60609 Country:US Phone:312-376-7132 CAGE:5V430

======= Composition/Information on Ingredien

Ingred Name: METHYL ETHYL KETONE (SARA III) (VAPOR PRESSURE 71.2 MM HG) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 46% Other REC Limits:NONE RECOMMENDED OSHA PEL:100 PPM ACGIH TLV:200 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ingred Name: PHENYL CARBINOL CAS:100-51-6 RTECS #:DN3150000 Fraction by Wt: 20% Other REC Limits:NONE RECOMMENDED Ingred Name: BENZALDEHYDE (MAY BE CONTAINED [0.3%] AS AN IMPURITY IN PHENYL CARBINOL) CAS:100-52-7 RTECS #:CU4375000 Other REC Limi ts:NONE RECOMMENDED

Ingred Name:DIBENZYL ETHER (MAY BE CONTAINED [0.1%] AS AN IMPURITY IN PHENYL CARBINOL) CAS:103-50-4 RTECS #:DQ6125000 Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE MONOMETHYL ETHER (MAY BE CONTAINED [0.025%] AS AN IMPURITY IN PHENYL CARBINOL) CAS:150-76-5 RTECS #:SL7700000 Other REC Limits:NONE RECOMMENDED

Ingred Name:REACTION PRODUCTS OF EPICHLOROHYDRIN & BISPHENOL A CAS:25085-99-8 Fraction by Wt: 8.9% Other REC Limits:NONE RECOMMENDED

Ingred Name:NH

2CH2CH(CH3)(CH2)3NH2 (VAPOR PRESSURE 130 MM HG) CAS:15520-10-2 RTECS #:SA0248500 Fraction by Wt: 23% Other REC Limits:NONE RECOMMENDED Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: OVEREXPOSURE MAY PRODUCE VARIOUS EFFECTS, INCLUDING: ACUTE TOXICITY (HEADACHE, DIZZINESS, NAUSEA, UNCONSCIOUSNESS). SEVERE EYE IRRITATION (POSSIBLY PERMANENT DAMAGE). IRRITATED MUCOUS MEMBRANES. V OMIT ING DUE TO INGESTION. DEFATTING & DRYING OF SKIN. SENSITIZATION AFTER REPEATED CONTACT. First Aid:EYE:FLUSH W/LUKEWRM LOW PRESSR H2O 15 MIN,LIFT EYELID.GET MED AID.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN IF BREATH DIFFICLT.GIVE ARTIF RESP, IF NO BREATH.GET MED AID.KEEP WARM/COMFRTBL.NEVER GIVE UNCONS CIOUS LIQ.INGEST:CALL DR IMMED.INDUCE VOMIT ON DR'S INSTRCTN.IF VOMIT.KEEP HEAD BELOW HIP.NEVER GIVE ANYT HING TO UNCONSCIOUS.SKIN:FLUSH W/H2O REMOVING CONTAM CLOTH.WASH W/SOAP&H2O.GET MED AID IF IRRIT Flash Point Method:SCC Flash Point:22.0F,-5.6C Lower Limits:2. Extinguishing Media: FOAM, CO2, OR DRY CHEMICAL Fire Fighting Procedures:WATER MAY BE USED TO COOL EXPOSED CONTAINER, & TO KEEP FLAMMABLE STRUCTURES WET. DON'T ENTER FIRE AREA WITHOUT PROTECTION BECAUSE DECOMP PRODUCT MAY BE PRESENT. **Unusual Fire/Explosio** n Hazard:WATER PRESSURE MAY SPREAD A FLAMMABLE LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVERHEATED. Spill Release Procedures: WARNING - FLAMMABLE. ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. SOAK UP WITH AN ABSORBENT AND PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTLY FOR PROPER DIS POSAL.

Handli

ng and Storage Precautions:FLAMMABLE. KNOW DOT REGS BEFORE TRANSPORTING.WARNING:HOT ORGANIC CHEMICAL VAPOR OR MIST SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED W/AIR. Other Precautions:IGNIT MAY OCCUR AT TEMP BELOW AUTOIGNIT/IGNIT TEMPS.IGNIT TEMPS DECREASE W/INCREASING VAPOR VOLUME & VAPOR/AIR CONTACT TIME & INFLUENCED BY PRESSR CHANGE.IGNIT MAY OCCUR AT ELEVATED TEMP,ESPECIALLY IN VACUUM IF SUDDEN INGRESS AIR OR \*

======= Exposure Controls/Personal Prote

ction ===========

Respiratory Protection: IMPORTANT-MUST PROVIDE ADEQUATE VENTILATION TO MAINTAIN VAPOR CONCENTRATIONS BELOW ESTABLISHED TLV LIMIT AS GIVEN BY OSHA. IN MORE CONFINED AREAS NIOSH-MSHA APPROVED RESPIRATOR EQUIPPED WITH ORGANIC V APOR CARTRIDGE SHOULD BE WORN. Ventilation: MUST PROVIDE ADEQUATE VENTILATION. SEE PARAGRAPH ON **RESPIRATORY PROTECTION.** Protective Gloves: USE RUBBER GLOVES. Eye Protection: WEAR APPROVED SAFETY GOGGLES OR FACESHLD Other Protective Equipment :HAVE EYE BATH AND SAFETY SHOWER AVAILABLE. Work Hygienic Practices: DO NOT REUSE CONTAMINATED CLOTHING OR SHOES. Supplemental Safety and Health \* OUTSIDE PROCESS EQUIPMENT OPERATING UNDER ELEVATED PRESSURE IF SUDDEN ESCAPE OF VAPOR OR MIST TO THE ATMOSPHERE OCCURS. ANY PROPOSED USE SHOULD BE THOROUGHLY EVALUATED TO ASSURE THAT SAFE OPERATING CONDITIONS ARE ESTABLISHED AND MAINTAINED.

HCC:F3 Boiling Pt:B.P. Text:1 74 TO 401F Vapor Density:> AIR Spec Gravity:0.86 Viscosity:65 KU Evaporation Rate & amp; Reference:3.19 X N-BU AC Solubility in Water:SLIGHT Appearance and Odor:CLEAR LIQUID / SOLVENT ODOR Percent Volatiles by Volume:73.3 Corrosion Rate:NOT CORR

Stability Indicator/Materials to Avoid:YES MAY BE INCOMPATIBLE WITH OXIDIZING AGENT AND STRONG ALKALIES. Stability Condition to Avoid:AVOID HEAT, SPARKS, AND OPEN FLAMES. Hazardous Deco mposition Products:INCOMPLETE COMBUSTION FOR PRODUCTS LIKE THIS MAY GENERATE HIGH POISONOUS CARBON MONOXIDE AND OTHER TOXIC GASES.

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE, AND FEDERAL REGULATION. CONTACT AN APPROVED DISPOSAL FACILITY. EPA HAZARDOUS WASTE CODE: D001, IGNITABLE.

Disclaimer (provided with this information by the compiling agencies): This information is fo

rmulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.