

S.C. JOHNSON WAX -- BRAVO EXTRA HEAVY DUTY STRIPPER -- 7930-01-380-8341

=====  
Product Identification  
=====

Product ID: BRAVO EXTRA HEAVY DUTY STRIPPER

MSDS Date: 08/14/1993

FSC: 7930

NIIN: 01-380-8341

MSDS Number: BVGTS

=== Responsible Party ===

Company Name: S.C. JOHNSON WAX

City: RACINE

State: WI

ZIP: 53403-5011

Country: US

Info Phone Num: 800-725-6737

Emergency Phone Num: 800-228-5635 EXT 092

CAGE: GO050

=== Contractor Identification ===

Company Name: S C JOHNSON & SON INC/PROF WAX DIV

Address: 1525 HOWE ST

City: RACINE

State: WI

ZIP: 53403

Country: US

Phone: 800-725-6737/414-886-1480 INTNL#

CAGE: 0U826

Company Name: S.C. JOHNSON WAX CORP.

Address: 1525 HOWE ST

City: RACINE

State: WI

ZIP: 53403-2237

Phone: 414-631-2488

CAGE: GO050

=====  
Composition/Information on Ingredients  
=====

Ingred Name: MONOETHANOLAMINE (LD50: 2050 MG/KG [ORAL,RAT])

CAS: 141-43-5

RTECS #: KJ5775000

Fraction by Wt: 3-6%

Other REC Limits:NONE RECOMMENDED  
OSHA PEL:3 PPM; STEL 6 PPM  
ACGIH TLV:3 PPM; STEL 6 PPM

Ingred Name:SODIUM SILICATE (LD50: 1300 - 2600 MG/KG [ORAL-RAT])  
CAS:1344-09-8  
Fraction by Wt: 3-6%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM HYDROXIDE (LD50: 140-340 MG/KG [ORAL-RAT]; LC50: >40  
MG/M3/1 HR [INHALATION-RAT])  
CAS:1310-73-2  
RTECS #:WB4900000  
Fraction by Wt: 3-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 MG/M3 CEILING  
ACGIH TLV:2 MG/M3 CEILING  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty  
:1000 LBS

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 75-90%  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:ACUTE ORAL EST LD50: >5000 MG/KG (RAT)  
Health Hazards Acute and Chronic:EYES: CORROSIVE: MAY CAUSE PERMANENT  
EYE DAMAGE. SKIN: CORROSIVE: MAY CAUSE CHEMICAL BURNS. INHALTION:  
MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT. INGESTION: CORROSIVE  
TO MOUTH AND DIGESTIVE TRACT.

Medical  
Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN  
DISORDERS MAY BE MORE SUSCEPTIBLE TO IRRITATING EFFECTS.

=====  
===== First Aid Measures =====

First Aid:IF EYE CONTACT OCCURS,REMOVE CONTACT LENSES. FLUSH  
IMMEDIATELY WITH WATER FOR 20 MIN. GET IMMEDIATE MEDICAL ATTENTION.  
GO TO EMERGENCY ROOM BUT WASH EYE FIRST. SKIN: RINSE WITH PLENTY OF  
WATER. IF IRR ITATION PERSISTS, GET MEDICAL ATTENTION. INHALATION:  
REMOVE TO FRESH AIR. INGESTIO

N: DON'T INDUCE VOMITING. DRINK 1-2  
GLASSES WATER/MILK. NOTHING BY MOUTH TO UNCONSCIOUS PERSON. GET  
IMMED MEDICAL AID.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG  
Fire Fighting Procedures:NORMAL FIRE FIGHTING PROCEDURES MAY BE USED.  
COOL AND USE CAUTION WHEN APPROACHING OR HANDLING FIRE-EXPOSED  
CONTAINERS.  
Unusual Fire/Explosion Hazard:CORROSIVE MATERIAL

===== Accidental Release Measu  
res =====

Spill Release Procedures:ABSORB WITH OIL-DRI OR SIMILAR INERT MATERIAL.  
SWEEP OR SCRAPE UP AND CONTAINERIZE. RINSE AFFECTED AREA THOROUGHLY  
WITH WATER. WEAR/USE APPROPRIATE PROTECTIVE EQUIPMENT.

===== Handling and Storage =====

Handling and Storage Precautions:WARNING:CORROSIVE. CONTAINS CAUSTIC  
ALKALI AND MONOETHANOLAMINE. AVOID CONTACT. MAY BURN SKIN & DAMAGE  
EYES. HARMFUL IF SWALLOWED. FOR INDUSTRIAL USE.

Other Preca  
utions:WHEN HANDLING CONCENTRATE, WEAR EYE PROTECTION &  
RUBBER GLOVES. STORE IN A COOL, DRY PLACE WITH ADEQUATE  
VENTILATION. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED  
CLOTHING/EQUIPMENT BEFORE REU SE. KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF MISTS/VAPORS ARE NOT ADEQUATELY CONTROLLED BY  
LOCAL VENTILATION, USE APPROPRIATE RESPIRATORY PROTECTION TO  
PREVENT OVEREXPOSURE.

Ventilation:  
GENRL ROOM VENT NORMALLY ADEQUATE.SUBSTANTIAL AMTS OF  
MIST/VAPOR CAN BE CONTROLLED W/LOCAL EXHAUST VENT OR RESP PROTECTN.

Protective Gloves:WEAR LONG RUBBER GLOVES

Eye Protection:UNDILUTED: CHEMICAL SPLASH PROOF GOGGLES

Other Protective Equipment:IF MAJOR EXPOSURE IS POSSIBLE TO EYES/SKIN,  
WEAR/USE APPROPRIATE PROTECTIVE EQUIPMENT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C  
Melt/Freeze Pt:M.P/F.P Tex

t:32.0F,0.0C

Spec Gravity:1.1

pH:12.8MN

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, MILD CITRUS ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS (MURIATIC ACID). STRONG OXIDIZING MATERIALS (LIQUID CHLORINE). AVOID CONTACT W/NON-FERROUS METAL.

Stability Condition to Avoid:NONE KNOWN

Hazardous Decomposition Products:PRODUCES NORMAL PRODUCTS OF COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OF UNDILUTED PRODUCT IS REGULATED UNDER ENVIRONMENTAL AND TRANSPORTATION LAWS AS A CORROSIVE WASTE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.