View NSN Online: https://aerobasegroup.com/nsn/7930-01-380-8514

## 

Product ID:FREEDOM SPEED STRIPPER

MSDS Date:06/14/1994

FSC:7930

NIIN:01-380-8514

MSDS Number: BVGWL === Responsible Party ===

Company Name: S.C. JOHNSON WAX

City:RACINE State:WI

ZIP:53403-5011 Country:US

Info Phone Num:414-631-2777

Emergency Phone Num:800-228-5635 EXT 092

Preparer's Name:TERRY A MEYER

S

CAGE:GO050

=== Contractor Identification ===

Company Name: S C JOHNSON & SON INC/PROF WAX DIV

Address:1525 HOWE ST

City:RACINE State:WI ZIP:53403 Country:US

Phone:800-725-6737/414-886-1480 INTNL#

CAGE:0U826

Company Name: S.C. JOHNSON WAX CORP.

Address:1525 HOWE ST

City:RACINE State:WI

ZIP:53403-2237 Phone:414-631-2488

CAGE:GO050

======= Composition/Information on Ingredients ========

Ingred Name: MONOETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000 Fraction by Wt: 6-10% Other REC Limits :NONE RECOMMENDED

OSHA PEL:3 PPM; STEL 6 PPM ACGIH TLV:3 PPM; STEL 6 PPM

Ingred Name: SODIUM XYLENE SULFONATE

CAS:1300-72-7 Fraction by Wt: 3-8%

Other REC Limits: NONE RECOMMENDED

Ingred Name: ETHYLENE GLYCOL PHENYL ETHER

CAS:122-99-6

RTECS #:KM0350000 Fraction by Wt: 10-15%

Other REC Limits: DOW TLV: 25 PPM

Ingred Name: BUTYL PROPASOL

CAS:5131-66-8

RTECS #:UA7700000 Fraction by Wt: 1-6%

Other REC Limits: NONE RECOMMENDED

Ingred Name: SODIUM SILICATE

CAS:1344-09-8 Fraction by Wt: 1-4% Other REC Lim

its:NONE RECOMMENDED

Ingred Name: POLYOXYETHYLENE PHENYL ETHER PHOSPHATE

CAS:39464-70-5 Fraction by Wt: 1-3%

Other REC Limits: NONE RECOMMENDED

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 60-70%

Other REC Limits: NONE RECOMMENDED

Ingred Name: VOC AS PACKAGED, MINUS H2O: BUTYL PROPASOL 0.26 LBS/GAL

(THEORETICAL VOC)
RTECS #:9999999VO

Other REC Limits: NONE RECOMMENDED

=========== Hazards Identification ==============

Health Hazards Acute and Chronic:DI

## RECT CONTACT OF PRODUCT WITH EYES

CAN CAUSE SEVERE IRRITATION AND DAMAGE. DIRECT CONTACT OF PRODUCT WITH SKIN CAN CAUSE IRRITATION. IF TAKEN INTERNALLY, PRODUCT MAY CAUSE CORROSIVE DAMAGE TO MOUTH, THROAT, OR STOMACH.

Medical Cond Aggravated by Exposure: CHRONIC RESP DISORDERS
(ASTHMA, CHRONIC BRONCHITITS, EMPHYXEMA, ETC) MAY BE ADVERSELY
AFFECTED BY EXPOSURE TO ANY VAPOR OR AIRBORNE PARTICLE. PRE-EXISTING
SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO IRRITTN

==== First Aid Measures ==========

First Aid:IF EYE CONTACT OCCURS, FLUSH EYES WITH WATER FOR 15-20 MIN, THEN GET PROMPT MEDICAL AID. IF PRODUCT IS SWALLOWED, DO NOT INDUCE VOMITING. SEEK MEDICAL AID AT ONCE. IF PRODUCT IS SWALLOWED, DRINK LARGE QUANTITIES OF WATER OR MILK AND SEEK MEDICAL AID.

=========== Fire Fighting Measures ==========================

## Flash Point:NONE

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures: NORMAL

FIRE FIGHTING PROCEDURES MAY BE USED.

COOL & USE CAUTION WHEN APPROACHING OR HANDLING FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CORROSIVE MATERIAL. VAPOR MAY ACCUMULATE IN CONFINED SPACES (E.G., PITS, SUMPS, SEWERS) AND INADEQUATELY VENTILATED AREAS.

======== Accidental Release Measures ===========

Spill Release Procedures:DIKE LRG SPILLS. ABSORB WITH OIL-DRI OR SIMILAR INERT MATERIAL. SWEEP OR SCRAPE UP AND CONTAINERIZE. RINSE AFFECTED A

REA THOROUGHLY WITH WATER. WEAR/USE APPROPRIATE PROTECTIVE EQUIPMENT.

============= Handling and Storage ==========================

Handling and Storage Precautions: WARNING: CONTAINS ALKALI DETERGENT.
CAN CAUSE EYE DAMAGE. AVOID CONTACT WITH EYES, SKIN & CLOTHING.
HARMFUL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN

Other Precautions:WHEN HANDLING CONCENTRATE, WEAR EYE PROTECTION & RUBBER GLOVES. PRODUCT RESIDUE MAY REMAIN ON/IN EMPTY CONTAINERS. ALL PRECAUTIONS FOR HAN

Melt/Freeze Pt:M.P/F.P Text: