View NSN Online: https://aerobasegroup.com/nsn/6750-01-353-8701

Product ID:24022-91 FUJI AUDEL INDUSTRIAL X DEVELOPER, ITEM PT-A #1505 MSDS Date:08/15/1993 FSC:6750 NIIN:01-353-8701 Kit Part:Y MSDS Number: BVHMR === Responsible Party === Company Name: ALLIED PHOTO PRODUCT CO, SUB OF ALLIED PRODUCT CORP Address:5440-A OAKBROOK PKY City:NORCROSS State:GA ZIP:30093-2251 Country:US Info Phone Num:404-448-0250 Emergency Phone Num:800-424-9300(CHEMTREC) CAGE:1CG79 === Contractor Identification === Company Name: ALLIED PHOTO PRODUCT CO, SUB OF ALLIED PRODUCT CORP Address:5440-A OAKBROOK PKY Box:City:NORCROSS State:GA ZIP:30093-2251 Country:US Phone:770-448-0250 CAGE:1CG79 Company Name: FUJI MEDICAL SYSTEMS USA INC Address:1540 W NORWOOD AVE Box:City:ITASCA State:IL ZIP:60143 Country:US Phone:312-7 73-3360 CAGE:8Y572 Ingred Name: POTASSIUM HYDROXIDE (CERCLA) CAS:1310-58-3 RTECS #:TT2100000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:C 2 MG/M3 ACGIH TLV:C 2 MG/M3; 9495 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:SODIUM SULFITE CAS:7757-83-7 RTECS #:WE2150000 Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM METABORATE TETRAHYDRATE CAS:7775-19-1 RTECS #:ED4640000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA) CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9495 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 50-55% Other REC Limits:NONE RECOMMENDED

=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHAL:LOW HAZARD FOR ORDINARY INDUSTRIAL HANDLING. EYES:VAPORS MAY CAUSE IRRIT. SKIN:REPEATED/PROLONGED CONTACT MAY CAUSE IRRIT. INGEST:POISON. DO NOT TAKE INTERNALLY. MAY CAUSE NAUSEA. Explanation of Carcinogenicity:PER MSDS:EVIDENCE OF CARCINOGEICITY:NONE SPECIFIED BY MANUFACTURER. Effects of Overexposure:EYE IRRIT, SKIN IRRIT. POISON IF INGEST. NAUSEA. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:SKIN:THOROUGHLY WASH EXPO AREA W/SOAP/WATER.REMOVE CONTAMIN CLOTH. EYES:IMMED FLUSH W/WATER,LIFTING UPPER/LOWER EYELIDS OCCASIONALLY.GET MED ATTN. INGEST:IMMED DRINK 2 GLASSES OF WATER & INDUCE VOMITI NG BY EITHER GIVING IPECAC SYRUP OR BY PLACING FINGER @BACK OF THROAT.NEVER GIVE ANYTHING BY MOUTH IF UNCONSC.GET MED ATTN IMMED. INHAL:REMOVE INDIVIDUAL TO FRESH AIR.

Flash Point:242F,117C Extinguishing Media:USE METHOD APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:USE PROTECTIVE CLOTHING TO PREVENT CONTACT W/SKIN/EYES.

Unusual Fire/Explosion Hazard:WHEN HEATED TO DECOMPOSITION IT CAN EMIT TOXIC FUMES

OF SO2.

Spill Release Procedures:WEAR PROTECTIVE CLOTHING AS SPECIFIED IN MSDS. NEUTRALIZE WITH SODIUM BICARBONATE. IF FED/STATE/LOC LAWS PERMIT FLUSH TO SEWER W/LG AMTS OF WATER. Neutralizing Agent:SODIUM BICARBONATE.

Handling and Storage Precautions:DO NOT STORE/CONSUME FOOD/DRINK/TOBACCO IN SURROUNDING AREA.KEEP AWAY FROM HEAT/FLAME.KEEP A WAY FROM ALKALIS,AMINES,ALCOHOLS,STRONG OXIDIZERS. Other Precautions:NONE SPECIFIED BY MANUFACTURER.

Respiratory Protection: SHOULD NOT BE NECESSARY UNDER NORMAL CONDITIONS. IF EXPOSED TO VAPORS THAT EXCEED TLV OR PEL WEAR APPROVED VAPOR RESPIRATOR.

Ventilation: NONE SPECIFIED BY MANUFACTURER.

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: PROTECTIVE GOGGLES.

Other Protective Equipment: AS NECESSARY TO PREVENT SKIN C ONTACT.

EYEWASH FACILITIES IN VICINITY OF USE.

Work Hygienic Practices: LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH THOROUGHLY AFT USE.

Supplemental Safety and Health

DISPOSAL:ASCERTAIN PROPER DISPOSAL PROCEDURES. 4-PART KIT,PER TIR:UNIT PKG YIELDS 75 LITERS.SEE SAME NSN PNIND:B,C,D FOR PARTS B,C,D,RESPECTIVELY.KEY1:C4.

HCC:B3 Boiling Pt:>100.C, 212.F B.P. Text:>212F,>100C Vapor Pres:17.0 Vapor Density:0.6 Spec Gravity:1.29 pH:10.90 Solubility in Water:COMPLETE. Appearance and Odor:OFF WHITE, ODORLESS. Percent Volatiles by Volume:55

Stability Indicator/Materials to Avoid:YES
ALKALI, AMINES, ALCOHOLS, STRONG OXIDIZERS, MINERAL AICDS.
Stability Condition to Avoid:KEEP AWAY FROM HEAT OR FLAME. KEEP AWAY
FROM ALKALIS, AMINES, SLCOHOLS, STRONG OXIDIZERS.
Hazardous Decomposition Products:WHEN HEATED TO DECOMPOSITION IT CAN EM

IT TOXIC FUMES.WILL PRODUCE CO2 & POSSIBLY CO, SO2.

Waste Disposal Methods:NEUTRALIZE W/SODIUM BICARBONATE.FED/STATE &/OR LOC LAWS PERMIT FLUSH TO SEWER W/LG AMTS OF WATER.OTHERWISE DISPOSE OF CONTAMIN PROD/MATLS USED IN SPILL CLEANUP IN MANNER APPROVED FOR MATL.CONSULT PROP ER FED/STATE &/OR LOC REG AGENCIES TO (SUPPLEMENT)

Disclaimer (provided with this information by the compiling agencies): This informat

ion is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.