

SHERWIN-WILLIAMS CO -- 1501 GLOSSY WHITE, INDUSTRIAL MAINTENANCE (SUPDAT) --
8010-00-132-2865

===== Product Identification =====

Product ID:1501 GLOSSY WHITE, INDUSTRIAL MAINTENANCE (SUPDAT)

MSDS Date:01/05/1994

FSC:8010

NIIN:00-132-2865

MSDS Number: BVMYM

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS CO

Address:101 PROSPECT AVE NW

City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Info

Phone Num:800-247-3266

Emergency Phone Num:216-292-7400

CAGE:54636

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS CO THE

Address:101 PROSPECT AVE NW

Box:City:CLEVELAND

State:OH

ZIP:44115-1042

Country:US

Phone:800-251-2486/216-566-2242

CAGE:54636

===== Composition/Information on Ingredients =====

Ingred Name:PROPANE (PROPELLANT). VP:760

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 13%

OSHA PEL:1000 PPM

ACGIH TLV:ASPHYXIAN

Ingred Name:PROPANE, 2-METHYL-; (2-

METHYLPROPANE (PROPELLANT)). VP:760

CAS:75-28-5

RTECS #:TZ4300000

Fraction by Wt: 7%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:BENZENE, ETHYL-; (ETHYLBENZENE) (SARA 313). VP:7.1

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 2%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/125 STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE (SARA 313) (CERCLA). VP:59

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 11%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

I

ingred Name:BUTYL ALCOHOL; (1-BUTANOL) (SARA 313) (CERCLA). VP:55

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 2%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE (SARA 313) (CERCLA). VP:180

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 36%

OSHA PEL:1000 PPM

ACGIH TLV:750PPM/1000STEL

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTANONE; (METHYL ETHYL KETONE) (MEK) (SARA 313)
(CERCLA). VP:700

CAS:78-93-3

RTECS #:EL6475000

Fract

ion by Wt: 4%
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID, 2-METHOXY-1-METHYLETHYL ESTER;
(1-METHOXY-2-PROPANOL ACETATE). VP:18
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 7%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE)
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 7%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:VOLATILE ORGANIC CONTENT AS A PERCENT BY WT PER BAAQMD RULE
49:81
RTECS #:99
99999VO
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:SUPDAT:FROM SUNLIGHT, RADIATORS, STOVES, HOT WATER, & OTHER
HEAT SOURCES COULD CAUSE CNTNR TO BURST. DO NOT TAKE(ING 12)
RTECS #:9999999ZZ

Ingred Name:ING 11:INTERNALLY. KEEP OUT OF REACH OF CHILDREN.
INTENTIONAL MISUSE BY DELIB CONC & INHAL CONTENTS CAN BE (ING 13)
RTECS #:9999999ZZ

Ingred Name:ING 12:HARMFUL OR FATAL. USE ONLY W/ADEQ VENT. AVOID BRTHG
VAP & SPRAY MIST. AVOID CONT W/SKIN & EYES. WASH (ING 14)
RTECS #:9999999ZZ

Ing

red Name:ING 13:HANDS AFTER USING. THIS COATING MAY CONTAIN MATLS
CLASSIFIED AS NUISANCE PARTICULATES LISTED "AS DUST" IN(ING 15)
RTECS #:9999999ZZ

Ingred Name:ING 14:IN INGREDIENTS WHICH MAY BE PRESENT AT HAZ LEVELS ONLY
DURING SANDING/ABRADING OF DRIED FILM. IF NO SPECIFIC (ING 16)
RTECS #:9999999ZZ

Ingred Name:ING 15:DUSTS ARE LISTED IN INGREDIENTS, APPLICABLE LIMITS FOR NUISANCE
DUSTS ARE ACGIH TLV 10 MG/M3 (TOTAL DUST). OSHA PEL (ING 17)
RTECS #:9999999ZZ

Ingred Name:ING 16:15 MG/M3) TOTAL DU
ST; 5 MG/ML (RESPIRABLE FRACTION).
RTECS #:9999999ZZ

Ingred Name:EYE PROT:GENERATED FROM THIS PRODUCT, UNDERLYING PAINT, OR
ABRASIVE.
RTECS #:9999999ZZ

Ingred Name:ING 18: INCINERATE, OR EXPOSE TO TEMPS >120F. KEEP FROM
SUNLIGHT, RADIATORS, STOVES, HOT WATER, & OTHER HEAT (ING 20)
RTECS #:9999999ZZ

Ingred Name:ING 19: SOURCES COULD CAUSE CONTAINER TO BURST. DO NOT TAKE
INTERNALLY. KEEP OUT OF REACH OF CHILDREN. THIS COATING (ING 21)
RTECS #:9999999ZZ

Ingred Name:ING 20:MAY CONTAIN MATERIALS CLASSIFIED AS NUISANCE PARTICULATES
WHICH MAY BE PRESENT AT HAZ LEVELS ONLY DURING SANDING(ING 22)
RTECS #:9999999ZZ

Ingred Name:ING 21:OR ABRADING OF DRIED FILM. IF NO SPECIFIC DUSTS ARE
LISTED IN INGREDIENTS, APPLICABLE LIMITS FOR NUISANCE (ING 23)
RTECS #:9999999ZZ

Ingred Name:ING 22: DUSTS ARE ACGIH TLV 10 MG/M3 TDUST, OSHA PEL 25
MG/M3 (TDUST), 5 MG/M3 (RESP)
RTECS #:9999999ZZ

Ingred Name:RESP PROT: WHICH MAY BE GENERATED FROM THIS PRODUCT,
UNDERLYING PAINTS, OR THE ABRASIVE.

RTECS #:9999999ZZ

Ingred Name:VENT: EXPOSURE LIMITS. REFER TO OSHA STANDARDS 1910.94,
1910.107, 1910.108.

RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRIT TO EYES, SKIN & RESP SYS.

MAY CAUSE NERV SYS DEPRESS. EXTREME OVEREXP MAY RSLT IN UNCON &

POSSIBLY DEATH. SIGNS & SYMP OF OVEREXP:HDCH, DIZZ, NAUS, & LOSS OF
COORDINATION ARE INDICATIONS O F EXCESS EXPOS TO VAP/SPRAY MISTS.
REDNESS & ITCHING/BURNING SENSATION MAY INDICATE EYE/EXCESS SKIN
(EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:EXPOS. CHRONIC:PRLNGD OVEREXP TO SOLV
INGREDS MAY CAUSE ADVERSE EFTS TO LIVER, URINARY, BLOOD-FORMING,
CARDIOVASCULAR, & REPROD SYS. METHYL-ETHYL KETONE MAY INCREASE NERV
SYS EFTS

OF OTHER SO LV. RPTS HAVE ASSOC RPTD & PRLNGD OVEREXP TO

SOLV W/PERM BRAIN & NERV SYS DAMAGE.

Medical Cond Aggravated by Exposure:NONE.

===== First Aid Measures =====

First Aid:INHAL:REMOVE FROM EXPOSURE. RESTORE BRTHG. KEEP WARM & QUIET.

SKIN:WASH AREA THORO W/SOAP & WATER. REMOVE CONTAMD CLTHG & LAUNDER
BEFORE RE-USE. EYES:FLUSH W/LG AMTS OF WATER FOR @ LEAST 15 MINS.

GET MED ATTN. INGEST:GET MEDICAL ATTENTION.

===== F
ire Fighting Measures =====

Flash Point Method:PMCC

Flash Point: