

COURTAULDS AEROSPACE, INC -- PR-1440 B-4, BASE -- 8030-00-850-0758

=====
Product Identification
=====

Product ID:PR-1440 B-4, BASE

MSDS Date:10/21/1993

FSC:8030

NIIN:00-850-0758

MSDS Number: BVNDY

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE, INC

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060 / 818-549-7825

Emergency

Phone Num:800-228-5635/800-424-9300 CHEMTREC

Preparer's Name:SEROJE HARTOONIANI

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====
Composition/Information on Ingredients
=====

Ingred Name:TITANIUM DIOXIDE (LISTED AS REQ'D BY 29 CFR1910.1200, FULLY
ENCAPSULATED, NOT HAZARDOUS UNDER NORMAL USE)

C

AS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 3.140%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:CALCIUM CARBONATE(LIMESTONE)(LISTED AS REQ'D BY 29CFR
1910:1200,FULLY ENCAPSULATD,NOT HZDOUS UNDER NORMAL CIRCUMSTANCES)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 30.421%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:15.0 MG/M3

ACGIH TLV:10.0 MG/M3

Ingred Name:TOLUENE (SARA III) (VAPOR PRESSURE 23 MM HG)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt:

0.978%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM;STEL 150 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:POLYSULFIDE POLYMER (NON-HAZARDOUS)
CAS:68611-50-7
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA DERIVATIVES (NON HAZARDOUS INGREDIENT)
CAS:67762-90-7
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC PER EPA METHOD 24: 35 G/L (COMBINED PART A & B)
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE BURNING, TEARING,
REDDENING. SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING & CRACKING OF
SKIN & DERMATITIS. INHALATION: MAY CAUSE DIZZINESS, DROWSINESS, &
FATIGUE. MAY CAUSE LIVER & KIDNEY DAMAGE. INGESTION: DROWSINESS,
DIZZINESS, & NAUSEA. CHRONIC: DISTURBANCE IN MEMORY, THINKING,
EMOTIONS & COORDINATION.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER. IF SYMPTOMS PERSIST, CONSULT A
PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSISTS,
CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS
ARE PRESENT, CONSULT A PHYSICIAN. INGESTION: DRINK LARGE AMOUNTS
OF WATER; INDUCE VOMITING; CONSULT A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:>200F,>93C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY.

Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR.

Unusual Fire/Explosion Hazard:NONE KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP INTO CONTAINERS. CLEAN-UP RESIUDE WITH A
SUITABLE SOLVENT. CERCLA RQ FOR TOLUENE IS 1,000 LBS.

===== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING A
ND
BEFORE SMOKING OR EATING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:GENERAL VENTILATION.

Protective Gloves:SOLVENT RESISTANT GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE KNOWN

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
SMOKING OR EATING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:230 TO
350F

Vapor Density:> AIR

Spec Gravity:1.571

Viscosity:10500P#7@2RPM

Evaporation Rate & Reference:< N-BUTYL ACETATE

Solubility in Water:SLIGHT

Appearance and Odor:BEIGE THIXOTROPIC PASTE

Percent Volatiles by Volume:3.3

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN

Stability Condition to Avoid:NOT KNOWN

Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE,
TRACES OF HYDROGEN SULFIDE.

=====

===== Disposal Considerations =====

Waste Disposal Methods: NOT A HAZARDOUS WASTE ACCORDING TO EPA REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.