

GRAPHITE PRODUCTS CORP -- MINERAL OIL MIL-L-17672B -- 9150-00-404-6055
===== Product Identification =====

Product ID:MINERAL OIL MIL-L-17672B
MSDS Date:04/24/1986
FSC:9150
NIIN:00-404-6055
MSDS Number: BVPYY
=== Responsible Party ===
Company Name:GRAPHITE PRODUCTS CORP
Address:5756 SHARON-WARREN RD
Box:207
City:BROOKFIELD
State:OH
ZIP:44403-9507
Country:US
Info Phone Num:216-394-1617
Emergency P
hone Num:216-394-1617
Preparer's Name:RICHARD MOORE
CAGE:60218
=== Contractor Identification ===
Company Name:GRAPHITE PRODUCTS CORP
Address:5756 SHARON-WARREN RD
Box:207
City:BROOKFIELD
State:OH
ZIP:44403-9507
Country:US
Phone:216-394-1617
CAGE:60218

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL
CAS:8012-95-1
RTECS #:PY8030000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3 (MIST); 9394

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY CAUSE SKIN AND EYE IRRITATION WITH
PROLONGED CONTACT.
Effects of Overexposure:SKIN AND EYE IRRITATION.
Medical Cond Aggravated by Exposure:MAY AGGRAVATE PRE-EXISTING SKIN AND
EYE DISORDERS.

=====
===== First Aid Measures =====

First Aid:EYES- FLUSH WITH PLENTY
OF WATER FOR AT LEAST 15 MINUTES,
CALL A DOCTOR. SKIN- WASH WITH SOAP AND WATER. INGESTION- CALL A
PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>300F,>149C
Autoignition Temp:Autoignition Temp Text:>500F
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL AND
SAND/EARTH.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR AN APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/
Explosion Hazard:DENSE SMOKE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP AS MUCH AS POSSIBLE. COVER THE
REMAINDER WITH AN OIL ABSORBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:USE GOOD NORMAL INDUSTRIAL HYGIENIC
PRACTICES. KEEP CONTAINERS CLOSED WHEN NOT IN USE.
Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Protective

Gloves:OIL RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES OF FULL FACE SHIELD.

Other Protective Equipment:NONE

Work Hygienic Practices:WASH HANDS AFTER HANDLING MATERIAL.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:400F,204C

Spec Gravity:0.87

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID WITH MINERAL OIL ODOR.

===== Stability and Reactivity Data =====

Stabilit

y Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS SUCH AS HYDROGEN PEROXIDE, CHROMIC ACID,
BROMINE, ETC.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information

is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.