

FARWEST PAINT MFG CO -- 259 (TT-E-489) BLACK QUICK DRY ENAMEL -- 8010-00-527-2050
===== Product Identification =====

Product ID:259 (TT-E-489) BLACK QUICK DRY ENAMEL

MSDS Date:07/28/1992

FSC:8010

NIIN:00-527-2050

MSDS Number: BVTXL

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-244-8844

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM SOLVENT [NAPHTHA, LIGHT ALIPHATIC]

CAS:64742-89-8

Fraction by Wt: 40.19%

Other REC Limits:100 PPM

Ingred Name:ALIPHATIC HYDROCARBON [STODDARD SOLVENT]

CAS:8052-41-3

RTECS #:WJ892

5000
Fraction by Wt: 8.06%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9394

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 1.46%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PHENYLETHANE [ETHYL BENZENE (SARA III)]
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 0.27%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:1
00 PPM/125STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PARAFFINS (INCLUDING NAPHTHALENES) [HYDROTREATED LIGHT
PETROLEUM DISTILLATE]
CAS:64742-47-8
Fraction by Wt: 0.45%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AROMATICS [NAPHTHA, LIGHT AROMATIC]
CAS:64742-95-6
Fraction by Wt: 0.86%
Other REC Limits:70 PPM

Ingred Name:VOLATILE ORGANIC COMPOUNDS: 473 GRAMS/LITER
RTECS #:9999999VO
Fraction by Wt: 60.82%
Other REC Limits:NONE RECOMMENDED

===== Hazards

Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT WITH EYES MAY CAUSE IRRITATION. INHALATION MAY CAUSE CNS EFFECTS. ASPIRATION CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. CHRONIC: PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN DE FATTING, DRYING, IRRITATION, OR SENSITIZATION.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS

LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALED: HEADACHE, NAUSEA, DIZZINESS, LOSS OF CONSCIOUSNESS. EYES: REDNESS, TEARING, BLURRED VISION. SKIN: REDNESS, DISCOMFORT.

Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH SAFE HANDLING INSTRUCTIONS.

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH LOTS OF WATER FOR 15 MINUTES. SEEK MEDICAL ATTENTION. SKIN-WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP, GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:107F,42C

Extinguishing Media:USE WATER FOG,CARBON DIOXIDE,FOAM,DRY CHEMICAL OR ANY CLASS B EXTINGUISHER.WATER MAY BE INEFFECTIVE EXCEPT FOR COOLING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT & A

FULL FACED SELF CONTAINED BREATHING APPARATUS.COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:VAPOR MAY FORM EXPLOSIVE MIXTURE WITH AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB SPILL WITH INERT MATERIAL AND PLACE IN A C

LOSED

CONTAINER. WEAR PROTECTIVE CLOTHING/EQUIPMENT DURING CLEAN-UP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID PROLONGED OR REPEATED INHALATION. AVOID CONTACT WITH SKIN, CLOTHES OR EYES. KEEP AWAY FROM HEAT OR FLAME.

Other Precautions:DO NOT WELD ON FULL OR EMPTY CONTAINERS. KEEP CONTAINERS CLOSED AND PROPERLY LABELED WHEN NOT IN USE.

===== Exposure Control
rols/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:USE ADEQUATE EXPLOSION-PROOF MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NEOPRENE OR NATURAL RUBBER GLOVES

Eye Protection:PAINT GOGGLES/SAFETY GLASSES AS REQUIRED

ASSESS AS REQUIRED

Other Protective Equipment:INDUSTRIAL-TYPE WORK CLOTHING, HAT AND APRON AS REQUIRED.

Work Hygienic Practices:USE WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR/SPRAY MIST. AVOID CONTACT WITH SKIN & EYES. WASH HANDS AFTER USE.

Supplemental Safety and Health

MSDS ENTERED BY DLA-HMIS UNDER PROJECT FOR GSA.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>307F,>153C

Vapor Pres:2.6 MM HG

Vapor Density:>1

Spec Gravity:0

.92

Evaporation Rate & Reference: