View NSN Online: https://aerobasegroup.com/nsn/8040-00-800-1811

Product ID:CT-5047-2,PART B MSDS Date:04/28/1992 FSC:8040 NIIN:00-800-1811 Kit Part:Y MSDS Number: BVTYY === Responsible Party === Company Name: EMERSON CUMING INC. SUB OF W R GRACE AND CO. Address:77 DRAGON COURT City:WOBURN State:MA ZIP:01888 Country:US Info Phone Num:617-828-3 300 Emergency Phone Num:617-935-4850/617-938-8630 Preparer's Name: DAVID HAAS CAGE:0B562 === Contractor Identification === **Company Name: EMERSON & CUMING** Address:55 HAYDEN AVE Box:City:LEXINGTON State:MA ZIP:02173 Country:US Phone:617-861-6600 CAGE:0B562

Ingred Name:PROPOXYLATED TRIETHYLENE-TETRAMINE CAS:26950-63-0 Fraction by Wt: 65 - 75% Other REC Limits:NONE RECOMMENDED

Ingred Name:TRIETHYLENE TETRAMINE CAS:112-24-3 RTECS # :YE6650000 Fraction by Wt: 25 - 35% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY & GI TRACTS. ACUTE- EYE/SKIN:CORROSIVE. MAY CAUSE SEVERE BURNS. HARMFUL IF ABSORBED THROUGH SKIN. MAY CAUSE SENSITIZATION. INHALE:MAY CAUSE RESPIRATORY SENSITIZATI ON. ORAL:HARMFUL IF INGESTED. MAY CAUSEBURNS TO UPPER GI TRACT. CHRONIC- MAY CAUSE LIVER & KIDNEY INJURY. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION OF EYES, SKIN, RESPIRATORY AND

GASTROINTESTINAL TRACTS; CORNEAL INJURY, BLINDNESS, SKIN BLISTERING, TIGHTNESS OF THE CHEST, ASTHMA-LIKE SYMPTOMS, RESPIRATORY DISTRESS, SKIN SENSITIZATION/AL LERGIC SKIN REACTIONS WHICH MAY BE SEVERE IN CERTAIN INDIVIDUALS

Μ

edical Cond Aggravated by Exposure: THIS PRODUCT MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE.

First Aid:GET MEDICAL HELP IMMEDIATELY. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:IMMEDIATELY FLUSH WITH WATER, THEN WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF CONSCIOUS, DRINK LARGE AMOUNT OF WATER. NE VER GIVE ANYTIHING BY

MOUTH TO AN UNCONSCIOUS PERSON.

Flash Point:>200F,>93C

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL. Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE. Unusual Fire/Explosion Hazard:MAY FOR

M TOXIC COMBUSTION PRODUCTS. CLOSED CONTAINERS MAY VIOLENTLY RUPTURE UNDER FIRE CONDISIONS.

Spill Release Procedures: VENTILATE AREA. WIPE UP OR ABSORB SPILLED MATERIAL WITH VERMICULITE OR OTHER SIMILAR MATERIAL. WASH AREA WITH SOAPY WATER TO REMOVE RESIDUE. COLLECT ABSORBED MATERIAL AND WATER RINSES IN APPROPRIATE C ONTAINERS FOR LATER DISPOSAL. Neutralizing Agent:NOT RELEVENT

======= Handling a

Handling and Storage Precautions:STORE IN COOL, VENTILATED AREA, AWAY FROM OPEN FLAMES & INCOMPATIBLES. KEEP CONTAINER TIGHTLY CLOSED.
Other Precautions:AVOID BREATHING VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. LAUNDER BEFORE REUSE. KEEP OUT OF REACH OF CHILDREN.

Re

spiratory Protection: IF WORKING IN A CONFINED AREA OR FIGHTING FIRE, USE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED AIR RESPIRATOR WITH FULL FACEPIECE, OPERATED IN POSITIVE PRESSURE MODE.

Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO DRAW VAPORS, MISTS OR FUMES GENERATED DURING PROCESSING AWAY FROM WORKERS. Protective Gloves:RUBBER OR PLASTIC

Eye Protection: SPLASH-PROOF CHEMICAL GOGGLES

Other Protective Equipment: SAFETY SHOWER AND EYE WASH FOUNTAIN SH OULD

BE LOCATED NEARBY. CHEMICAL-RESISTANT APRON AND IMPERVIOUS CLOTHING Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

KEY1:C2. THIS PRODUCT IS A KIT CONSISTING OF TWO PARTS. PART A HAS PNI A; PART B HAS PNI B, SAME NSN.

HCC:B2 NRC/State Lic Num:NOT RELEVENT Boiling Pt:>204.4C, 400.F Vapor Pres: