

DELTA D.P.C., INC -- EPOXY RESIN AND HARDNER TOOLING SYSTEM -- 8030-00-187-7747

===== Product Identification =====

Product ID:EPOXY RESIN AND HARDNER TOOLING SYSTEM

MSDS Date:08/03/1988

FSC:8030

NIIN:00-187-7747

Kit Part:Y

MSDS Number: BVWWK

=== Responsible Party ===

Company Name:DELTA D.P.C., INC

Address:983 E. LEVIN AVE

City:TULARE

State:CA

ZIP:93274

Country:US

Info Phone Num:209-686-1644

Emerg

ency Phone Num:209-686-1644

CAGE:43702

=== Contractor Identification ===

Company Name:DELTA D.P.C., INC

Address:983 E. LEVIN AVE

Box:City:TULARE

State:CA

ZIP:93274

Country:US

Phone:209-686-1644

CAGE:43702

===== Composition/Information on Ingredients =====

Ingred Name:NON HAZARDOUS INGREDIENT

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >2000 MG/KG

Routes of Entry: Inhalation:NO Sk

in:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED CONTACT MAY
CAUSE EYE IRRITATION AND OTHER ALLERGIC RESPONSES SUCH AS SKIN
IRRITATION OR DERMATITIS.
Explanation of Carcinogenicity:NOT CARCINOGENIC.
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:IN CASE
OF SKIN CONTACT WASH IMMEDIATELY WITH SOAP & WATER
FOR EYES, FLUSH WITH PLENTY OF WATER FOR 15 MINUTES AND CONSULT A
PHYSICIAN IMMEDIATELY. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE
REUSE.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:470F,243C
Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICALS.
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE.
Unusual Fire/Explosion Hazard:AVOID HEAT, OPEN FLAMES AND ELECTRIC
SPARKS.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP IN ABSORBENT MATERIAL & FLUSH AREA WIH
PLENTY OF WATER.

===== Handling and Storage =====

Handling and Storage Precautions:WARNING: MAY CAUSE SKIN SENSITIZATION
OR ALLERGIC RESPONSE.
Other Precautions:AVOID SKIN CONTACT OR EYE CONTACT. AVOID INHALATION
OF VAPORS. USE GOOD VENTILATION PARTICULARLY IF HEATED OR SPRAYED.

===== Expo

sure Controls/Personal Protection =====

Respiratory Protection: AIR MASK IF IN CONFINED AREA.

Ventilation: LOCAL EXHAUST IS PREFERABLE.

Protective Gloves: YES

Eye Protection: SAFETY GLASSES OR GOGGLES.

Other Protective Equipment: SAFETY SHOWER AND EYE BATH. USE COVERALLS OR APRONS, GLOVES, ETC. TO PROTECT AGAINST SKIN & CLOTHING CONTAMINATION.

Work Hygienic Practices: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

CAUTION: THIS SYSTEM CONTAINS A

N EPOXY RESIN WITH AN ACCELERATED AMINO

AMINE HARDENER AGENT.

===== Physical/Chemical Properties =====

HCC: N1

Boiling Pt: B.P. Text: 500F, 260C

Vapor Density: >AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG ACIDS, AMINES, MERCAPTANS AND BASES.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous

Decomposition Products: NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE IN FURNACE OR BURY IN LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this

s information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.