

DAP INC -- DAP 1012 GLAZING -- 8030-00-823-7920

=====
Product Identification
=====

Product ID:DAP 1012 GLAZING
MSDS Date:01/07/1994
FSC:8030
NIIN:00-823-7920
MSDS Number: BVZHJ
=== Responsible Party ===
Company Name:DAP INC
Box:277
City:DAYTON
State:OH
ZIP:45401
Country:US
Info Phone Num:800-543-3840
Emergency Phone Num:800-535-5053; 800-543-3840
CAGE:90300

==== Contractor Identification ===

Compa
ny Name:DAP INC.
Box:277
City:DAYTON
State:OH
ZIP:45401-0277
Country:US
Phone:513-253-7154/800-543-3840
CAGE:90300

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:HYDROUS MAGNESIUM SILICATE
CAS:14807-96-6
RTECS #:WW2710000
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC LESS WATER LESS EXEMPT SOLVENTS: 48 GRAM

S/LITER. VOC

MATERIAL: 48 GRAMS/LITER

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE EFFECTS: MAY IRRITATE EYES,
SKIN, NOSE & RESPIRATORY TRACT. HARMFUL IF INHALED. HARMFUL OR
FATAL IF SWALLOWED. IF INGESTED, THIS PRODUCT MAY CAUSE VOMITING,
DIARRHEA, & DEPRESSED RESPIRATION. INHALATION MAY AFFECT THE BRAIN

OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE, OR NAUSEA.

Effects of Overexposure:CHRONIC EFFECTS: REPORTS HAVE ASSOCIATED
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE WITH PROLONGED AND REPEATED
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS. PROLONGED OR REPEATED
CONTACT WITH SKIN MAY CAUSE IRRITATION.

=====
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15
MINUTES.

CONTACT A PHYSICIAN IMMEDIATELY. SKIN CONTACT: WASH WITH
SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. CONTACT A
PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. CONTACT
A PHYSICIAN IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:194F,90C

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS
* (MINERAL SPIRITS)

Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT, INCLUDING
SELF-CONTAINED BREATHING APPARATUS, IS RECOMMENDED TO PROTECT FROM

COMBUSTION PRODUCTS. COOL EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:CONTAINER MAY EXPLODE W/EXTREME
HEAT.ELIMINATE IGNITION SOURCES:HEAT,ELECTRICAL EQUIP,SPARKS,& OPEN
FLAMES.DON'T PUT IN CONTACT W/OXIDIZERS OR CAUSTIC MATERIALS

=====
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP DRIED MATERIAL AND PLACE INTO
CONTAINERS.

=====

Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM CAUSTICS AND OXIDIZERS. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS FROM EXCESSIVE HEAT AND FREEZING.

Other Precautions:KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. DO NOT STORE AT TEMPERATURES ABOVE 120F. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING VAPOR MAY BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respirato

ry Protection:IF 8 HOUR EXPOSURE LIMIT OR VALUE IS EXCEEDED FOR ANY COMPONENT, USE AN APPROVED NIOSH/OSHA RESPIRATOR. CONSULT YOUR SAFETY EQUIPMENT SUPPLIER AND THE OSHA REGULATION, 29 CFR 1910.134 FOR RESPIRATOR R EQUIREMENTS.

Ventilation:PROVED SUFFICIENT MECHANICAL VENT (LOCAL OR GENERAL EXHAUST) TO MAINTAIN EXPOSURE BELOW PEL/TLV. *

Protective Gloves:IMPERVIOUS GLOVES RECOMMENDED

Eye Protection:SAFETY GLASSES ARE RECOMMENDED

Other Protective Equipment:PROVIDE EYEWASH AND SOLV ENT IMPERVIOUS APRON

IF BODY CONTACT WITH PRODUCT MAY OCCUR. BARRIER CREAMS MAY BE USED.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

* VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS. CHECK ALL LOW AREAS (BASEMENTS, SUMPS, ETC) FOR VAPOR BEFORE ENTERING.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>325F,>163C

Vapor Pres:3.1 *

Vapor Density:> 1

Spec Gravity:2.2 (WATER=1)

Evaporati

on Rate & Reference: