View NSN Online: https://aerobasegroup.com/nsn/8030-00-244-1297

Product ID:TECTYL 502-C, MIL-C-16173D GR#2 (11 OZ AEROSOL) MSDS Date:07/01/1993 FSC:8030 NIIN:00-244-1297 MSDS Number: BWCBJ === Responsible Party === Company Name: F AND L CO INC Address:1537 E DEL AMO BLVD City:CARSON State:CA ZIP:90746 Country:US Info Phone Num:213-603-2200 Е mergency Phone Num:213-603-2200 CAGE:KO816 === Contractor Identification === Company Name: F & L COMPANY Address:1537 E DEL AMO BLVD Box:City:CARSON State:CA ZIP:90746 Country:US Phone:310-603-2200 CAGE:0KWT9 Company Name: F AND L CO INC Address:1537 E DEL AMO BLVD Box:City:CARSON State:CA ZIP:90746 Country:US Phone:213-603-2200 CAGE:KO816

Ingred Name:OIL ADDITIVE Fraction by Wt: 10-25% Other REC Limits:NONE RECOMMENDED

Ingred

Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 25-40% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9394

Ingred Name:MINERAL OIL, HYDROTREATED (MILD), HEAVY NAPHTHENIC DISTILLATE, PETROLEUM CAS:64742-52-5 RTECS #:PY8035000 Fraction by Wt: 10-15% Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON DIOXIDE CAS:124-38-9 RTECS #:FF6400000 Fraction by Wt: 3% Other REC Limits:NONE RECOMMENDED OSHA PEL:5000 PPM ACGIH TLV:5000PPM/30000STEL;94

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:OVEREXPOSURE TO THIS MATERIAL (OR ITS COMPONENTS) HAS BEEN SUGGESTED AS A CAUSE OF CENTRAL NERVOUS SYSTEM EFFECTS. Effects of Overexposure:EYES- SEVERE IRRITATION, REDNESS, TEARING AND

BLURRED VISION. SKIN- IRRITATION, DEFATTING AND DERMATITIS. Medical Cond Aggravated by Exposure :NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE LIFTING EYELIDS. SKIN: FLUSH WITH WATER. REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE VICTIM TO FRESH AIR. GIVE OXYGEN OR ARTIFICIAL RESPIRATIO N AS REQUIRED. GET MEDICAL ATTENTION. INGESTION- DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION. KEEP PERSON QUIET. ASPIRATION OF MATERIAL CAN BE FATAL.

=========

Flash Point Method:COC Flash Point:>100F,>38C Lower Limits:1.0 Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures:WEAR A NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT WHEN FIGHTING FIRES. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:HAZARDOUS DECOMPOSITION PRODUCTS MAY FORM IN FIRE CONDITIONS.

======= Accidental Rel

ease Measures =================

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. STOP SPILL AT SOURCE. SMALL SPILL - REMOVE LIQUID BY OIL-ABSORBING MATERIALS. LARGE SPILL - EXCLUDE PERSONS NOT WEARING PROTECTIVE EQUIPMENT, DIKE AR EA OF SPILL AND PUMP LIQUID INTO SALVAGE TANK.

Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHENB EMPTIED SINCE EMPT IED CONTAINERS RETAIN PRODUCT RESIDUES. Other Precautions:NONE

Respiratory Protection: A NIOSH/MSHA-APPROVED AIR-SUPPLIED RESPIRATOR IS ADVISED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL. Ventilation: PROVIDE LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME AND PATTERN SO AS TO MAINTAIN EXPOSURE BELOW TLV'S. Protective Gloves: WEAR RESISTANT GLOVES Eye Protection: CHEMICAL SPLASH GOGGLES. Other Protective Equipment: N ORMAL WORK CLOTHING COVERING ARMS AND LEGS. Work Hygienic Practices: WASH HANDS BEFORE EATING OR SMOKING. Supplemental Safety and Health NONE

HCC:V3 Boiling Pt:B.P. Text:>300F,>149C Vapor Pres:95 PSIG Vapor Density:>1 Spec Gravity: