

OCTAGON PROCESS INC. -- MIL-L-46152D GRADE 10W-30 -- 9150-00-186-6699

=====  
Product Identification  
=====

Product ID:MIL-L-46152D GRADE 10W-30

MSDS Date:07/13/1992

FSC:9150

NIIN:00-186-6699

MSDS Number: BWCVN

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-313-1187/FAX -1057 (CAROL)

Emergency Ph

one Num:201-945-9400/800-424-9300(CHEMTREC)

Preparer's Name:J.J. BURGARD

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ZINC (SARA III) [CONTAINS 0.1%-0.13%]

CAS:7440-66-6

RTECS #:ZG8600000

Fraction by Wt: 0.1%

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000

LBS

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE PRESENT IN THIS PRODUCT.

RTECS #:9999999ZZ

Fraction by Wt: >99%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE: EXPOSURE MAY CAUSE EYE, SKIN,  
NOSE, THROAT & UPPER RESPIRATORY TRACT IRRITATION. INHALATION OF

VAPORS MAY CAUSE CNS DEPRESSION. INGESTION MAY CAUSE GI TRACT  
IRRITATION. CHRONIC: PROLONGED OR RE PEATED EXPOSURE MAY CAUSE  
CONJUNCTIVITIS, SKIN DEFATTING & DERMATITIS.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%  
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION. INHALED:  
IRRITATION, DIZZINESS, HEADACHE, STUPOR, LOSS OF COORDINATION.  
INGESTED: NAUSEA, PAIN, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL  
RESPIRATION/OXYGEN IF NEEDED. GET MEDICAL ATTENTION IMMEDIATELY.  
EYE: FLOOD WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, GET  
MEDICAL ATTENTION. S KIN: WASH WITH SOAP & WATER. IF IRRITATION  
PERSISTS, GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING.  
IF CONSCIOUS, GIVE WATER. GET M  
EDICAL ATTENTION IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:410F,210C

Extinguishing Media:WATER FOG, CARBON DIXOIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:DO NOT USE DIRECT STREAM OF WATER-PRODUCT MAY  
FLOAT ON SURFACE OF WATER & REIGNITE. KEEP FIRE EXPOSED CONTAINERS  
COOL WITH WATER FOG.

Unusual Fire/Explosion Hazard:NONE.

=====  
===== Accidental Release Measures =====

Spill Release

Procedures:DIKE & CONTAIN SPILL. DO NOT ALLOW TO ENTER SEWERS, DRAINS, OR WATERWAYS. RECOVER FREE LIQUID IF POSSIBLE. ABSORB WITH INERT MATERIAL & PLACE INTO PROPER CONTAINERS FOR DISPOSAL. ALL RESPONSE ACTIVITIES MUST COMPLY WITH HAZWOPER (29CFR1910.120).

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY FROM STRONG OXIDIZERS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:CLEAN CONTAMINATED EQUIPMENT BEFORE STARTING ANY REPAIR WORK. USE THIS PRODUCT ONLY AS DIRECTED-REFER TO MANUFACTURER'S DIRECTIONS. THIS PRODUCT CONTAINS 0.1-0.13% ZINC WHICH IS REGULATED UNDER SARA II SECTION 313 SUPPLIER NOTIFICATION.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:DLA-IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR

SUPPLIED AIR RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:RUBBER OR NEOPRENE.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:IF EXCESSIVE MISTING, USE RUBBER APRON & FACESHIELD. PROVIDE LOCAL EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:ANY USERS SHOULD CONSULT MSDS BEFORE HANDLING

THIS MATERIAL. AVOID PROLONGED BREATHING OF VAPORS.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>420F,>216C

Vapor Pres:NIL

Vapor Density:12

Spec Gravity:0.88

Evaporation Rate & Reference:0.001 (ETHYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK AMBER LIQUID; SLIGHT PETROLEUM ODOR.

Percent Volatiles by Volume:NIL

=====  
===== Stability and Reactivity Data =====

St

ability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS.

Stability Condition to Avoid: HEAT, SPARKS, OPEN FLAME.

Hazardous Decomposition Products: CARBON MONOXIDE, TRACES OXIDES OF  
SULFUR, PHOSPHORUS & ZINC.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF WASTE IN COMPLIANCE WITH LOCAL, STATE  
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by e

lements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.