

LORD CORP CHEMICAL PRODUCTS GR -- VERSILOK 506 STRUCTURAL ADHESIVE 55060 L

=====
MSDS Safety Information
=====

FSC: 8040
NIIN: 01-170-3599
MSDS Date: 12/08/1992
MSDS Num: BWFPP
Product ID: VERSILOK 506 STRUCTURAL ADHESIVE 55060 L
MFN: 03
Kit Part: Y
Responsible Party
Cage: 30676
Name: LORD CORP CHEMICAL PRODUCTS GROUP
Address:
2000 W GRANDVIEW BLVD
City: ERIE PA 16514
Info Phone Number: 814-868-3611
Emergency Phone Number: 814-763-2345
Preparer's Name: THD
Proprietary Ind: Y
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 30676
Name: LORD CORPORATION, CHEMICAL PRODUCTS DIVISION
Address: 2000 WEST GRANDVIEW BLVD
City: ERIE PA 16514-0038
Phone: 814-868-3611

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ADHESIVE
Specification Number: NONE
Type/Grade/Class: NONE
Unit of Issue: KT
UI Container Qty: 0
Type of Container: UNKNOWN

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards

Data

LD50 LC50 Mixture: LD50 (ORAL, RAT) IS UNKNOWN.

Route Of Entry Inds - Inhalation: YES

Skin: NO

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: TARGET ORGANS:EYES, SKIN, RESPIRATORY TRACT. ACUTE- OVER EXPOSURE MAY CAUSE EYES, SKIN, RESPIRATORY TRACT IRRITATION. MAY CAUSE HEADACHE AND NAUSEA. MAY BE HARMFUL IF INGESTED. ASPIRATION HAZARD. CHRO NIC- MAY CAUSE SKIN SENSITIZATION.

Explanation Of Carcinogenicity: NONE

Signs And Symptoms Of Overexposure: EYES, SKIN, RESPIRATORY TRACT IRRITATION; HEADACHE, SKIN SENSITIZATION

Medical Cond Aggravated By Exposure: PERSONS WITH PRE-EXISTING SKIN DISORDERS, EYE PROBLEMS OR IMPAIRED GASTROINTESTINAL TRACT OR RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

First Aid: GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING E

YELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER, HOSPITAL EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY. IF CONSCIOUS, DRINK ONE OR TWO GLASSES OF WATER OR MILK TO DILUTE. TREAT SYMPTOMATICALLY.

Handling and Disposal

Spill Release Procedures: WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. CONTAIN SPILL.

PICK UP SPILL WITH NON-FLAMMABLE

ABSORBENT SUCH AS SAND, EARTH/USE PUMP (EXPLOSION PROOF). GROUND ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM ENTERING SEWERS.

Neutralizing Agent: NOT RELEVANT

Waste Disposal Methods: DISPOSE IN AN APPROVED INCINERATOR OR CONTRACT WITH LICENSED CHEMICAL WASTE DISPOSAL SERVICE. DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: STORE IN COOL, WELL VENTILATED PLACE, AWAY FROM IGNITION SOURCES & I

INCOMPATIBLE MATERIALS. USE GROUND STRAP. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions: WARNING! FLAMMABLE. EMPTY CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS. DO NOT PUNCTURE/WELD ON OR NEAR CONTAINER. USE WITH ADEQUATE VENTILATION. DO NOT BREATHE VAPORS. AVOID EYES AND SKIN CONTACT. KEEP OUT OF REACH OF CHILDREN.

=====
Fire and Explosion Hazard Information
=====

Flash Point

Test Method: SCC

Flash Point: =11.7C, 53.F

Flash Point Text: 53.0F,11.7C

Lower Limits: 1.6

Upper Limits: 8.8

Extinguishing Media: USE NFPA CLASS B (ALL PURPOSE DRY CHEMICAL, CARBON DIOXIDE/ALCOHOL FOAM). POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. WATER MAY BE INEFFECTIVE, BUT SHOULD BE USED TO COOL FIRE-EXPOSED CONTAINER

Unusual Fire/Explosion Hazard: VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL

CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

=====
Control Measures
=====

Respiratory Protection: WEAR NIOSH-APPROVED RESPIRATOR FOR REMOVING ORGANIC VAPORS IF PEL ARE EXCEEDED. IN CONFINED AREA USE APPROVED AIR-LINE TYPE RESPIRATOR OR HOOD.

Ventilation: MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)

VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: RUBBER, NEOPRENE, NITRILE

Eye Protection: SAFETY GOGGLES/FACE SHIELD

Other Protective Equipment: PROTECTIVE CLOTHING, SAFETY SHOWER AND EYEWASH FACILITY

Work Hygienic Practices: OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health: KEY1:F2. THIS PRODUCT IS A KIT CONSISTING OF TWO PARTS. PART A, HAS PNI C; PART B HAS PNI B, SAME NSN. FORMULA CHANGED. FOR PREVIOUS FORMULAT

ION SEE PNI A, SAME NSN.

=====
Physical/Chemical Properties
=====

HCC: F2

NRC/State LIC No: NOT RELEVANT

Boiling Point: =101.1C, 214.F

Vapor Pres: UNKNOWN

Vapor Density: >1

Spec Gravity: 0.996

Viscosity: UNKNOWN

Solubility in Water: INSOLUBLE

Appearance and Odor: PINK PASTE - SWEET ODOR

Percent Volatiles by Volume: 0

Corrosion Rate: UNKNOWN
=====

==
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: HEAT, SPARKS, FLAMES AND OTHER SOURCES OF
IGNITION

Materials To Avoid: STRONG OXIDIZING AGENTS, PEROXIDES

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, ORGANIC OR
INORGANIC NITROGEN COMPOUNDS INCLUDING TRACE AMOUNT OF HYDROGEN CYANIDE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT
=====

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
=====
Other Information
=====
=====

=====
=====
Transportation Information
=====

Responsible Party Cage: 30676
Trans ID NO: 112790
Product ID: VERSILOK 506 STRUCTURAL ADHESIVE 55060 L
MSDS Prepared Date: 12/08/1992
Review Date: 01/24/1995
MFN: 3
Net Unit Weight: UNKNOWN
Multipl
e KIT Number: 0
Kit Part IND: Y
Review IND: Y
Unit Of Issue: KT
Container QTY: 0
Type Of Container: UNKNOWN
Additional Data: PROPER SHIPPING NAME, PER MSDS. CONTAINS METHYL METHACRYLATE.
UNIT PACKAGE IS 3.0 OZ.

=====
=====
Detail DOT Information
=====

DOT PSN Code: AFR
DOT Proper Shipping Name: ADHESIVES,
DOT PSN Modifier: CONTAINING A FLAMMABLE LIQUID
Hazard Class: 3
UN ID Num: UN1133
DOT Packaging
Group: II
Label: FLAMMABLE LIQUID
Special Provision: B52,T,T30
Packaging Exception: 150
Non Bulk Pack: 173
Bulk Pack: 242
Max Qty Pass: 5 L
Max Qty Cargo: 60 L
Vessel Stow Req: B

=====
=====
Detail IMO Information
=====

IMO PSN Code: AIH
IMO Proper Shipping Name: ADHESIVES,
IMO PSN Modifier: CONTAINING A FLAMMABLE LIQUID o
IMDG Page Number: 3174
UN Number: 1133
UN Hazard Class: 3.2
IMO Packaging Group:

I/II*

Subsidiary Risk Label: -

EMS Number: 3-05

MED First Aid Guide NUM: 330

=====
Detail IATA Information
=====

IATA PSN Code: AKY

IATA UN ID Num: 1133

IATA Proper Shipping Name: ADHESIVES

IATA PSN Modifier: ,CONTAINING FLAMMABLE LIQUID

IATA UN Class: 3

IATA Label: FLAMMABLE LIQUID

UN Packing Group: II

Packing Note Passenger: 305

Max Quant Pass: 5L

Max Quant Cargo: 60L

Packaging Note Cargo: 307

Exceptions: A7

=====
Detail AFI Information
=====

AFI PSN Code: AKY

AFI Proper Shipping Name: ADHESIVES

AFI PSN Modifier: ,CONTAINING FLAMMABLE LIQUID

AFI Hazard Class: 3

AFI UN ID NUM: UN1133

AFI Packing Group: II

Special Provisions: P5

Back Pack Reference: A7.3

=====
HAZCOM Label
=====

Product

ID: VERSILOK 506 STRUCTURAL ADHESIVE 55060 L

Cage: 30676

Company Name: LORD CORPORATION, CHEMICAL PRODUCTS DIVISION

Street: 2000 WEST GRANDVIEW BLVD

City: ERIE PA

Zipcode: 16514-0038

Health Emergency Phone: 814-763-2345

Label Required IND: Y

Date Of Label Review: 01/24/1995

Status Code: C

MFG Label NO: NOT RELEVANT

Label Date: 01/24/1995

Origination Code: F

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: DANGER

Health Hazard: Moderate

Contact Hazard: Slight

Fire Hazard: Severe

Reac

tivity Hazard: None

Hazard And Precautions: TARGET ORGANS:EYES, SKIN, RESPIRATORY TRACT. ACUTE- MAY CAUSE EYES, SKIN, RESPIRATORY TRACT IRRITATION; HEADACHE & NAUSEA. ASPIRATION HAZARD. CHRONIC- MAY CAUSE SKIN SENSITIZATION. STORE IN COOL, WELL VENTILATED AREA AWAY FROM IGNITION SOURCES & INCOMPATIBLES. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND. PREVENT LIQUID FROM ENTERING SEWERS. FIRST AID- GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. P

PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. CALL PHYSICIAN. IF CONSCIOUS, DRINK ONE/TWO GLASSES OF WATER OR MILK.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly

ly or implied

warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume respon

sibility for the suitability of this information to their

particular situation regardless of similarity to a corresponding Department of Defense or other government situation.