View NSN Online: https://aerobasegroup.com/nsn/8030-00-244-1295

Product ID:PL-2 MSDS Date:03/11/1993 FSC:8030 NIIN:00-244-1295 MSDS Number: BWGJK === Responsible Party === Company Name:ESGARD, INC. Box:2698 City:LAFAYETTE State:LA ZIP:70502 Country:US Info Phone Num:318-234-6327 Emergency Phone Num:800-732-9876 CAGE:ESGAR === Contractor Identification === Company Name: ESGARD, INC. Add ress:PO DRAWER 2698 Box:2698 **City:LAFAYETTE** State:LA ZIP:70502 Country:US Phone:318-234-6327 CAGE:ESGAR Ingred Name:SOLVENT NAPHTHA (PETROLEUM) MEDIUM ALIPHATIC CAS:64742-88-7 Other REC Limits:NONE SPECIFIED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST) Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Other REC Limits:NONE SPECIFIED OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9394

====== Hazar

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-INHALATION OF VAPORS MAY BE NARCOTIC OR ANESTHETIC. INGESTION OF LIQUID WILL CAUSE G/I DISTRESS, IRRITATION & NAUSEA. LIQUID OR VAPORS MAY BE IRRITATINGTO SKIN & EYES. CHRONIC-UNKNOWN,STUDIES W/ MICE & RATS HAVE SHOWN THAT SOME PETROLEUM DISTILLATES HAVE CAUSED DAMAGE OR TUORS TO THE KIDN

EYS & LIVER & SKIN CANCER.

Explanation of Carcinogenicity:SEE CHRONIC HEALTH HAZARDS FOR CARCINOGENICITY EXPLINATION.

Effects of Overexposure:SIGNS OF INHALATION OVEREXPOSURE:RESPIRATORY IRRITATION, CNS DEPRESSION, HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS, COMA.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS.

First Aid:IF IRRITATION OR SYMPTOMS PERSIST OR ARE SEVERE, SEE A DOCTOR. EYE:FLUSH W/WATER 15 MIN, HOLD LIDS OPEN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. INHALED:RE MOVE TO FRESH AIR. AID/RESTORE BREATHING IF NECESSARY. INGESTED:DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL CARE.

Flash Point Method:PMCC Flash Point:355F,179C Lower Limits:0.9 Upper Limits:7 Extinguishing Media:DRY POWDER, CARBON DIOSIDE, WATER FOG OR SPRAY Fi re Fighting Procedures:APPROACH FIRE FROM UPWIND. AVOID BREATHING SMOKE,FUMES,VAPOR,MIST ON DOWNWIND SIDE. FIREFIGHTERS WEAR PROTECTIVE CLOTHING & SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT & MAY IGNITE ON WATER. IF STORED IN DRUMS,CONTAINERS MAY RUPTURE FROM INTERNAL PRESSURE FROM THE HEAT. COOL WITH WATER. EVACUATE AREA.

Spill Release Procedures: EMERGENCY RESPONSE COO

RDINATOR MUST HAVE MANDATED TRAINING. PICK UP WITH ABSORBENT MEDIA. STORE AS NON-HAZARDOUS OIL WASTE. NOTIFY PROPER LOCAL, STATE & FEDERAL AGENCIES. Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.
======================================
 Handling and Storage Precautions:STORE IN A COOL, VENTILATED AREA AWAY FROM IGNITION SOURCES. STORE AWAY FROM OXIDIZERS OR MATERIALS BEARING A YELLOW DOT LABEL. Other Precautions:CLEAN UP LEAKS/SPILLS IMMEDIAT ELY TO PREVENT SOIL OR WATER CONTAMINATION.
======================================
 Respiratory Protection:NOT NORMALLY NEEDED UNDER PROPER CONDITIONS OF USE AND STORAGE. Ventilation:LOCAL EXHAUST AND MECHANICAL (GENERAL) VENTILATION RECOMMENDED Protective Gloves:CHEMICAL IMPERVIOUS Eye Protection:CHEMICAL GOGGLES OR FULL FACE SHIELD Other Protective Equipment:BOOTS,APRONS,DRENCH SHOWERS,EYE WASH AS NEEDED FOR PROTECTION AGAINST SPILLS AND/OR SPLASH ES. Work Hygienic Practices:AVOID CONTACT W/SKIN,EYES & CLOTHING. AFTER HANDLING, WASH HANDS BEFORE EATING,DRINKING OR SMOKING. Supplemental Safety and Health AVOID WATER CONTAMINATION AND USE MINIMUM HANDLING TEMPERATURES TO AVOID PRODUCT DEGRADATION. PRODUCT DEGRADATION MAY INCREASE HEALTH HAZARDS.
======================================
HCC:N1 NRC/State Lic Num:NONE Boiling Pt:B.P. Text:>300F,>149C

Vapor Pres:4 Spec Gravity:0.94 pH:8-9 Evaporation Ra

te & Reference: