View NSN Online: https://aerobasegroup.com/nsn/8010-01-040-3760

ROSE TALBERT PAINT CO -- 16376 IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL HIGH GLOSS -- 8010-01-040-3760

============= Product Identification ==================

Product ID:16376 IMFLO RUST INHIBITIVE INDUSTRIAL ENAMEL HIGH GLOSS

MSDS Date:06/24/1993

FSC:8010

NIIN:01-040-3760

MSDS Number: BWGLB === Responsible Party ===

Company Name: ROSE TALBERT PAINT CO

Address:901 FRINK ST

City:CAYCE State:SC ZIP:29033 Country:US

Info

Phone Num:803-796-0324

Emergency Phone Num:800-796-0324

Preparer's Name: DAVID KELLY

CAGE:0CUY5

=== Contractor Identification ===

Company Name: ROSE TALBERT PAINT CO

Address:901 FRINK ST

Box:City:CAYCE

State:SC ZIP:29033 Country:US

Phone:803-796-0324

CAGE:0CUY5

======= Composition/Information on Ingredients ========

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 21.09%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST;

9394
Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 42.5% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:100 PPM; 9394
========= Hazards Identification ==========
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY CAUSE IRRITATION AND DEFATTING.INGEST:MAY CAUSE GI TRACT IRRITATION.INHAL:MAY CA USE RESPIRATORY IRRITATION AND CNS DEPRESSION.CHRONIC:SOLVENTS MAY CAUSE PERMANENT BR AIN AND CNS DAMAGE. Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA. Effects of Overexposure:INHAL:DIZZINESS,HEADACHE,EUPHORIA.SKIN:DERMATITIS,CRAC KING. Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING BRAIN AND CNS AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE.
======================================
ineasures ====================================
First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH WARM WATER.EYES:FLUSH WITH LUKEWARM WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:DO

С NOT INDUCE VOMI TING.GET PROMPT QUALIFIED MEDICAL ATTENTION.IF CONSCIOUS, RINSE MOUTH WITH WATER; GIVE 6-8 OUNCES OF WATER TO DILUTE STOMACH CONTENTS.

Flash Point Method:TCC

Flash P

oint:107F,42C Lower Limits:0.7
Upper Limits:6
Extinguishing Media:CLASS B EXTINGUISHERDRY CHEMICAL, CARBON DIOXIDE, FOAM.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.
Unusual Fire/Explosion Hazard:A DIRECT WATER STREAM MAY SPREAD BURNING LIQUID.CONTAINERS MAY BURST FROM HEAT OF FIRE.DECOMPOSITION PRODUCT MAY BE TOXIC.
======================================
Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT. VENTILATE AREA. SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT (CLAY, SAND); PLACE IN PROPER CONTAINER FOR DISPOSAL. SPILL ON WATER; CALL NATL RESPONSE CTR, 800-424-8802.
Neutralizing Agent:NOT APPLICABLE.
=========== Handling and Storage ============
Handling and Storage Precautions:STORE IN A COOL,DRY,WELL-VENTILATED PLACE.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM HEAT,SPARKS,FLAMES AND INCOMPATIBLE MATERIALS. Other Precautions:EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUE;DISPOSE OF PROPERLY.AVOID BREATHING VAPORS;AVOID SKIN AND EYE CONTACT.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/PARTICULATES.
Ventilation:LOCAL VENTILATION AT THE WORKSIT E;MECHANICAL(GENERAL) VENTILATION TO MAINTAIN TLV/PEL.
Protective Gloves:NBR,BUNA N, NITRILE,NEOPRENE.
Eye Protection:CHEMICAL SPLASH GOGGLES Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.
Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA.
Supplemental Safety and Health THIS ITEM IS LEAD AND CHROMATE FREE.
======== Physical/Chemical Properties =

============

HCC:F4

Boiling Pt:B.P. Text:318-383F
Vapor Pres:2.6
Vapor Density:>1
Spec Gravity:1.105
Evaporation Rate & Description Reference: