

EXXENE CORPORATION -- EX-002 AMMONIATE ANTI-FOG -- 6850-01-399-3022

===== Product Identification =====

Product ID:EX-002 AMMONIATE ANTI-FOG

MSDS Date:08/15/1994

FSC:6850

NIIN:01-399-3022

MSDS Number: BWMMS

=== Responsible Party ===

Company Name:EXXENE CORPORATION

Address:5939 HOLLY ROAD

City:CORPUS CHRISTI

State:TX

ZIP:78414

Country:US

Info Phone Num:512-991-8391

Emergency Phone Num:512-991-8391

CAGE:NO301

=== Contractor Identification ===

Company Name:ADVANCED INDUSTRIES INC

Address:415 NORTHCUTT STREET

Box:5666

City:LONGVIEW

State:TX

ZIP:75608

Country:US

Phone:214-236-4101

CAGE:0GA21

Company Name:EXXENE CORP

Address:5939 HOLLY RD

Box:City:CORPUS CHRISTI

State:TX

ZIP:78412

Country:US

Phone:512-991-8391

CAGE:9T321

Company Name:EXXENE CORPORATION

Address:5939 HOLLY ROAD

Box:City:CORPUS CHRISTI

State:TX

ZIP:78414

Country:US

Phone:512-853-9943

CAGE:NO301

Company Name:MOODY PRECISION SUPPLY

INC
Box:UNKNOWN
CAGE:6T922

=====
Composition/Information on Ingredients
=====

Ingred Name:UNDER "HAZARDOUS INGREDIENTS", MFR LISTED "NONE".
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIA (SARA 302/313) (CERCLA)
CAS:7664-41-7
RTECS #:BO0875000
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:25 PPM/35 STEL; 9596
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

=====
Hazards Identification
=====

LD50 LC50 Mixture:
LD50 ORAL RATS: NOT GIVEN
Health Hazards Acute and Chronic:INHALATION OF VAPORS MAY CAUSE
ANESTHESIA, HEADACHE. SKIN CONTACT CAUSES IRRITATION. EYE CONTACT
CAUSES IRRITATION.
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.
Effects of Overexposure:ANESTHESIA, HEADACHE, SKIN IRRITATION, EYE
IRRITATION.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYES: IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MINUTES.
FLUSH UNDER LIDS BY LIFTING THEM OR ROLLING EYES. SEE DOCTOR ASAP.
SKIN: FLUSH WITH WATER. REMOVE CLOTHING AND CONTINUE FLUSHING.
INHALATION : REMOVE TO FRESH AIR AND RESTORE BREATHING. GET MEDICAL
HELP. INGESTION: DO NOT INDUCE VOMITING. DILUTE. GET PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:=19.4

C, 67.F

Lower Limits:2.52

Upper Limits:7.49

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICALS.

Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR A NIOSH/MSHA APPROVED
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:PROCEDURES FOR LOW FLASH POINT.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID SPARKS AND OPEN FLAMES. ABSORB WITH
INERT ABSORBANT AND COLLECT FOR DISPOSAL. USE NON-SPARKING TOOLS.

Neutralizing Agent:NONE

SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:HANDLE AS A FLAMMABLE LIQUID.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GENERAL DILUTION SHOULD BE SUFFICIENT.

Protective Gloves:RUBBER

Eye Protection:GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO

PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE
AVAILABLE.

Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER
BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:=60.C, 140.F

Vapor Pres:32.4

Spec Gravity:0.89

pH:5.8

Evaporation Rate & Reference:1.7-00 (N-BUTYL ACETATE=1

Solubility in Water:MISCI

BLE

Appearance and Odor:ALCOHOLIC

Percent Volatiles by Volume:76

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:EXTREME HEAT AND IGNITION SOURCES.

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCAR

D ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR

LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profess

ional advice to verify and

assume responsibility for the suitability of this information to their particular situation.