View NSN Online: https://aerobasegroup.com/nsn/6850-01-394-0167

BRULIN AND CO INC -- BRULIN SD 1291 -- 6850-01-394-0167

Product ID:BRULIN SD 1291 MSDS Date:04/07/1994

FSC:6850

NIIN:01-394-0167

MSDS Number: BWMWX === Responsible Party ===

Company Name:BRULIN AND CO INC Address:2920 DR ANDREW J BROWN AVE

Box:270

City:INDIANAPOLIS

State:IN

ZIP:46205-0270

Country:US

Info Phone Num:317-923-3211 OR 800-428-7149

Emergency Phone Num

:317-923-3211 CAGE:94058

=== Contractor Identification ===

Company Name: BRULIN AND CO INC

Address:2920 DR ANDREW J BROWN AVE

Box:270

City: INDIANAPOLIS

State:IN

ZIP:46205-0270 Country:US

Phone:317-923-3211

CAGE:94058

======= Composition/Information on Ingredients ========

Ingred Name: ETHYL-3-ETHOXYPROPIONATE

CAS:763-69-9

RTECS #:UF3325000 Fraction by Wt: 10-30%

Other REC Limits: NONE RECOMMENDED

Ingred Name: DIPROPYLENE GLYCOL METHYL ETHER

CAS:34590-94-8 RTECS #:JM1575000

Fraction b

y Wt: 50-70% Other REC Limits:NONE RECOMMENDED OSHA PEL:S,100PPM ACGIH TLV:S,100PPM/150STEL; 94
Ingred Name:ESSENTIAL OILS AND AROMATICS CHEMICALS Fraction by Wt: 0-1% Other REC Limits:NONE RECOMMENDED
========== Hazards Identification ============
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE:DIRECT CONTACT MAY CAUSE MODERATE IRRIT. INGEST:MODERATELY TOXIC. INHAL:EXC ESSVIE EXPOSURE MAY CAUSE RESPIRATORY IRRIT. SKIN:PROLONGED/REPEATED CONTACT MAY CAUSE IRRIT. CHRONIC SKIN EXPO MAY CAUSE DERMATITIS. OVEREXPO BY AIR &/OR PROLONGED SKIN CONTACT MAY CAUSE TEMPORARY BLURRING OF VISION. Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY:NTP/IARC/OSHA:NO. Effects of Overexposure:EYE/RESPIRATORY SKIN IRRITATION. DERMATITIS. BLURRING OF VISION. Medical Cond Aggravated by Exposure:NONE KNOWN.
======================================
First Aid:EYE:FLUSH W/LARGE QUANTITIES OF WATER FOR 15MINS LIFTING UPPER/LOWER LIDS OCCASIONALLY. GET MED ATTN. INHAL:REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF DIFFICULTY BREATHING. GET MED ATTN. SKIN:WASH W/MI LD SOAP & WATER. REMOE CONTAMIN CLOTHING. INGEST:GIVE 2 GLASSES OF WATER & INDUCE VOMIT IMMED BY STICKING FINGER DOWN THROAT. CALL PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO UNSCONSC PERSON.
======================================
Flash Point Method:PMCC Flash Point:160F,71C Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICALS. Fire Fighting Procedures:WATER FOG MAY BE USED TO COOL CLOSED CONTAINERS. Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR

Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM EVEN EMPTY.

======== Accidental Release Measures ===========

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE THE AREA WELL. ABSORB ON SOLID ABSORBENT & SHOVEL INTO CONTAINER

. FLUSH RESIDUES WITH WATER.
========== Handling and Storage ===========
Handling and Storage Precautions:STORE BETWEEN 40 AND 120F. Other Precautions:NONE SPECIFIED BY MANUFACTURER.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF RECOMMENDED LIMITS ARE EXCEEDED USE A USE NIOSH/MSHA APPROVED RESPIRATOR. CONTACT YOUR LOCAL SAFETY EQUIPMENT SUPPLIER FOR RECOMMENDATIONS. Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV. Protective Gloves:BUTYL RUBBER Eye Protection:GOGGLES Other Protective Equipment:OTHER PROT CLOTHING/EQPMT AS NECESSARY TO PREVENT SKIN CONTACT. Work Hygienic Practices:AVOID BREATHING SPRAY MIST. WASH HANDS AFTER HANDLING. LAUNDER CONTAMIN CLOTHING PRIOR TO REUSE. Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:V4 Boiling Pt:B.P. Text:212F,100C Melt/Freez e Pt:M.P/F.P Text: