View NSN Online: https://aerobasegroup.com/nsn/9150-00-967-5860

KEYSTONE LUBRICANTS -- KEYCUT SOLUBLE, G4K221K -- 9150-00-967-5860

Product ID:KEYCUT SOLUBLE, G4K221K MSDS Date:06/23/1993 FSC:9150 NIIN:00-967-5860 **MSDS Number: BWNLC** === Responsible Party === Company Name: KEYSTONE LUBRICANTS Address:5 N STILES ST City:LINDEN State:NJ ZIP:07036 Country:US Info Phone Num:908-862-9300 Emergency Phone Num:908-862-9300 Preparer's N ame:PETER KONOPI CAGE:75262 === Contractor Identification === Company Name: KEYSTONE LUBRICANTS Address:5 N STILES ST Box:City:LINDEN (WAS IN KING OF PRUSSIA, PA) State:NJ ZIP:07036 Country:US Phone:800-344-2241 CAGE:75262 

Ingred Name:PETROLEUM-BASED LUBRICATING OIL CONTAINING ING 2 OR 3 OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (SEVERE) LIGHT NAPHTHENIC CAS:64742-53-6 RTECS #:PY8036001 OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED (SEVERE), HEAVY NAPHTHENIC CAS:64742-52-5 RTECS #:PY8035001 OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:SODIUM PETROLEUM SULFONATE OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:SUPDAT: DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY BUNGED & RETURNED TO DRUM RECONDITIONER. ALL OTHER CNTNRS (ING 6) RTECS #:9999999ZZ

Ingred Name:ING 5: SHOULD BE DISPOSED OF IN ENVIRON SAFE MANNER & I/A/W GOVT REGS. FOR WORK ON TANKS REFER TO OSHA REG (ING 7) RTECS #:99999992Z

Ingred Name: ING 6: ANSI Z49.1 & OTHER GOVT & CONTEMPLATED OPERATIONS. RTECS #:99999992Z

Ingred Name:RESP PROT: TYPE UNDER CNDTNS EXCEEDING TWA STANDARD. RTECS #:99999992Z

Ingred Name:VENT: THAN 60 FT PER MIN HOOD FACE VELOCITY FOR CONFINED SPACES. PROVIDE VENT SUFFICIENT TO PVNT EXCEEDING (ING 10) RTECS #:9999999ZZ

Ingred Name:ING 9: RECOM EXPOS LIMIT OR BUILDUP OF EXPLOSIVE CONCENTRATION S OF VAPOR IN AIR. RTECS #:99999992Z

Ingred Name:HYGIENE PRACT: REUSE. REMOVE CONTAMD SHOES & THORO CLEAN BEFORE REUSE; DISCARD IF OIL-SOAKED. CLEANSE SKIN (ING 12) RTECS #:9999999ZZ

Ingred Name:ING 11: THORO AFTER CNTCT, BEFORE BREAKS & MEALS & AT END OF WRK PERIOD. PROD IS READILY REMOVED FROM SKIN BY (ING 13) RTECS #:9999999ZZ

Ingred Name:ING 12: WATERLESS HAND CLEANERS FOLLOWED BY WASHING THOROUGHLY W/SOAP & WATER. RTECS #:9999999ZZ

Ingred Name: EYE PROTECTION: WITH FULL LENG

TH FACESHIELD . RTECS #:99999992Z Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50: (ORAL) > 5 G/KG (TOTAL BODY WT) Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: HEALTH STUDIES HAVE SHOWN THAT MANY PETRO HYDROCARBONS & SYNTHETIC LUBRICANTS POSE POTENTIAL HUMAN HEALTH RISKS WHICH VARY FROM PERSON TO PERSON. AS A PRECA UTION, EXPOS TO LIQS, VAPS, MISTS/FUMES SHOU LD BE MINIMIZED. PRLNG/RPTD SKIN CONTACT W/PROD TENDS TO REMOVE SKIN OILS POSS LEADING TO **IRRITATION & (EFTS OF OVEREXP)** Explanation of Carcinogenicity:NOT RELEVANT Effects of Overexposure: HLTH HAZ: DERMATITIS; HOWEVER, BASED ON HUMAN EXPERIENCE & AVAIL TOXICOLOGICAL DATA, PROD IS JUDGED NEITHER "CORROSIVE" NOR "IRRITANT" BY OSHA CRITERIA. PROD CONTACTING EYE MAY CAUSE IRRIT. PROD HAS L OW ORDER OF ORAL & DERMAL TOXICITY. Ρ

OSS ASPIRATION HAZ. INDUCED VOMITING MAY CAUSE ASPIRATION OF PROD INTO LUNGS.

Medical Cond Aggravated by Exposure:UNKNOWN.

First Aid:EYES: FLUSH W/CLEAR WATER FOR AT LEAST 15 MIN UNTIL IRRIT SUBSIDES. IF IRRIT PERSISTS, CALL MD. SKIN: REMOVE CONTAMD CLTHG & WASH SKIN THORO W/SOAP & WATER. INHAL: VAP PRESS IS VERY LOW. VAP INHAL UND ER AMBIENT CNDTNS IS NORM NOT PROB. IF OVERCOME BY VAP FROM HOT PROD, IMMED

REMOVE FROM EXPOS & CALL MD. IF BRTHG IS IRREGULAR/HAS STOPPED, START RESUSCITATION; ADMIN OXYGEN IF AVAIL. IF (SUPDAT)

Flash Point Method:COC
Flash Point:320F,160C
Lower Limits:1%
Upper Limits:6%
Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, FOAM OR CARBON DIOXIDE.
Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP.
WATER/FOAM MAY CAUSE FROTHING. USE WATER TO KEEP FIRE-EXPOS CNTNRS

COOL. WATER FROTH MAY BE USED TO (SUPDAT) Unusual Fire/Explosion Hazard:NOT APPLICABLE.

Spill Release Procedures: KEEP PROD OUT OF SEWERS & WATERCOURSES BY DIKING/IMPOUNDING. ABSORB W/SAND/INERT MATL. SWEEP/SCOOP UP & REMOVE. PVNT SPREAD OF SPILL. ADVISE AUTH IF PROD HAS ENTERED/MAY ENTER SEWERS, WATERCOURSES/EXT ENSIVE LAND AREAS, ASSURE CONFORMITY W/LOCAL REGS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTUR ER. Handling and Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS. Other Precautions: EMPTY CNTNRS RETAIN RESIDUE (LIQ/VAP) & CAN BE DANGEROUS. DO NOT PRESSURIZE, WELD, CUT, BRAZE, SOLDER, DRILL, GRIND/EXPOSE SUCH CNTNRS TO HEAT, FLAME, SPKS/OTHER SOURCES OF IGNIT; THEY MAY EXPLODE & C AUSE INJURY/DEATH. DO NOT (SUPDAT) ======== Exposure Controls/Personal Protection ======== Respiratory Protection: USE ONLY NIOSH/MSHA APPRVD EQUIP. NORM NOT NEEDED AT AMBIENT TEMPS. USE SUPPLIED AIR RESP PROT IN CONFINED/ENCLOSED SPACES, IF NEEDED. USE FILTER, DUST, FUME/MIST RESP TYPE UNDER MIST CNDTNS. USE CAN/ CARTRIDGE, GAS/VAP RESP TYPE (ING 8) Ventilation: ALWAYS AMINTAIN BELOW PERMISSIBLE EXPOS LIMS. USE LOC EXHST TO CAPTURE VAP, MIST/FUMES, IF NEC. PROVIDE GREATER (ING 9) Protective Gloves: CHEMICAL-RESISTANT GLOV ES. Eye Protection: ANSI APPRVD CHEM WORKER GOGGLES (ING 14) Other Protective Equipment: USE CHEM-RESISTANT APRON/OTHER IMPERVIOUS CLTHG TO AVOID CONTAM REGULAR CLTHG WHICH COULD RSLT IN PRLNG/RPTD SKIN CNTCT. Work Hygienic Practices: MINIMIZE BRTHG VAP, MIST/FUMES. AVOID PRLNG/RPTD CNTCT W/SKIN. REMOVE CONTAMD CLTHG; LAUNDER/DRY-CLEAN **BEFORE (ING 11)** Supplemental Safety and Health FIRE FIGHT PROC: FLUSH SPILLS AWAY FROM EXPOS. MINIMIZE BRTHG GASES, VAP, FUMES/DECOMP PRODS. FIRS

## T AID PROC: OVEREXP TO OIL MIST, REMOVE FROM FURTHER EXPOS UNTIL EXCESS OIL MIST CNDTN SUBSIDES. INGES T: DO NOT INDUCE VOMIT. CALL MD IMMED. OTHER PREC: ATTEMPT TO CLEAN SINCE RESIDUE IS DFCLT TO REMOVE. "EMPTY" (ING 5)

Boiling Pt:B.P. Text:WIDE RANGE Vapor Pres:8 Spec Gravity: