View NSN Online: https://aerobasegroup.com/nsn/6850-01-393-9049

CHEMTRONICS INC -- ELCTRONICS CLEANER/DEGREASER 2000 -- 6850-01-393-9049

Product ID:ELCTRONICS CLEANER/DEGREASER 2000 MSDS Date:01/26/1997 FSC:6850 NIIN:01-393-9049 MSDS Number: BWNSP === Responsible Party === **Company Name: CHEMTRONICS INC** Address:8125 COBB CENTER DRIVE City:KENNESAW State:GA ZIP:30144 Country:US Info Phone Num:404-424-4888 **Emergency Phone Num:40** 4-424-4888/800-424-9300(CHEMTREC) Preparer's Name: MICHAEL S. WATKINS CAGE:2M589 === Contractor Identification === Company Name: CHEMTRONICS INC Address:8125 COBB CENTER DRIVE Box:City:KENNESAW State:GA ZIP:30152 Country:US Phone:770-424-4888/800-645-5244 CAGE:21267 Company Name: CHEMTRONICS INC (CANCELLED USE 21267) City:HAUPPAUGE State:NY ZIP:11760 Country:US CAGE:2M589

======= Composition/Information on Ingredients ==========

Ingred Name:1,1-DICHLORO-1-FLUOROETHANE (SARA 313) CAS:17

17-00-6 RTECS #:KI0997000 Fraction by Wt: 90-95% Other REC Limits:NONE RECOMMENDED Ozone Depleting Chemical:2

Ingred Name:ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9596

Ingred Name:METHYLCYCLOHEXANE CAS:108-87-2 RTECS #:GV6125000 Fraction by Wt: 0.1-1.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:400 PPM; 9596

Ingred Name:CARBON DIOXIDE CAS:124-38-9 RTECS #:FF6400000 Frac tion by Wt: 1-5% Other REC Limits:NONE RECOMMENDED OSHA PEL:5000 PPM ACGIH TLV:5000PPM/30000STEL;96

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES-LIQUID, AEROSOLS & VAPORS ARE IRRITATING. SKIN-CONTACT CAUSES SKIN IRRITATION. INGESTION-HARMFUL IF SWALLOWED. IRRITATING TO MOUTH,THROAT & STOMACH. INHALATION-HARMFUL IF

INHALED.

Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYES-CAN CAUSE PAIN, TEARING, REDDENING & SWELLING. INGESTION-MAY CAUSE VOMITING. INHALATION-HIGH CONCENTRATIONS OF VAPORS IN IMMEDIATE AREA CAN DISPLACE OXYGEN AND CAUSE DIZZINESS, UNCONSCIOUSNESS, A ND EVEN DEATH WITH LONGER EXPOSURE. KEEPPEOPLE AWAY FROM SUCH VAPORS WITHOUT SELF-CONTAINE D BREATHING APPARATUS.

Medical Cond Aggravated by Exposure:HEART, LUNG, SKIN, EYE.

======================================
First Aid:EYES-IMMEDIATELY FLUSH WITH PLENTY OF WATER. HAVE EYES EXAMINED. SKIN-WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION FOR IRRITATION. INGESTION-DO NOT INDUCE VOMITIN G, BUT GIVE 1 OR 2 GLASSES OF WATER TO DRINK AND GET IMMEDIATE MEDICAL ATTENTION. INHALATION-REMOVE TO FRESH AIR. I F NOT
BREATHING, CPR OR OXYGEN. GET MEDICAL ATTENTION.
======================================
Flash Point Method:TCC Flash Point:NONE TO BOILING Lower Limits:7.4 Upper Limits:15.5
Extinguishing Media:USE ALCOHOL FOAM, CARBON DIOXIDE, OR WATER SPRAY WHEN FIGHTING FIRES INVOLVING THIS MATERIAL. Fire Fighting Procedures:AS WITH ANY FIRE, WEAR SELF-CONTAINED BREATHING APPARATUS (PRESSURE-DEMAND, MSHA/NIOSH APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GE
AR. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.
======================================
Spill Release Procedures:SMALL SPILL: ABSORB SPILL WITH INERT MATERIAL (E.G. DRY SAND OR EARTH) THEN PLACE IN A CHEMICAL WASTE CONTAINER FOR PROPER DISPOSAL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions: DO NOT REUSE THIS CONTAINER. STORE IN
A COOL DRY PLACE AWAY FROM HEAT, SPARKS AND FLAME. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID DIRECT SUNLIGHT. Other Precautions:AVOID PROLONGED OE REPEATED CONTACT WITH EYES, SKIN AND CLOTHING. WASH HANDS BEFORE EATING. USE WITH ADEQUATE VENTILATION. AVOID BREATHING PRODUCT VAPOR OR MIST.
======================================
Respiratory Protection:WEAR A POSITIVE PRESSURE AIR-SUPPLIED RESPIRATOR IN SITUATIONS WHERE THERE MAY BE POTENTIAL FOR AIRB

ORNE EXPOSURE.
Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. LOCAL EXHAUST VENTILATION MAY BE NECESSARY.
Protective Gloves:RUBBER/CHEMICAL RESISTANT GLOVES.
Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS.
Other Protective Equipment:CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. AN EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE.
Work Hygienic Practices:WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACI LITIES.
Supplemental Safety and Health

NONFLAMMABLE GAS.

HCC:V2 Boiling Pt:=32.2C, 90.F Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN Decomp Temp:Decomp Text:NOT GIVEN Vapor Pres:493 @70F Vapor Density:>1 Spec Gravity:1.23 Viscosity:1 Evaporation Rate & amp; Reference:>1 (N-BUTYL ACETATE=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR, COLORLESS LIQUID. ETHEREAL ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES
DO NOT MIX WITH POWDERED ALKALI AND ALKALILNE EARTH METALS OR STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:DO NOT SPRAY NEAR OPEN FLAMES, RED HOT SURFACES OR OTHER SOURCES OF IGNITION.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE & INCOMPLETELY BURNED HYDROCARBONS, HYDROCHLORIC AND HYDROFLUORIC ACID VAPOR.

========= Disposal Considerations ========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. WATER RUNOFF CAN CAUSE ENVIRONMENTAL DAMAGE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.