

INTERNATIOAL LUBRICANTS CO INC -- LUBRICATING OIL ACMA COMPOUND 7 -- 9150-00-011-5892

===== Product Identification =====

Product ID:LUBRICATING OIL ACMA COMPOUND 7

MSDS Date:04/07/1994

FSC:9150

NIIN:00-011-5892

MSDS Number: BWPDF

=== Responsible Party ===

Company Name:INTERNATIOAL LUBRICANTS CO INC

Address:10363 AIRLINE HIGHWAY

City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Info Phone Num:504-469-

0940

Emergency Phone Num:504-469-0940/800-424-9300(CHEMTREC)

CAGE:JO811

=== Contractor Identification ===

Company Name:CROWN OIL & CHEMICAL CO.

Address:751 HILL STREET

Box:City:JEFFERSON

State:LA

ZIP:70121

Country:US

Phone:504 OUT OF BUSINESS

CAGE:0CF76

Company Name:INTERNATIONAL LUBRICANTS INC

Address:10363 W AIRLINE HWY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940(504-471-0104FAX)

CAGE:0W1H4

Company Name:INTERNATIONAL LUBRICATES INC

Address:10363 AIRLINE HIGHWAY

Box:

City:SAINT ROSE
State:LA
ZIP:70087
Country:US
Phone:504-469-0940
CAGE:JO811

Company Name:UNI-KEM INTERNATIONAL
Address:1001 HARIMAW COURT EAST
Box:City:METAIRIE
State:LA
ZIP:70001
Country:US
Phone:504-835-7600/FAX:504-835-7608
CAGE:4S446

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBON LUBRICANT
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5MG/
M3

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: LOW HEALTH HAZARD. MINIMAL
IRRITATION ON CONTACT. INHALATION OF VAPORS OR MISTS WHEN SPRAYING
MAY CAUSE IRRITATION. SLIGHTLY TOXIC IF SWALLOWED. CHRONIC:
DERMATITIS. ACCIDENTAL RELEASE UNDER HI GH PRESSURE APPLICATIONS
MAY RESULT IN INJECTION OF OIL INTO THE SKIN CAUSING LOCAL
NECROSIS.

Explanation of Carcinogenicity:NONE OF THE
INGREDIENTS IN THIS PRODUCT

IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYES: MINIMAL IRRITATION. SKIN: IRRITATION,
SKIN DRYING ON PROLONGED CONTACT. INHALATION: IRRITATION OF NOSE
AND THROAT. INGESTION: DISCOMFORT, NAUSEA, DIARRHEA. INJECTION:
NECROSIS MAY BE EVIDENCED B Y DELAYED ONSET OF PAIN AND TISSUE
DAMAGE A FEW HOURS FOLLOWING PRESSURE INJECTION.

Medical Cond Aggravated by Exposure:BECAUSE OF ITS DEFATTING
PROPERTIES, PROLONGED AND REPE

ATED SKIN CONTACT MAY AGGRAVATE AN
EXISTING DERMATITIS.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, SEE DOCTOR. SKIN: WASH WITH SOAP. IF IRRITATION PERSISTS, SEE DOCTOR. INHALATION: REMOVE VICTIM TO FRESH AIR. GIVE OXY GEN/CPR IF NEEDED. SEE DOCTOR. INGESTION: DO NOT INDUCE VOMITING. SEE DOCTOR. INJECTION: THIS IS A MEDICAL EMERGENCY. SEE DOCTOR IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>392F,>200C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 100F,IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND

STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:MECHANICAL (GENERAL) VENTILATION.

Protective Gloves:NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHING

AS REQUIRED TO MINIMIZE
EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH AND SAFETY
SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE. DISCARD
CONTAMINATED SHOES

Supplemental Safety and Health

USED GASOLINE MOTOR OILS HAVE BEEN SHOWN TO CAUSE SKIN CANCER WHEN
REPEATEDLY APPLIED TO MOUSE SKIN WITHOUT ANY EFFORT TO REMOVE THE
MATERIAL BETWEEN APPLICATIONS. THERE IS NO EVIDENCE OF A CAUSAL REL

ATIONSHIP BETWEEN SKIN CANCER IN HUMANS AND EXPOSURE TO USED MOTOR
OIL.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>626F,>330C

Vapor Pres:NEGLIGIBLE

Spec Gravity:0.89

Viscosity:>100 SUS

Evaporation Rate & Reference:0

Solubility in Water:0

Appearance and Odor:LIQUID;DARK GREEN;PUNGENT SULFUR-TYPE ODOR.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to

Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES
OF IGNITION

Hazardous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE,OXIDES
OF PHOSPHOROUS AND SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER.
DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling

agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.