

KINNEY VACUUM CO -- SUPER X OIL-VACUUM PUMP LUBRICANT, D-250-76

=====  
MSDS Safety Information  
=====

FSC: 9150  
NIIN: 00-569-7007  
MSDS Date: 05/04/1994  
MSDS Num: BWPRY  
Product ID: SUPER X OIL-VACUUM PUMP LUBRICANT, D-250-76  
MFN: 02  
Responsible Party  
Cage: 33781  
Name: KINNEY VACUUM CO  
Address: 495 TURNPIKE ST  
City: CANT  
ON MA 02021  
Info Phone Number: 617-828-9500  
Emergency Phone Number: 617-828-9500  
Preparer's Name: A. H. BORNEMANN  
Proprietary Ind: Y  
Published: Y

=====  
Contractor Summary  
=====

Cage: 33781  
Name: KINNEY VACUUM CO A UNIT OF GENERAL SIGNAL CORP  
Address: 495 TURNPIKE ST  
City: CANTON MA 02021-2702  
Phone: 617-828-9500

=====  
Item Description Information  
=====

Item Name: LUBRICATING OIL,VACUUM PUMP  
=====

Ingredients  
=====

Name: \*\*\* PROPRIETARY \*\*\*  
-----  
=====

Health Hazards Data  
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.  
Route Of Entry Inds - Inhalation: YES

Skin: YES  
Ingestion: YES  
Carcinogenicity Inds - NTP: NO  
IARC: NO  
OSHA: NO

Effects of Exposure: INHALATION: EXPOSURE TO OIL MIST OR VAPOR IN EXCESS OF LIMIT MAY CAUSE BREATHING IRRITATION, HEADACHE AND NAUSEA. SKIN/EYES: MAY CAUSE IRRITATION TO SENSITIVE SKIN AND WITH EYE CONTACT. PROLONGED SKIN CONTACT MAY LEAD TO SKIN DISORDERS. INGESTION: MAY CAUSE NAUSEA, STOMACH IRRITATION OR CRAMPS.

Explanation Of Carcinogenicity: NOT RELEVANT

Signs And Symptoms Of Overexposure: SEE HEALTH HAZARDS

Medical Cond Aggravated By Exposure: NOT KNOWN. IF IRRITATION PERSISTS SEE MD.

First Aid: INHAL: REMOVE TO FRESH AIR. SKIN: REMOVE OILY CLOTHING. WASH SKIN WITH WATER AND SOAP. EYES: FLUSH EYES WITH CLEAN WATER FOR AT LEAST 15 MINUTES. INGEST: DO NOT INDUCE VOMITING.

=====  
Handling and Disposal  
=====

Spill Release Procedures: MECHANICAL CLEAN UP: USE OIL ABSORBENT (SPEED DRY).  
NORMAL CONTA

INER SIZES UP TO 5 GALLONS. MAX 55 GALLON DRUM. NOT SUBJECT TO  
RELEASE REPORTS PER SARA TITLE III (313) FOR CHEMICALS IN 40 CFR 372.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DO NOT FLUSH SPILLS OR USED OIL INTO DRAINS OR  
WATERWAYS. USE NORMAL INDUSTRIAL METHOD IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS.

Handling And Storage Precautions: STORE BELOW 120F IN CLOSED METAL OR PLASTIC  
CONTAINER. PREVENT MOISTURE ACCUMULATION AT CONTAINER CLOSURE  
TO RETAIN  
PHYSICAL CHARACTERISTICS.

Other Precautions: VACUUM PUMP DISCHARGE MUST BE FILTERED TO AVOID EXCESSIVE  
OIL USE AND OIL MIST/VAPOR CONCENTRATION INSIDE PER OSHA AND OUTSIDE PER EPA.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Method: COC

Flash Point Text: >450F,>232C

Lower Limits: 0.9%

Upper Limits: 7%

Extinguishing Media: FOAM, DRY CHEMICAL POWDER, CARBON DI

OXIDE.

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT (FP N). USE WATER TO COOL FIRE-EXPOSED CONTAINERS AND TO DISPERSE VAPORS FROM UNIGNITED SPILLS.

Unusual Fire/Explosion Hazard: NONE. NFPA RATING: 1-H/1-F/O-R.

=====  
Control Measures  
=====

Respiratory Protection: NONE NEEDED FOR NORMAL USE. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE O F CONCERN (FP N).

Ventilation: TO COMPLY W/OIL MIST/VAP LIM. PUMP FILTER DISCHARGE W/ANY RESIDUAL SMOKE & PRIMARILY VAP ODOR MAY NEED TO BE (SUPDAT)

Protective Gloves: IMPERVIOUS GLOVES (FP N).

Eye Protection: ANSI APPRVD SAFETY GLASSES (FP N).

Other Protective Equipment: NONE REQUIRED.

Work Hygienic Practices: APPLY GOOD HOUSEKEEPING AND HYGIENE PRACTICE.

Supplemental Safety and Health: VP: <0.001 @ 20C. VENT: PIPED OUTSIDE, SUBJECT TO PUMP CAPACITY & ROOM VOLUME W/PROTECTION AGA INST ENTRY OF RAIN OR SNOW.

=====  
Physical/Chemical Properties  
=====

B.P. Text: >400F,>204C

Vapor Pres: SUPDAT

Vapor Density: >1

Spec Gravity: 0.88 (H\*2O=1)

Solubility in Water: NIL BY VOLUME

Appearance and Odor: CLEAR OIL WITH MILD ODOR.

=====  
Reactivity Data  
=====

Stability Indicator:

YES

Stability Condition To Avoid: FLAME.

Materials To Avoid: STRONG OXIDANTS SUCH AS LIQUID OXYGEN AND CHLORINE.

Hazardous Decomposition Products: SMOKE, CARBON MONOXIDE AND DIOXIDE, SULFUR OXIDES.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT

=====  
Toxicological Information  
=====

=====  
Ecological Infor

mation

=====  
=====  
MSDS Transport Information  
=====  
=====

Regulatory Information  
=====  
=====

Other Information  
=====  
=====

=====  
=====  
HAZCOM Label  
=====

Product ID: SUPER X OIL-VACUUM PUMP LUBRICANT, D-250-76

Cage: 33781

Company Name: KINNEY VACUUM CO A UNIT OF GENERAL SIGNAL CORP

Street: 495 TURNPIKE ST

City: CANTON MA

Zipcode: 02021-2702

Health Emergency Phone: 617-828-9500

Label Required IND: Y

Date Of Label Review: 03/01/1995

Status Code: C

Label Date: 03/01/1995

Origination Code: G

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: CA

UTION

Respiratory Protection IND: YES

Health Hazard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: ACUTE: INHALATION: EXPOSURE TO OIL MIST OR VAPOR IN EXCESS OF LIMIT MAY CAUSE BREATHING IRRITATION, HEADACHE AND NAUSEA.

SKIN/EYES: MAY CAUSE IRRITATION TO SENSITIVE SKIN AND WITH EYE CONTACT.

PROLONG ED SKIN CONTACT MAY LEAD TO SKIN DISORDERS. INGESTION: MAY CAUSE NAUSEA, STOMACH IRRITATION OR CRAMPS. CHRONIC: NONE LISTED BY MANUFACTURER.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrum

entality of the United

States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.