

VELSICOL CHEMICAL CORP -- MIL-H-46170B TYPE 2, PROD/MSDS#:0425599 -- 9150-01-119-8149

=====
Product Identification
=====

Product ID:MIL-H-46170B TYPE 2, PROD/MSDS#:0425599

MSDS Date:02/21/1991

FSC:9150

NIIN:01-119-8149

MSDS Number: BWPTK

=== Responsible Party ===

Company Name:VELSICOL CHEMICAL CORP

Address:10400 W. HIGGINS, SUITE 600

City:DES PLAINES

State:IL

ZIP:60018

Country:US

Info Phone Num:7

08-635-3471

Emergency Phone Num:708-298-9000

Preparer's Name:MANAGER, PRODUCT SAFETY

CAGE:VELSI

=== Contractor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

Company Name:VELSICOL CHEMICAL CORPORATION

Address:10400 W HIGGINS ROAD

Box:City:ROSEMONT

State:IL

ZIP:60018

Country:US

Phone:847-298-9000

CAGE:0Z6C4

Company Name:VELSICOL CHEMICAL CORPORATION

CAGE:VELSI

=====
Composition/Inf

ormation on Ingredients =====

Ingred Name:(PETROLEUM SULFONATE) BARIUM DINONYLNAPHTHALENE- SULFONATE
CAS:25619-56-1
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

Ingred Name:BARIUM COMPOUNDS
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE ESTABLISHED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute an

d Chronic:LOW ORAL & DERMAL TOXICITY.

MISTS/FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE/SKIN IRRIT,
NAUSEA, VOMITING, RESPIRATORY TRACT IRRIT. BARIUM COMPOUNDS IS
MODERATE SKIN IRRITANT & IS CORROSIVE TO EYES.

Effects of Overexposure:EYE/SKIN/RESPIRATORY TRACT IRRIT. NAUSEA,
VOMITING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:CONTACT:FLUSH EYES W/PLENTY OF WATER FOR 15MINS. W
ASH SKIN

W/SOAP & WATER. CALL PHYSICIAN IF IRRIT PERSISTS. INHAL:REMOVE TO
FRESH AIR & GIVE CPR OR OXYGEN IF NEEDED. CALL PHYSICIAN. INGEST:DO
NOT IND UCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:430F,221C

Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.

Fire Fighting Procedures:BURNING WILL PROUDCE TOXIC FUMES. WEAR
SELF-CONTAINED BREATHING APPARATUS & FULL TURN-OUT GE

AR TO FIGHT

FIRE. AVOID SPREADING LIQ & FIRE BY WATER FLOODING.

Unusual Fire/Explosion Hazard:EXPOUSRE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL WITH WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:COVER W/AN INERT ABSORBENT MATERAIL & REMOVE TO DISPOSAL CONTAINER. OBEY ALL RELEVANT LOCAL, STATE AND FEDERAL LAWS. DO OT CONTAMINATED ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY.

===== Handling and Storage =====

Handling and Storage Precautions:CAUTION:DO NOT USE OIL ABOVE MAX RECOMMENDED OPERATING TEMP OF 430F. MAY SOFTEN SOME PLASTIC & PAINT SURFACES. WIPE UP SPILLS IMMED.

Other Precautions:AVOID EYE/SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED USE APPROPRIATE NIOSH-APPROVED RESPIRATORY PROTECTIVE EQUIPMENT.

Ventilation:LOCAL EXHAUST & MECHANICAL VENTILATION RECOMM ENDED.

Protective Gloves:IMPERMEABLE GLOVES

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELDS

Other Protective Equipment:EYE WASH FOUNTAIN, SAFETY SHOWER. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.842

Solubility in Water:NEGLIGIBLE

Appearance and Odor:RED LIUQID.

Percent Volatiles by Volume:NOT VL

=====

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDANTS.

Hazardous Decomposition Products: BURNING WILL PRODUCE TOXIC FUMES.

===== Disposal Considerations =====

Waste Disposal Methods: OBEY RELEVANT LOCAL, STATE AND FEDERAL LAWS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY.

Disclaimer (provided with this information by the compiling agencies):

This information is formula

ted for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.