

MINNESOTA MINING AND MFG CO -- 62-0847-8530-2, SCOTCH-GRIP 847 RUBBER & (SUPDAT) --
8040-01-168-0440

===== Product Identification =====

Product ID:62-0847-8530-2, SCOTCH-GRIP 847 RUBBER & (SUPDAT)

MSDS Date:11/20/1992

FSC:8040

NIIN:01-168-0440

MSDS Number: BWRDL

=== Responsible Party ===

Company Name:MINNESOTA MINING AND MFG CO

Address:3M CTR

City:SAINT PAUL (FORMALLY IN DETROITT, MI)

State:MN

Z

IP:55144-1000

Country:US

Info Phone Num:612-733-1341/612-733-1110

Emergency Phone Num:612-733-1341

CAGE:76381

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA 313) (CERCLA) BP: 132F, 56C. FL PT: 0F,
-18C.

CAS:67-64-1

RTECS #:AL3

150000

Fraction by Wt: 60-70%

OSHA PEL:1000 PPM

ACGIH TLV:750 PPM; 1000 STEL

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ACRYLONITRILE BUTADIENE POLYMER

CAS:9003-18-3

Fraction by Wt: 10-20%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:PHENOL FORMALDEHYDE RESIN; (PHENOL-FORMALDEHYDE POLYMER)

CAS:9003-35-4

Fraction by Wt: 7-13%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:GLYCEROL ESTERS OF ROSIN ACIDS

CAS:8050-31-5

D

CAS:69-72-7

RTECS #:VO0525000

Fraction by Wt: 1-5%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:ZINC OXIDE (SARA 313) (CERCLA)

CAS:1314-13-2

RTECS #:ZH4810000

Fraction by Wt: