

EASTMAN KODAK CO. -- ALKALINE BATTERY (KAA, KAA-P TYPE) -- 6135-00-985-7845

=====
Product Identification
=====

Product ID:ALKALINE BATTERY (KAA, KAA-P TYPE)

MSDS Date:07/03/1996

FSC:6135

NIIN:00-985-7845

MSDS Number: BWSGL

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:7

16-722-5151 202-625-3333

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====
Composition/Information on Ingredients
=====

Ingred Nam

e:MANGANESE DIOXIDE
CAS:1313-13-9
RTECS #:OP0350000
Fraction by Wt: 35-40%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:5 MG MN/M3 CEILING
ACGIH TLV:5 MG MN/M3

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 15-20%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM HYDROXIDE (SARA III)
CAS:1310-58-3
RTECS #:TT2100000

Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:GRAPHITE, NATURAL
CAS:7782-42-5
RTECS #:MD9659600
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MPPCF; Z-3
ACGIH TLV:2 MG/M3 RDUST; 9394

Ingred Name:STEEL CASING
Fraction by Wt: 20-25%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PAPER
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALLOY BRASSY
F

raction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:PLASTIC
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:METALIZED PLASTIC LABEL
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV FOR POT HYDROXIDE IS 2MG/M3 CEILING
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SEALED
BATTERY NO HAZARD EXPECTED
UNLESS BATTERY CONTENTS ARE RELEASED. EYES:MAY CAUSE BURNS OR
INJURY. SKIN:MAY CAUSE BURNS OR INJURY. INGESTION:MAY BE FATAL IF
SWALLOWED. INHALATION:MAY CAUSE RESPIRATORY IRRITATION.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:BATTERY CONTENTS MAY CAUSE BURNS OR INJURY.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;REMOVE METAL FRAGMENTS;WASH
WITH WATER.GET MEDICAL ATTENTION.EYES:FLUSH WITH WATER FOR 15
MINUTES.GET MEDICAL ATTENTION.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN
OR ARTIFICAL RESPIRATION IF NEEDED.INGEST:DO NOT INDUCE
VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION.IF BATTERY WAS
CHEWED,RINSE MOUTH WITH WATER.

=====
===== Fire Fighting Measures =====
===

Flash Point:NONE
Lower Limits:NOT GIVEN
Upper Limits:NOT GIVEN
Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:FIRE OR HIGH TEMPERATURES MAY CAUSE
BATTERY TO VENT AND/OR EXPLODE OR LEAK HAZARDOUS VAPORS. DAMAGED OR
OPENED BATTERIES CAN RESULT IN RAPID HEATING.

=====
===== Accidental Release Measures =====

Spill Rel

ease Procedures:NO SPECIAL REQUIREMENTS
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE BELOW 70F IN A DRY, WELL-VENTILATED PLACE.AVOID HIGH TEMPERATURE AND HUMIDITY.
Other Precautions:DO NOT DISASSEMBLE, SHORT OR REVERSE POLARITY.AVOID BREATHING VAPORS FROM LEAKERS.AVOID SKIN AND EYE CONTACT WITH BATTERY CONTENTS.DO NOT ENCASE IN AIRTIGHT COMPARTMENTS(H2 GAS HAZARD).

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT NEEDED IN NORMAL SERVICE.
Ventilation:SUPPLEMENTAL VENTILATION MAY BE NEEDED IN SPECIAL CIRCUMSTANCES TO CONTROL FUMES/VAPORS TO AN ACCEPTABLE LEVEL.
Protective Gloves:IMPERVIOUS GLOVES.
Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS.
Other Protective Equipment:PROVIDE A LOCAL EYE WASH STATION.
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING IF CONTENTS OF BATTERY ARE RELEASED.
Supplemental Safety and Health
NOTE TO PHYSICIAN:INTACT BATTERIES SMALLER THAN 22-25MM MAY PASS SAFELY THROUGH THE GUT.

=====
Physical/Chemical Properties
=====

HCC:N1
Boiling Pt:B.P. Text:NOT GIVEN
Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN
Vapor Pres:NEGLIGIBLE
Vapor Density:NOT GIVEN
Spec Gravity:NOT GIVEN
Evaporation Rate & Reference:NOT GIVEN
Solubility in Water:INSOLUBLE
Appearance and Odor:SOLID;ODORLESS.

=====
Stability and Reactivity Data
=====

=====

Stability Indicator/Materials to Avoid: YES

NONE WITH COMMON MATERIALS AND CONTAMINANTS WITH WHICH THE MATERIAL MAY REASONABLY COME INTO CONTACT.

Stability Condition to Avoid: HIGH TEMPERATURES.

Hazardous Decomposition Products: NONE SPECIFIED BY MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods: DO NOT INCINERATE OR EXPOSE TO FIRE. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.