

FUEL QUALITY SERVICES, INC. -- LTSA-15 -- 6850-01-167-4789

=====  
===== Product Identification =====

Product ID:LTSA-15  
MSDS Date:04/11/1995  
FSC:6850  
NIIN:01-167-4789  
MSDS Number: BWSHL  
=== Responsible Party ===  
Company Name:FUEL QUALITY SERVICES, INC.  
Address:1754 GREEN ROAD  
Box:317  
City:BUFORD  
State:GA  
ZIP:30518  
Country:US  
Info Phone Num:404-945-7139/800-827-9790  
Emergency Phone Num:800-441-3637/800-4  
24-9300(CHEMTREC)  
CAGE:40161  
=== Contractor Identification ===  
Company Name:FUEL QUALITY SERVICES, INC.  
Address:4584 CANTRELL ROAD  
Box:1380  
City:FLOWERY BRANCH  
State:GA  
ZIP:30542  
Country:US  
Phone:(800) 827-9790 - (770) 967-9790  
CAGE:40161

=====  
===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETROLEUM SOLVENT/KEROSENE  
CAS:8008-20-6  
RTECS #:OA5500000  
Fraction by Wt: 50 - 58%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3 AS OIL MIST  
ACGIH TLV:5 MG/M3 AS

OIL MIST

Ingred Name:TRADE SECRET COMPONENT/NJ TRADE SECRET # 00850201001-5029 P

Fraction by Wt: 8- 12.6%

Other REC Limits:NONE RECOMMENDED

Ingred Name:STYRENE MONOMER (SARA 313)

CAS:100-42-5

RTECS #:WL3675000

Fraction by Wt: 0- 0.84%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:S,50PPM/100STEL;9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:N,N-DIMETHYLCYCLOHEXYLAMINE

CAS:98-94-2

RTECS #:GX1198000

Fraction by Wt: 10-14.7%

Other REC Limits:NONE RECOMMENDED

Ingred N

ame:N,N'DISALYCYLIDENE-1,2 PROPANE DIAMINE

CAS:94-91-7

RTECS #:GP3130000

Fraction by Wt: 0.8-2.1%

Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 0.2-0.6%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9596

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA 313)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 0-0.084%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/125STEL;9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:3,5-XYLENOL/MIXED CRESOLS AND XYLENOLS  
CAS:108-68-9  
RTECS #:ZE6475000  
Fraction by Wt: 0.0-0.2%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:TRADE SECRET COMPONENT/NJ TRADE SECRET REGISTRY #  
00850201001-5030 P  
Fraction by Wt: 4.2-8.4%  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) 12,700 MG/KG (KE  
ROSENE)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:LIVER, KIDNEY, CNS,  
LUNG, BLOOD, HEART. ACUTE- CORROSIVE TO EYE & SKIN. INHALATION MAY  
HAVE EFFECTS ON HEART, CNS, BLOOD, LIVER, KIDNEY, SPLEEN, BONE  
Marrow. INGESTION MAY CAUSE GI BLEED ING, CNS DEPRESSION, VOMITING.  
ASPIRATION HAZARD. CHRONIC- MAY CAUSE ALLERGIC SKIN REACTION.

Explanation of Carcinogenicity:CONTAI  
NS STYRENE. MOUSE SKIN PAINTING

STUDIES INDICATE THAT PETROLEUM MIDDLE DISTILLATE SUCH AS KEROSENE  
CAUSES CANCER.

Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, NAUSEA,  
VOMITING, DROWSINESS, BLURRED VISION, PAIN, BURNS, COUGHING,  
WHEEZING, SHORTNESS OF BREATH, COLLAPSE, UNCONSCIOUSNESS, BLEEDING

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING  
DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, LIVER, KIDNEYS, BONE  
Marrow, BLOOD CELLS, CNS MAY HAVE IN  
CREASED SUSCEPTIBILITY TO THE  
TOXICITY OF EXCESSIVE EXPOSURES.

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH  
AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES/SKIN:FLUSH WITH WATER FOR  
15 MINUTES. HOLD EYELIDS OPEN. ORAL:DO NOT INDUCE VOMITING. CALL  
PHYSICI AN OR POISON CONTROL CENTER IMMEDIATELY. IF CONSCIOUS,  
DRINK 2 GLASSES OF WATER. NEVER GIVE ANYTIHING BY MOUTH TO AN  
UNCONSCIOUS PE

PERSON. NOTE TO PHYSICIAN: ACTIVATED CHARCOAL MIXTURE  
MAY BE USEFUL.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:109F,43C

Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE (CO2), FOAM OR DRY  
CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED  
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:FLAMMABLE. VAPOR CAN TRAVEL CONSIDERABLE

DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY  
RUPTURE.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES  
OF IGNITION. VENTILATE AREA. SOAK UP SPILL WITH SAWDUST, SAND,  
EARTH, VERMICULITE. TRANSFER TO CONTAINER. PREVENT LIQUID FROM  
ENTERING SEWERS. REPORT A RELEASE OF 100 LBS OR MORE TO  
AUTHORITIES.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, VENTILATED AREA,  
AWAY FROM IGNITION SOURCES & INCOMPATIBLES. KEEP CONTAINER TIGHTLY  
CLOSED.

Other Precautions:EMPTY CONTAINERS RETAIN RESIDUE AND CAN BE DANGEROUS.  
DO NOT WELD, SOLDER OR DRILL SUCH CONTAINERS. KEEP OUT OF REACH OF  
CHILDREN. DO NOT INGEST. DO NOT GET IN EYES OR ON SKIN. DO NOT  
BREATHE VAPORS. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED OR FOR SYMPTOMS OF OVER  
EXPOSURE, WEAR NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR OR  
AIR-PURIFYING RESPIRATOR. IN EMERGENCY, WEAR A NIOSH-APPROVED  
POSITIVE-PRESSURE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)  
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:RUBBER/LATEX

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective E

equipment:SAFETY SHOWER AND EYE WASH FOUNTAIN SHOULD BE LOCATED NEARBY. WEAR APPROPRIATE PROTECTIVE CLOTHING FOR RISK OF EXPOSURE.

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

FORMULA AND/OR PERCENTAGES CHANGED. FOR PREVIOUS FORMULATIONS/CONCENTRATIONS, SEE PNI A OR B, SAME NSN.

===== Physical/Chemical Properties =====

HCC:F6

NRC/

State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:351F,177C

Spec Gravity:0.90

Solubility in Water:IMMISCIBLE

Appearance and Odor:AMBER LIQUID - AMINES ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE REASONABLY FORESEEABLE.

Stability Condition to Avoid:HIGH HEAT, SPARKS, FLAME, OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN AND OTHER DECOMPOSITION PRODUCTS MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS. RECYCLING OR REUSING IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.