

COURTAULDS AEROSPACE INC -- PR-1201-RLS, POLYSULFIDE SEALANT, ACCELERATOR --  
8030-01-110-6184

===== Product Identification =====

Product ID:PR-1201-RLS, POLYSULFIDE SEALANT, ACCELERATOR

MSDS Date:09/23/1993

FSC:8030

NIIN:01-110-6184

MSDS Number: BXBQD

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

|

Info Phone Num:818-240-2060

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:A SHARABY

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRC-DESOTO INTL INC

Address:5454 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91203

Country:US

Phone:818-240-2060/800-228-5635

CAGE:92108

===== Com

position/Information on Ingredients =====

Ingred Name:LEAD DIOXIDE  
CAS:1309-60-0  
RTECS #:OG0700000  
Fraction by Wt: 65%  
OSHA PEL:0.05 MG/M3 (MFR)  
ACGIH TLV:0.15 MG/M3 (MFR)

Ingred Name:TERPHENYLS, HYDROGENATED; (HYDROGENATED TERPHENYLS)  
CAS:61788-32-7  
RTECS #:WZ6535000  
Fraction by Wt: 25%  
OSHA PEL:0.5 PPM  
ACGIH TLV:0.5 PPM

Ingred Name:LEAD MONOXIDE  
CAS:1317-36-8  
RTECS #:OG1750000  
Fraction by Wt: 10%  
OSHA PEL:0.05 MG/M3 (MFR)  
ACGIH TLV:0.15 MG/M3 (MFR)

===== Hazards I  
dentification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:LEAD APPEARS ON NAVY LISTING OF OCCUP  
CHEM REPROD HAZARDS. SEEK CONSULTATION FROM APPROP HEALTH  
PROFESSIONALS CONCERNING LATEST HAZARD LIST INFORMATION & SAFE  
HANDLING & EXPOSURE INFO . MOST SIG NIFICANT HLTH HAZ OF LEAD  
DIOXIDE IS BYINHAL OF AIRBORNE D  
UST PARTICLES. IN THIS PROD, LEAD  
DIOXIDE (EFTS OF OVEREXP)  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:HLTH HAZ:IS THORO & PERM WETTED, & THEREFORE  
DOES NOT PRESENT RISK OF EXPOS TO DUST PARTICLES. HOWEVER, INORG  
LEAD CMPDS IN GEN ARE TOX BY INGESTION, ALTHOUGH NOT READILY  
ABSORB. ANEMIA, CENTRAL NERVO US SYSTEM EFTS, ABDOMINAL  
COLIC/KIDNEY FUNCTION LOSS CAN OCCUR @ BLOOD LEAD LEV OF 60  
MICROGRAMS/100 GRAMS. (SUPDAT)  
Medical Cond Aggravated by Ex



APPRVD EMERGENCY EYE WASH & DELUGE  
SHOWER .

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE  
SMOKING OR EATING.

Supplemental Safety and Health

EFTS OF OVEREXP:REC MAX IS 40 MICROGRAMS/100 GRAMS.

===== Physical/Chemical Properties =====

Spec Gravity:2.65

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK BROWN PASTE

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Mat

erials to Avoid:YES

EASILY OXIDIZABLE MATERIALS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:SMOKE; SOOT; CARBON MONOXIDE; CARBON  
DIOXIDE; LEAD COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN COMPLIANCE W/FEDERAL, STATE AND  
LOCAL REGULATIONS. D008 EPA HAZARDOUS WASTE. DISPOSE OF SPILLAGE IN  
COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with t  
his information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.