

TONER ETC -- TONER,TEC. TYPE III, HP 92291A -- 6850-01-343-6998

===== Product Identification =====

Product ID:TONER,TEC. TYPE III, HP 92291A

MSDS Date:07/20/1993

FSC:6850

NIIN:01-343-6998

MSDS Number: BXCCR

=== Responsible Party ===

Company Name:TONER ETC

Address:124 HERITAGE AVE

City:PORTSMOUTH

State:NH

ZIP:03801

Country:US

Info Phone Num:603-431-0705 703-971-7628 VA #

Emergency Phone Num:303-62

3-5716/603-880-5555

CAGE:0YL79

=== Contractor Identification ===

Company Name:TONER ETC

Address:124 HERITAGE AVE

Box:City:PORTSMOUTH

State:NH

ZIP:03801

Country:US

Phone:800-370-8663 603-431-3624

CAGE:0YL79

===== Composition/Information on Ingredients =====

Ingred Name:STYRENE/ACRYLATE POLYMER, CAS#25213-46-2

Fraction by Wt: 45-55%

Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE, MAGNETITE

CAS:1317-61-9

Fraction by Wt: 45-55%

Other REC Limits:NONE RECOMMENDED

OSHA PE

L:10 MG/M3
ACGIH TLV:5 MG/M3

Ingred Name:BLACK PIGMENT
CAS:31714-55-3
Fraction by Wt: .2-1.5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYOLEFIN, CAS#9003-07-0.
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMORPHOUS SILICA, CAS#68905-20-6.
Fraction by Wt: .3-1.5%
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:N

O OSHA:NO

Health Hazards Acute and Chronic:EYE:MAY CAUSE IRRIT.SKIN:REPEATED

CONTACT MAY CAUSE IRRIT;MAY CAUSE ALLERGIC SKIN

REACTION.INHAL:INHAL OF DUST COULD CAUSES RESP IRRIT ABOVE TLV BUT
CONSIDERED A LOW HAZ.INGEST:MAY CAUSE IRRIT OF MUCO US MEMBRANES OR
DIGESTIVE TRACT.CHRONIC:COMPUTERIZED LITERATURE SEARCH OF NAT
DATABASES DID NOT YIELD CHRONIC EFFECTS.

Explanation of Carcinogenicity:PER MSDS:CARCINOGENICITY

LISTING:NTP/IARC/OSHA:NO.

Effects of Overexposure:EYE IRR

IT. SKIN IRRIT. ALLERGIC SKIN REACTION.

MUCOUS MEMBRANES OR DIGESTIVE TRACT IRRIT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYE:IMMED FLUSH W/PLENTY OF RUNNING WATER FOR 15MINS. OBTAIN
MED ATTN. SKIN:FLUSH AFFECTED AREAS PROMPTLY W/WATER FOR 15MOINS.
REMOVE CONTAMIN CLOTHING. IN CASE OF CONTD IRRIT CONSULT PHYSICIAN.
INHAL :FOR OVER-EXPO REMOVE TO FRESH AIR. INGEST:OBTAIN I

MMED MED
ATTN.

===== Fire Fighting Measures =====

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE OR FOAM.

Fire Fighting Procedures:COTNAINERS SHOULD BE KEPT COOL WITH WATER
SPRAY. TO AVOID INHAL OF TOXIC FUMES WEAR MHSA/NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTIBLE DUST.TONER LIKE MOST ORG MATL
IN POWDER FORM WHEN DISPERSED IN AIR CAN FORM EXPLOSIVE MIXTURES
THAT CAN PRODUCE TOXI
C FUMES SUCH AS CO & CO2.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEPUP/VACUUM.CAREFULLY TRANSFER INTO
SEALABLE WASTE CNTNR.SWEEP SLOWLY TO MIN GENERATION/DUST DURING
CLEANUP.VACUUM USED MOTOR MUST BE RATED AS DUST TIGHT.CONDUCTIVE
HOSE BONDED TO MACHINE SHOULD BE USED TO REDUCE STATAIC
BUILDUP.REMOVE (SUPPLEMEN)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN WELL VENTI AREA.KEEP CNTNR
TIGHTLY CLSD.DO NOT STORE W/INCOMPAT MATLS.DO NOT STORE/CONSUME
FOOND/DRINK/TOBACCO IN AREA WHERE CONTAMIN W/MATL.

Other Precautions:CHEM FORMULATION HAS NOT BEEN TESTED FOR ENVIRO
EFFECTS.ALTHOUGH IN SPILL SITUATION FORMULATION MAY BE
AUSTHETICALLY UNPLEASANT IT'S WATER INSOLUBLE ISN'T EXPECTED TO
SHOW ANY ADVERSE ENVRION EFFECTS.

===== Exposure Controls/Personal Protection =====

=

Respiratory Protection:NONE NEEDED W/WORKING MIXTURES & NORMAL ROOM
VENTILATION IF USED AS INTENEDED. AVOID BREATHING DUST IF SPILLED.

Ventilation:ROOM VENTILATION IS SUFFICIENT UNDER NORMAL OFFICE
CONDITIONS. AVOID USE OF PRODUCT IN UNVENTILATED AREAS.

Protective Gloves:CHEMICAL GLOVES NOT NECESSARY

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH HANDS AFTER HANDLING.

Supplemental Safety and Health

SPILL:RESIDUE W/

SOAP & COLD WATER.GARMENTS MAY BE WASHED/DRY CLEANED
AFT REMOVAL OF LOOSE TONER.

===== Physical/Chemical Properties =====

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:SOFTEN@160F

Spec Gravity:2.94

Solubility in Water:NEGLIGIBLE

Appearance and Odor:FINE BLACK POWDER, SLIGHT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZERS.

Stability Condition to Avoid:EXCESSIVE HEAT OR FLAME.

Hazar

dous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:ACCORDING TO FED REG 40CFR261 MATL NOT HAZ WASTE
WHEN DISCARDED.HOWEVER STATE/LOCAL REQMTS MAY BE MORE
RESTRICTIVE.THEREFORE CONSULTATION W/PROPER STATE/LOCAL AUTHORITIES
IS ADVISED.INCINERATE ONLY IN CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use b

y elements of the Department

of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.