

MOBIL OIL CORP -- MOBIL 600 W CYLINDER OIL -- 9150-01-202-3604

===== Product Identification =====

Product ID:MOBIL 600 W CYLINDER OIL

MSDS Date:03/15/1994

FSC:9150

NIIN:01-202-3604

MSDS Number: BXCPR

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-662-4525/800-227-0707 X3265

Emergency Phone Num:609-

737-4411/CHEMTREC 800-424-9300

Preparer's Name:ENV HEALTH + SAFETY DEPT.

CAGE:3U728

=== Contractor Identification ===

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

CAGE:0T5C6

===== Composition/Information on Ingredients =====

==

Ingred Name:SEVERELY SOLVENT REFINED & SEVERELY HYDROTREATED MINERAL
BASE OILS

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC CONTENT=0.075 LBS/GAL

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >2000MG/KG

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chro

nic:ACUTE: LOW HEALTH HAZARD. MINIMAL

IRRITATION ON CONTACT. INHALATION OF VAPORS OR MISTS WHEN SPRAYING
MAY CAUSE IRRITATION. SLIGHTLY TOXIC IF SWALLOWED. CHRONIC:
DERMATITIS. ACCIDENTAL RELEASE UNDER HI GH PRESSURE APPLICATIONS
MAY RESULT IN INJECTION OF OIL INTO THE SKIN CAUSING LOCAL
NECROSIS.

Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT
IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYES: MINIMAL IRRITATION. SKIN: IR
RITATION,

SKIN DRYING ON PROLONGED CONTACT. INHALATION: IRRITATION OF NOSE
AND THROAT. INGESTION: DISCOMFORT, NAUSEA, DIARRHEA. INJECTION:
NECROSIS MAY BE EVIDENCED B Y DELAYED ONSET OF PAIN AND TISSUE
DAMAGE A FEW HOURS FOLLOWING PRESSURE INJECTION.

Medical Cond Aggravated by Exposure:BECAUSE OF ITS DEFATTING
PROPERTIES, PROLONGED AND REPEATED SKIN CONTACT MAY AGGRAVATE AN
EXISTING DERMATITIS.

=====
===== First Aid Measures =====

First A

id:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF
IRRITATION PERSISTS, SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. IF
IRRITATION PERSISTS, SEE DOCTOR. INHALATION: UNLIKELY ROUTE OF
EXPOSURE . INGESTION: DO NOT INDUCE VOMITING. SEE DOCTOR.
INJECTION: THIS IS A MEDICAL EMERGENCY. SEE DOCTOR IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:540F,282C

Lower Limits:0.6

Upper Limits:7

Extinguishing Media

:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PERSONNEL. ELIMINATE IGNITION SOURCES.

VENTILATE AREA. WEAR PROTECTIVE CLOTHING AND EQUIPMENT. DIKE AND CONTAIN. ABSORB IN INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER AND COVER. WASH AREA WITH SOAP AND WATER.NRC,800-424-8802.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

Other

Precautions:AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:MECHANICAL (GENERAL) VENTILATION.

Protective Gloves:NITRILE GLOVES.

Eye Protection:SPLASH GOGGLES IF MISTING.

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. DISCARD CONTAMINATED SHOES

Supplemental Safety and Health

USED GASOLINE MOTOR OILS HAVE BEEN SHOWN TO CAUSE SKIN CANCER WHEN REPEATEDLY APPLIED TO MOUSE SKIN WITHOUT ANY EFFORT TO REMOVE THE MATERIAL BETWEEN APPLICATIONS. THERE IS NO EVIDENCE OF A CAUSAL RELATIONSHIP BETWEEN SKIN CANCER IN HUMANS AND EXPOSURE TO USED MOTOR

OIL.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Melt/Freeze Pt:M.P/F.P Text:15.8F,-9.0C

Vapor Pres:1

Spec Gravity:0.901

Viscosity:375CS@104F

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID;BROWN;MILD ODOR.

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT.

Haza

rdous Decomposition Products:CARBON DIOXIDE,CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER.
DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or
implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.