

TEXACO LUBRICANTS COMPANY -- 02109 URSA SUPER PLUS SAE 15W-40 -- 9150-01-352-2962

=====  
Product Identification  
=====

Product ID:02109 URSA SUPER PLUS SAE 15W-40

MSDS Date:05/12/1994

FSC:9150

NIIN:01-352-2962

MSDS Number: BXCQM

=== Responsible Party ===

Company Name:TEXACO LUBRICANTS COMPANY

Box:4427

City:HOUSTON

State:TX

ZIP:77210-4427

Country:US

Info Phone Num:800-782-7852

Emergency Phone Num:91

4-831-3400 800-424-9300(CHEMTREC)

Preparer's Name:MANAGER PRODUCT SAFETY

CAGE:TEXLU

=== Contractor Identification ===

Company Name:TEXACO LUBRICANTS

CAGE:TEXLU

Company Name:TEXACO LUBRICANTS CO AFFIL OF TEXACO INC

Address:158 PRIVATE DR 8323

Box:City:PROCTORVILLE

State:OH

ZIP:45669

Country:US

Phone:614-886-7508

CAGE:0TTJ3

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL OIL, SOLVENT REFINED HEAVY PARAFFINIC, SEVERELY  
HYDROTREATED (NON-CARCINOGENIC -  
IARC)

CAS:64741-88-4

RTECS #:PY8040501

Fraction by Wt: 65-75.9%

Other REC Limits:NONE RECOMMENDED

Ingred Name:PETROLEUM OIL

CAS:64741-89-5

RTECS #:PY8041500

Fraction by Wt: 10-19.9%

Other REC Limits:NONE RECOMMENDED

Ingred Name:DISTILLATES, SOLVENT-DEWAXED LIGHT PARAFFINIC

CAS:64742-56-9

RTECS #:PY8039500

Fraction by Wt: 3-9.99%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED

S:64742-65-0  
RTECS #:PY8038501  
Fraction by Wt: 3-9.99%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALKENYLSUCCINIMIDE DISPERSANT, ACCESSION NUMBER 110544  
Fraction by Wt: 3-9.99%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC DIALKYLDITHIOPHOSPHATE  
CAS:84605-29-8  
Fraction by Wt: 0.1-0.9%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC 0,0-BISISODECYL DITHIOPHOSPHATE  
CAS:25103-54-2  
Fraction by Wt: 0.1-0.9%  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification  
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5G/KG  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES:MAY CAUSE MINIMAL  
IRRITATION.SKIN:MAY CAUSE IRRITATION AND DEFATTING.INGEST:MAY CAUSE  
GI TRACT IRRITATION.INHAL:PRODUCT EXPOSED TO HIGH TEMPERATURES MAY  
RELEASE H\*2S(SEE HYDROGEN SULFIDE EXPOSURE IN SIGNS AND  
SYMPTOMS).MAY CAUSE RESPIRATORY IRRITATION.

Explanation of  
Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT  
IS LISTED BY NTP, IARC OR OSHA AS A CARCINOGEN.

Effects of Overexposure:EYES:TEMPORARY  
DISCOMFORT.SKIN:REDNESS,RASH.INHAL:HEADACHE,NAUSEA,DROWSINESS.INGES  
T:ABDOMINAL DISCOMFORT,NAUSEA,DIARRHEA.HYDROGEN SULFIDE  
EXPOSURE:HEADACHE,DIZZINESS,NAUSEA,DIARRHEA,FLUID ON THE LUNGS .MAY  
LEAD TO PARALYSIS,UNCONSCIOUSNESS AND DEATH.

Medical Cond Aggravated by Exposure:BECAUSE OF ITS DEFATTING  
PROPERTIES, PROLONGED AND REPEATED

SKIN CONTACT MAY AGGRAVATE AN  
EXISTING DERMATITIS.

=====  
First Aid Measures  
=====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND WATER.GET MEDICAL ATTENTION IF IRRITATION PERSISTS.EYES:FLUSH WITH WATER FOR 15 MINUTES.GET MEDICAL ATTENTION IF IRRITATION PERSISTS.INHAL:REMOVE T O FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:IF MORE THAN 2 MOUTHFULS ARE SWALLOWED,GIVE 2 GLASSES OF WATER(IF CONSCIOUS)  
.GET PROMPT  
QUALIFIED MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC  
Flash Point:>440F,>227C  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING.  
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.  
Unusual Fire/Explosion Hazard:HYDROGEN SULFIDE MAY BE RELEASED IF OVERHEATED.COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.VENTILATE AREA.SOAK UP WITH A NON-COMBUSTIBLE INERT ABSORBANT(CLAY,SAND);PLACE IN PROPER CONTAINER FOR DISPOSAL.AVOID CONTAMINATION OF SEWERS AND WATERWAYS.  
Neutralizing Agent:NOT APPLICABLE.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.  
Other Precautions:AVOID WATER CONTAMINATION.HYDROGEN SULFIDE MAY BE PRESENT IN THE HEADSPACE OF THE CONTAINER IF IT HAS BEEN EXPOSED TO HIGH TEMPERATURES DURING STORAGE.AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS .

=====  
Exposure Controls/Personal Protection  
=====

Respi

ratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED  
RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.ALWAYS  
MONITOR AVAILABLE OXYGEN LEVEL BEFORE ENTERING ENCLOSED SPACES.

Ventilation:MECHANICAL (GENERAL) VENTILATION.

Protective Gloves:NITRILE GLOVES.

Eye Protection:SPLASH GOGGLES IF MISTING.

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE  
EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH AND SAFETY  
SHOWER.

Work Hygienic Practices:WASH

THOROUGHLY AFTER HANDLING AND BEFORE  
EATING. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. DISCARD  
CONTAMINATED SHOES

Supplemental Safety and Health

USED GASOLINE MOTOR OILS HAVE BEEN SHOWN TO CAUSE SKIN CANCER WHEN  
REPEATEDLY APPLIED TO MOUSE SKIN WITHOUT ANY EFFORT TO REMOVE THE  
MATERIAL BETWEEN APPLICATIONS. THERE IS NO EVIDENCE OF A CAUSAL REL  
ATIONSHIP BETWEEN SKIN CANCER IN HUMANSAND EXPOSURE TO USED MOTOR  
OIL.

===== Physical/Chemical Properties =====

=====

HCC:V6

Vapor Pres:NEGLIGIBLE

Vapor Density:>1

Spec Gravity:0.891

Viscosity:110CST@104F

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID;PALE;MINERAL OIL ODOR.

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES  
OF IGNITION.AVOID WATER CONTAMINATION.

Hazardous Decomposition Products:C

ARBON DIOXIDE,CARBON

MONOXIDE,HYDROGEN SULFIDE,IRRITATING ALDEHYDES,KETONE,SULFUR  
COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND  
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, w

arrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.