View NSN Online: https://aerobasegroup.com/nsn/9150-00-252-6373

INTERNATIOAL LUBRICANTS CO INC -- CUTTING FLUID -- 9150-00-252-6373

Product ID:CUTTING FLUID MSDS Date:12/05/1996

FSC:9150

NIIN:00-252-6373

MSDS Number: BXDNK === Responsible Party ===

Company Name: INTERNATIOAL LUBRICANTS CO INC

Address:10363 AIRLINE HIGHWAY

City:SAINT ROSE

State:LA ZIP:70087 Country:US

Info Phone Num:504-469-0940 Emergency Phone Num:504-469-094

0

CAGE:JO811

=== Contractor Identification ===

Company Name: INTERNATIONAL LUBRICANTS INC

Address:10363 W AIRLINE HWY

Box:City:SAINT ROSE

State:LA ZIP:70087 Country:US

Phone:504-469-0940(504-471-0104FAX)

CAGE:0W1H4

Company Name: INTERNATIONAL LUBRICATES INC

Address:10363 AIRLINE HIGHWAY

Box:City:SAINT ROSE

State:LA ZIP:70087 Country:US

Phone:504-469-0940

CAGE:JO811

Company Name: SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA ZIP:70058 Country:US

Phone:504-366-4542

CAGE:0T5C6

====== Composition/Information on Ingredients ========
Ingred Name:HYDROCARBON OILS/DEOBASE (DEODORIZED KEROSENE) CAS:8020-83-5 RTECS #:HF9500000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 (OIL MIST) ACGIH TLV:5 MG/M3 (OIL MIST)
Ingred Name:ADDITIVE MIXTURES (TRADE SECRET) Other REC Limits:NONE SPECIFIED
=========== Hazards Identification ============
LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:NO Sk in:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS:UNKNOWN. ACUTE AND CHRONIC- UNKNOWN. Explanation of Carcinogenicity:NONE
======================================
First Aid:CALL A DOCTOR IF SYMPTOMS OCCUR. EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WIPE EXCESS OFF. WASH SKIN WITH SOAP & WATER. INHALED:MOVE TO FRESH AIR. ORAL:CONTACT A PHYSIC IAN IMMED IATELY.
======================================
Flash Point Method:COC Flash Point:>390F,>199C Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM/DRY CHEMICAL. DIRECTLY SPRAYING WATER/FOAM ONTO BURNING OIL MAY CAUSE FROTHING. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:NONE
========= Acc

idental Release Measures	2

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. REMOVE SPILL WITH PUMP OR INERT ABORBENT SUCH AS SAND, CLAY, EARTH. TRANSFER TO PROPER CONTAINERS FOR DISPOSAL. PREVENT RUN-OFF TO ENTER SEWERS OR WATERWAYS. REPORT SPILLS A S REQUIRED TO AUTHORITIES.

Neutralizing Agent: NOT RELEVANT

========== Handling and Storage ===============

Handling and Storage Precautions:STORE AWAY FROM HIGH HEAT & STRONG OXIDANTS. KEEP

CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN. DO NOT STORE ABOVE 100F.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND LAUNDER BEFORE RE-USE.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE NORMALLY NEEDED. IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED

OR IF EXPOSURE MAY OR DOES

EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS, WEAR NIOSH-APPROVED ORGANIC VAPOR AND MI ST RESPIRATOR (REFER TO 29 CFR 1910.134)

Ventilation: USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves: NEOPRENE

Eye Protection: SAFETY GLASSES/GOGGLES

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices: OBSERVE GOOD INDUST

RIAL HYGIENE PRACTICES AND

RECOMMENDED PROCEDURES. WASH BEFORE EATING OR DRINKING.

Supplemental Safety and Health

======== Physical/Chemical Properties ============

HCC:V6

NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:>626F,>330C

Vapor Pres:0 @ 68F Spec Gravity:0.89

Viscosity:>=100SUS@100F

Evaporation Rate & Dry Reference:0

Solubility in Water:0 @ 20C/68F

Appearance and Odor: AMBER, VISCOUS LIQUID - PUNGENT, SULFUR TYPE ODOR

Percent Volatiles by Volume:0

=====	Stability and Reactivity Data =========
Stability	Indicator/Materials to Avoid:YES
STRONG ACID	G OXIDIZING AGENTS SUCH AS HYDROGEN PEROXIDE, BROMINE, CHROMIC
Stability	Condition to Avoid:EXCESSIVE HEAT
Hazardo	us Decomposition Products:MAY PRODUCE SMOKE, CARBON MONOXIDE,

======= Disposal Considerations ===========

CARBON DIOXIDE, OXIDES OF PHOSPHORUS AND SULFUR.

Waste Disposal Methods:DISPOSE OF WASTE IN COMPLIANCE WITH LOCAL, STATE AND FEDERA

L REGULATIONS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS OR UNDERGROUND WATER SUPPLY. INCINERATION IS RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent pr ofessional advice to verify and assume responsibility for the suitability of this information to their particular situation.