

MINNESOTA MINING AND MFG CO -- CC-2 PREP KIT (CABLE CLEANER) -- 6850-01-015-2758

===== Product Identification =====

Product ID:CC-2 PREP KIT (CABLE CLEANER)

MSDS Date:12/01/1997

FSC:6850

NIIN:01-015-2758

Kit Part:Y

MSDS Number: BXFRM

=== Responsible Party ===

Company Name:MINNESOTA MINING AND MFG CO

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-737-6501,1-8

00-364-3577

Emergency Phone Num:612-737-6501,1-800-364-3577

Resp. Party Other MSDS Num.:11-4627-3

CAGE:76381

=== Contractor Identification ===

Company Name:BECKER JOHN A CO

Address:1341 EAST 4TH ST

Box:City:DAYTON

State:OH

ZIP:45402-2235

Country:US

Phone:513-226-1341

Contract Num:SP0450-99-M-C128

CAGE:12497

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

Company

Name:QUALITY ELECTRIC SUPPLY CO
Address:4425 SOUTHLAKE BLVD.
Box:3680
City:RICHMOND
State:VA
ZIP:23235
Country:US
Phone:804-794-0842
CAGE:4W935
Company Name:WESTINGHOUSE ELECTRIC SUPPLY CO
Address:2080 WINNERS CR
Box:187
City:DAYTON
State:OH
ZIP:45401
Country:US
Phone:937-463-4922
CAGE:2B094

=====
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATES
CAS:64771-72-8
Minumum % Wt:80.
Maxumum % Wt:95.
Other REC Limits:NONE RECOMMENDED

Ingred Name:D-LIMO
NENE
CAS:5989-27-5
RTECS #:GW6360000
Minumum % Wt:5.
Maxumum % Wt:20.
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MILD IRRITATION. SKIN: MODERATE
IRRITATION. INHALATION: IRRITATION OF UPPER RESPIRATORY SYSTEM.
PROLONGED/REPEATED OVE

REXPOSURE MAY CAUSE CNS DEPRESSION.

INGESTION: GASTROINTESTINAL TISSUES IRRITATION.

Explanation of Carcinogenicity:PRODUCT CONTAINS NO INGREDIENTS

CURRENTLY CLASSIFIED AS CARCINOGENIC BY NTP, IARC OR OSHA.

Effects of Overexposure:EYES: REDNESS, SWELLING, PAIN, TEARING. SKIN:
REDNESS, SWELLING, ITCHING, DRYNESS. INHALATION: SORENESS OF
NOSE/THROAT, COUGHING, SNEEZING, HEADACHE, DIZZINESS,
INCOORDINATION, SLOW REACTION, SLURRED SPEECH, GIDDINESS,
UNCONSCIOUSNESS. INGESTIO

N: PAIN, VOMITING, ABDOMINAL TENDERNESS,
NAUSEA, BLOOD IN VOMITUS AND FECES.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. GET MEDICAL
ATTENTION. SKIN: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION
PERSISTS, GET MEDICAL ATTENTION. INHALATION: MOVE TO FRESH AIR. IF
SIGNS/SYMPTOMS CONTINUE, GET MEDICAL ATTENTION. INGESTION: DO NOT
INDUCE VOMITING. DRINK 2 GLASSES OF WATER. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:=-62.2C, 144.F

Lower Limits:N/D

Upper Limits:N/D

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR FULL PROTECTIVE

CLOTHING,HELMET,SELF-CONTAINED, POSITIVE PRESS/PRESS DEMAND
BREATHING APPARATUS, BUNKER COAT AND PANTS, FACEMASK, PROTECTIVE
HEAD COVERING.

Unusual Fire/Explosion Hazar

d:NO UNUSUAL FIRE OR EXPLOSION HAZARDS ARE
ANTICIPATED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL. COVER WITH INORGANIC ABSORBENT
MATERIAL. COLLECT SPILLED MATERIAL. PLACE IN APPROVED METAL
CONTAINER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA
AWAY FROM HEAT, SPARKS, OP

EN FLAMES, AND OTHER SOURCES OF IGNITION.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. DO NOT EAT, DRINK, OR SMOKE WHEN USING THIS PRODUCT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID PROLONGED BREATHING OF VAPORS. IF EXHAUST VENTILATION IS NOT ADEQUATE, USE APPROPRIATE RESPIRATORY PROTECTION. WEAR A HALF-MASK ORGANIC VAPOR RESPIRATOR.

Ventilation:PROVIDE ADEQUATE LOCAL EXHAUST VENTILATION.

Protective Gloves:NITRILE RUBBER, POLYETHYLENE, VITON GLOVES

Eye Protection:AVOID EYE CONTACT. WEAR VENTED GOGGLES.

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH EXPOSED AREAS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE USING.

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:=193.3C, 380.F

B.P. Text:380 - 480 F

Vapor Pres:1.00

Spec Gravity:0.76

VOC Pounds/Gallon:740

pH:NA

Viscosity:NP

Solubility in Water:NIL

Appearance and Odor:LIQUID, CLEAR, CITRUS-LIKE ODOR.

Percent Volatiles by Volume:100

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:KEEP AWAY FROM HEAT/SPARKS/OPEN

FLAME/OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

=====

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN INDUSTRIAL OR COMMERCIAL FACILITY.
RECLAIM IF FEASIBLE. DISPOSE OF WASTE IN ACCORDANCE WITH LOCAL,
STATE AND FEDERAL REGULATIONS.

===== Regulatory Information =====

Federal Regulatory Information:ALL COMPONENTS OF THIS PRODUCT ARE
LISTED ON THE TOXIC SUBSTANCE CONTROL ACT (TSCA) CHEMICAL SUBSTANCE
INVENTORY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.