

NILES CHEMICAL PAINT CO -- 2345B GREEN PRIMER: COMP B -- 8010-01-302-3608

=====
Product Identification
=====

Product ID:2345B GREEN PRIMER: COMP B

MSDS Date:12/20/1994

FSC:8010

NIIN:01-302-3608

Kit Part:Y

MSDS Number: BXHBP

=== Responsible Party ===

Company Name:NILES CHEMICAL PAINT CO

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Info Phone Num:616-683-3377

Emergency P

hone Num:219-236-5856

Preparer's Name:MIKE LICHATOWICH

CAGE:02388

=== Contractor Identification ===

Company Name:NILES CHEMICAL PAINT

Address:225 FORT STREET

Box:307

City:NILES

State:MI

ZIP:49120

Country:US

Phone:616-683-3377/219-236-5856

CAGE:02388

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN

CAS:25068-38-6

RTECS #:KC2100000

Fraction by Wt: 49%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VM&P NAPHTHA (VAPOR PRESSURE 15 MM HG @ 37.7C)

CAS:8030

-30-6
RTECS #:DE3030000
Fraction by Wt: 24%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:300 PPM
ACGIH TLV:300 PPM;STEL 400 PPM

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 9%
Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYAMIDE
Fraction by Wt: 1%
Other REC Limits:NONE RECOMMENDED
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:50.0F,10.0C
Lower Limits:0.7
Upper Limits:6.0
Extinguishing Media:DRY CHEMICAL, FOAM, CO2
Fire Fighting Procedures:WEAR SCBA W/FULL FACPIECE (POSITIVE PRESSURE MODE) & FULL PROTECT CLOTH. USE WATER TO COOL CLOSED CNTNR TO PREVENT PRESSURE BLDUP/AUTO IGNIT/EXPLOSION W/HEAT.
Unusual Fire/Explosion Hazard:KEEP CNTNR CLSD.VAPOR HEAVY,TRAVEL ON GRND TO IGNIT.KEEP FROM HEAT/IGNIT.CLSD CNTNR EXPLODE W/HEAT.APPLIC TO HOT SRFCS REQ SPCL CAUTN.DECOMP PRODUCT-HEALTH HZD.

=====
===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:285F,141C
Vapor Density:> AIR
Spec Gravity:1.149
Viscosity:76 - 89 KU
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:SLIGHT
Appearance and Odor:LIQUID, ODOR OF SOLVENTS
Percent Volatiles by Volume:38.26
Corrosion Rate:MINIMAL

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Av

oid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HIGH TEMPERATURES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.