View NSN Online: https://aerobasegroup.com/nsn/8030-00-829-3982

FLUORAMICS INC -- FORMULA-8 -- 8030-00-829-3982

Product ID:FORMULA-8 MSDS Date:01/01/1994

FSC:8030

NIIN:00-829-3982 MSDS Number: BXJVJ === Responsible Party ===

Company Name:FLUORAMICS INC Address:18 INDUSTRIAL AVE

City:MAHWAH

State:NJ ZIP:07430 Country:US

Info Phone Num:201-825-8110

Emergency Phone Num:201-825-8110 Preparer's Name:FRANKLIN G REICK

CAGE:MO067

==

= Contractor Identification ===

Company Name:FLUORAMICS INC

Address:18 INDUSTRIAL AVE

Box:City:MAHWAH

State:NJ ZIP:07430 Country:US

Phone:201-825-8110

CAGE:MO067

Company Name:FLUORAMICS, INC Address:103 PLEASANT AVENUE Box:City:UPPER SADDLE RIVER

State:NJ ZIP:07458

Phone: (201) 825-8110

CAGE:28017

====== Composition/Information on Ingredients ========

Ingred Name: CARBOPOL #934; (CARBOPOL)

CAS:9003-01-4 Fraction by Wt: 5% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:TITANIUM OXIDE; (P

IGMENTS (TIO*2))
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 20%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:WATER (VEHICLE)

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 14% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name:SURFACTANTS - (TRITON 100)

Fraction by Wt: 01% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: ETHYLENE, TETRAFLUORO-, POLYMER; (TEFLON (PTFE) T30)

CAS:116-14-3

RTECS #:KX4025000 Fraction by Wt: 59% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: SILICA, AMORPHOUS FUMED; (COLLOIDAL SILICA

(DEGUSSA))
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 1%
OSHA PEL:N/K
ACGIH TLV:N/K

========= Hazards Identification ===============

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE/CHRONIC:TREAT SYMPTOMATICALLY.

PTFE POLYMER-WHEN THERMALLY DECOMPOSED, MAY CAUSE POLYMER FUME FEVER AND FLU-LIKE SYMPTOMS.

Explan

ation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:INHALATION:REMOVE TO FRESH AIR. SKIN:REMOVE BY WIPING AND WASH WITH SOAP AND WATER. EYES:WASH WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. INGESTION:CONTACT A PHYSICIAN.
======================================
Flash Poin t:NONE
Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE . INCOMBUSTIBLE.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT.
Unusual Fire/Explosion Hazard:IN EXTREME FIRE SITUATION, PROTECTION FROM HYDROGEN FLUORIDE FUMES SHOULD BE EMPLOYED.
========= Accidental Release Measures ==========
Spill Release Procedures:NOT APPLICABLE. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:STRICTLY ENFORCE NO SMOKING RULE FOR WORKERS HANDLING MATERIAL. Other Precautions:AT 650C (1202F), COF*2 IS THE PRINCIPAL TOXIC PRODUCT.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF EXPOSED TO HIGH TEMPERATURE PROCESSING FUMES, WEAR NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS. Ventilation:LOCAL EXHAUST:PREFERRED. MECHANICAL (GENERAL):USUALLY NONE. Protective Gloves

Boiling Pt:B.P. Text:212F,100C

Vapor Pres: