

DIAGRAPH CORP -- 0968500 GP-X WHITE MARKER -- 7520-00-558-1487

===== Product Identification =====

Product ID:0968500 GP-X WHITE MARKER

MSDS Date:11/20/1993

FSC:7520

NIIN:00-558-1487

MSDS Number: BXNXJ

=== Responsible Party ===

Company Name:DIAGRAPH CORP

Address:RT 148 AND OGDEN RD

Box:520

City:HERRIN

State:IL

ZIP:62948-5000

Country:US

Info Phone Num:618-997-3321

Emergency Phone Num:618-997-3321

P

reparer's Name:PETER GIMSE

CAGE:IO074

=== Contractor Identification ===

Company Name:DIAGRAPH CORP

Address:3401 RIDER TRAILS S

Box:520

City:EARTH CITY

State:MO

ZIP:63045-1110

Country:US

Phone:314-739-1221

CAGE:90316

Company Name:DIAGRAPH CORP

Box:520

City:HERRIN

State:IL

ZIP:62948

Country:US

Phone:618-997-3321

CAGE:IO074

===== Composition/Information on Ingredients =====

Ingred Name:XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *95-1*

CAS:1330-20-7

RTECS #:ZE2100000

Fr

action by Wt: 20-40%
Other REC Limits:100 PPM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM, SKIN
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:PROPYLENE GLYCOL METHYL ETHER (1-METHOXY-2-PROPANOL)
PROPYLENE GLYCOL MONO METHYL ETHER

CAS:107-98-2
RTECS #:UB7700000
Fraction by Wt: 0-20%
Other REC Limits:100 PPM
ACGIH TLV:100 PPM

Ingred Name:ETHYL BENZENE *95-1*

CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 0-20%
Other REC Limits:100 PPM
OSHA PEL:435 MG/CUM
ACGIH TLV:434 MG/CUM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE, TIO2 (SUSPECTED ANIMAL CARCINOGEN, IARC
GROUP 3) *95-1*

CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 20-40%
OSHA PEL:15 MG/CUM
ACGIH TLV:10 MG/CUM (DUST)

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50(RAT): 4300 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SKIN: IRRITATION

/DERMATITIS. EYES:

IRRITATION. INHALATION: IRRITATION. INGESTION: LARGE CONCENTRATIONS, MAY BE FATAL. OVEREXPOSURE MAY CAUSE KIDNEY & LIVER DAMAGE.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, REDNESS, BLURRED VISION, DIZZINESS, FATIGUE, VOMITING, NAUSEA

=====
===== First Aid Measures =====

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINS. INHALATION: PROVIDE FRESH AIR & REST. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:70F

Lower Limits:1

Extinguishing Media:DRY CHEMICAL, FOAM, CO2

Unusual Fire/Explosion Hazard:A STRAIGHT STREAM OF WATER COULD SPREAD FIRE. A VPOR ACCUMULATION WILL FLASH &/EXPLODE IF IGNITED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. ABSORB ON INERT MATERIAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE AWAY FROM ALL SOURCES OF IGNITION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED-ORGANIC VAPOR

Ventilation:NEEDED TO KEEP VAPOR CONCENTRATION BELOW TLV LEVEL.

Protective Gloves:NON-ABSORBENT

Eye Protection:RECOMMENDED

Other Protective Equipment:OIL RESISTANT FOOTWEAR, PROTECTIVE CLOTHING
Suppl

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230F
Vapor Density:>1
Spec Gravity:1.272
Evaporation Rate & Reference:SLOWER THAN BU ACETATE
Appearance and Odor:WHITE LIQUID INK W/SOLVENT ODOR
Percent Volatiles by Volume:42

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:STATIC DISCHARGE, OPEN SPARKS/FLAMES
&
OTHER IGNITION SOURCES
Hazardous Decomposition Products:CO₂, CO, HYDROCARBONS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this informa
tion to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.