View NSN Online: https://aerobasegroup.com/nsn/6810-00-275-8145

MALLINCKRODT INC., SCIENCE PRODUCTS DIV -- 78132 SODIUM METAL -- 6810-00-275-8145

Product ID:78132 SODIUM METAL MSDS Date:08/30/1985 FSC:6810 NIIN:00-275-8145 MSDS Number: BXPTT === Responsible Party === Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIV Box:M City:PARIS State:KY ZIP:40361-0315 Country:US Info Phone Num:314-895-2000 Emergency Phone Num:314-539 -1600 CAGE:1BF21 === Contractor Identification === Company Name: FREY SCIENTIFIC Address:100 PARAGON PARKWAY Box:City:MANSFIELD State:OH ZIP:44905 Country:US Phone:419-589-1900 CAGE:6U218 Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIV Box:M City:PARIS State:KY ZIP:40361-0315 Country:US Phone:314-982-5000 CAGE:1BF21 Company Name: SCIENCE KIT INC Address:777 E PARK DR Box:City:TONAWANDA State:NY ZIP:14150-6708 Country:US Phone:716-874-6020 CAGE:57020

======= Composition/Information on

Ingredients =========

Ingred Name:SODIUM (CERCLA) CAS:7440-23-5 RTECS #:VY0686000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: NOT EXPECTED TO BE INHALATION HAZARD; HOWEVER, SODIUM FUMES CAN BE AN INTENSE IRRITANT TO RESPIRATORY MUCOSA. CONTACT WITH SKIN AN
D EYES MAY CAUSE SEVERE
BURNS. INGESTION MAY CAUSE SEVERE BURNS TO MOUTH/THROAT; MAY COMBUST OR EXPLODE IN MOUTH/THROAT/ESOPHAGUS. CHRONIC: NO INFORMATION FOUND.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:INHALED-BURNS, CHOKING, DIFFICULT BREATHING. EYES-BURNS, PAIN, REDNESS, BLURRED VISION, DAMAGE. SKIN-VERY DEEP BURNS, TISSUE DAMAGE, PAIN, REDNESS. INGESTE
D-PAIN, BURNS TO

MOUTH/THROAT/ESOPHAGUS.

Medical Cond Aggravated by Exposure:NO INFORMATION FOUND.

First Aid:INHALED-REMOVE TO FRESH AIR. GET MEDICAL ATTENTION FOR ANY BREATHING DIFFICULTY. INGESTION-IF CONSCIOUS, GIVE WATER/MILK AND GET IMMEDIATE MEDICAL ATTENTION. SKIN-FLUSH WITH LOTS OF WATER FOR 15 MINUT ES WHILE REMOVING CONTAMINATED CLOTHES/SHOES. GET IMMEDIATE MEDICAL HELP. EYES-WASH WITH PLENTY OF WATER FOR 15

MINUTES, LIFTING LIDS. GET IMMEDIATE MEDICAL ATTENTION.

Flash Point:FLAMMABLE SOLID

Extinguishing Media:DRY SODA ASH, DRY SALT OR SAND. DO NOT USE WATER, CARBON DIOXIDE OR CHLORINATED FIRE EXTINGUISHERS. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE EXPOSED CONTAINERS WITH WATER. Unusual Fire/Explosion Hazard:REACTIONS WITH WATER FORMS SODIUM

HYDROXIDE AND HYDROGEN GAS WHICH MAY EXPLODE. BURNS VIOLENTLY	,
ACCOMPANIED BY EXPLOSIONS WHICH CAUSE SPATTERING OF MATERIAL	

Spill Release Procedures:COLLECT SPILLED MATERIAL QUICKLY & TRANSFER TO A CONTAINER OF KEROSENE, LIGHT OIL OR SIMILAR MATERIAL. MINIMIZE EXPOSURE TO AIR. DO NOT USE WATER ON METAL. IF SPILLED ONTO WATER, BE VERY CAUTIOUS! EVA CUATE AREA. WEAR PROPER PROTECTIVE EQUIPMENT. Neutralizing Agent :NONE SPECIFIED BY MANUFACTURER.

- Handling and Storage Precautions: ISOLATE FROM AIR, ACIDS, OXIDIZING AGENTS. STORE UNDER NITROGEN OR KEROSENE; NEVER UNDER HALOGENATED HYDROCARBONS. KEEP AWAY FROM WATER. Other Precautions: PROTECT CONTAINER FROM PHYSICAL DAMAGE. KEEP AWAY
- FROM LOCATIONS WHICH NEED WATER AS A FIRE EXTINGUISHING AGENT. A DETACHED FIRE-RESISTANT BUILDING IS RECOMMENDED FOR QUANTITY STORAGE.

===

Respiratory Protection: IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IN ACCORDANCE WITH 29 CFR 1910.13 4 AND MANUFACTURER'S RECOMMENDATIONS.

Ventilation: A LOCAL EXHAUST SYSTEM WHICH CAPTURES THE CONTAMINANT AT ITS SOURCE IS RECOMMENDED TO PREVENT DISPERSION TO WORKROOM AIR Protective Gloves: IMPER

VIOUS.

Eye Protection: CHEMICAL SPLASH GOGGLES.

Other Protective Equipment:BOOTS, LAB COAT, APRON OR COVERALLS TO PREVENT SKIN CONTACT. EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:DLA-HMIS-WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

NO DLSC-TIR OR SAMMS CTDF WAS PROVIDED WITH DLA-HMIS PACKET; STAFF ENTERED WITH SUPPLY DATA PER EXISTING HMIS RECORD (ITEM NAME, U/I, ETC HCC:R2 Boiling Pt:B.P. Text:1178F,637C Melt/Freeze Pt:M.P/F.P Text:208F,98C Spec Gravity:0.968 Solubility in Water:DECOMPOSES VIOLENTLY Appearance and Odor:LIGHT, SILVERY-WHITE METAL; ODORLESS.

Stability Indicator/Materials to Avoid:YES

WATER,OXYGEN,HALOGENS,ACETYLENE,ALUMINUM HALIDES,AMMONIUM SALTS,OXIDES,OXIDIZING AGENTS,ACIDS,CHLORINATED ORGANIC C MDS..

Stability Condition to Avoid: KEEP AWAY FROM WATER/MOISTURE. KEEP AWAY FROM INCOMPATIBLE MATERIALS.

Hazardous Decomposition Products:DOES NOT DECOMPOSE BUT DOES FORM FLAMMABLE HYDROGEN GAS IN CONTACT WITH AIR/WATER.

Conditions to Avoid Polymerization: THIS SUBSTANCE DOES NOT POLYMERIZE.

Waste Disposal Methods:WASTE SODIUM SHOULD BE PACKAGED UNDER A HYDROCARBON FLUID & SENT TO A PERMITTED RCRA DISPOSAL FACILITY.

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS. REPORTABLE QUA NTITY (RCRA,CWA,CERCLA): 10 POUNDS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document

should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

).