

ITW DEVCON/ A DYKEM COMPANY -- TOLE RED DX-296,B-I-C-81496 -- 6850-01-013-9937  
===== Product Identification =====

Product ID:TOLE RED DX-296,B-I-C-81496  
MSDS Date:06/01/1994  
FSC:6850  
NIIN:01-013-9937  
MSDS Number: BXPVM  
=== Responsible Party ===  
Company Name:ITW DEVCON/ A DYKEM COMPANY  
Address:8501 DELPORT DRIVE  
City:ST. LOUIS  
State:MO  
ZIP:63114  
Country:US  
Info Phone Num:314-423-0100/800-443-9536  
Emergency Phone Num:800-443-9536/800-424-9300(CHEMTREC)  
Preparer's Name:JAMES A SEPER  
CAGE:98148  
=== Contractor Identification ===  
Company Name:ITW DYKEM/ DYMON  
Address:805 E OLD 56 HWY  
Box:City:OLATHE  
State:KS  
ZIP:66061  
Country:US  
Phone:800-443-9536  
CAGE:98148

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ALCOHOL (ETHANOL)  
CAS:64-17-5  
RTECS #:KQ6300000  
Fraction by Wt: 31 - 50%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:1000 PPM; 9495

Ingred Name:N-BUTYL ACETATE (CERCLA)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 31 - 50%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM/200STEL;9495

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM/500STEL;9495

Ingred Name:COLLODION (WET NITROCELLULOSE)

CAS:9004-70-0

RTECS #:QW0970000

Fraction by Wt: 1 - 5%

Other

REC Limits:NONE RECOMMENDED

Ingred Name:N-BUTYL ALCOHOL (SARA 313) (CERCLA)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9495

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)

CAS:123-42-2

RTECS #:SA9100000

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:50 PPM

ACGIH TLV:50 PPM; 9495

Ingred Name:N-PROPYL ACETATE

CAS:109-60-4

RTECS #:AJ3675

000

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/250STEL;9495

Ingred Name:SOLVENT RED 125 (COBALT COMPOUND)

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYAMIDE RESIN

CAS:68410-23-1

Other REC Limits:NONE RECOMMENDED

Ingred Name:CASTOR OIL

CAS:8001-79-4

RTECS #:FI4100000

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLITILE ORGANIC CONTENT AS LISTED ON MSDS: 6.46 LBS/GAL.

RTECS #:9999999VC

Other REC Limits:NONE RECOMMEN

DED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, CNS,

RESPIRATORY & GI TRACTS. ACUTE- MAY CAUSE EYE & SKIN IRRITATION.

INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION, CNS EFFECTS. MAY  
BE ABSORBED THRO

UGH SKIN. CAN CAUSE G I TRACT IRRITATION.

ASPIRATION HAZARD. CHRONIC- SKIN SENSITIZATION OR DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, IRRITATION,

REDNESS AND ITCHING OR BURNING SENSATION OF EYES OR SKIN, ABDOMINAL  
PAIN, WEAKNESS, CONFUSION

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN

DISORDERS, EYE PROBLEMS OR IMPAIRED CNS OR RESPIRATORY FUNCTION MAY  
BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRO

DUCT.

=====  
===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. ORAL:DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:CC  
Flash Point:53.0F,11.7C  
Lower Limits:1.38  
Upper Limits:12

Extinguishing Media:FOAM, DRY CHEMICAL/CARBON DIOXIDE. DON'T USE WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND CAN TRAVEL CONSIDERABLE DISTANCE OR BE MOVED BY VENTILATION TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINER MAY EXPLODE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH. PREVENT LIQUID FROM ENTERING SEWERS.

Neutralizing Agent:NOT RELEVANT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:

STORE IN COOL, VENTILATED AREA, AWAY FROM SOURCES OF IGNITION & INCOMPATIBLE MATERIALS. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:HIGHLY FLAMMABLE. AVOID BREATHING VAPORS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. LAUNDRY BEFORE REUSE.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION IS AVAILABLE

VENTILATION

CONDITIONS EXIST. IF AIRBORNE CONCENTRATION IS HIGH, WEAR A NIOSH-APPROVED ORGANIC VAPOR RESPIRATOR.

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:NEOPRENE, NITRILE, POLYVINYL CHLORIDE

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STATION, SAFETY SHOWER, INDUSTRIAL-TYPE WORK CLOTHING, APRON AND BARRIER CREAM FOR EXPOSED SKIN

Work H

ygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATIONS, SEE PNI A AND B, SAME NSN.

===== Physical/Chemical Properties =====

HCC:F2

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:163F - 275F

Vapor Density:>1

Spec Gravity:0.84

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:APPR

ECIABLE

Appearance and Odor:RED TRANSPARENT LOW VISCOUSITY LIQUID WITH SWEET SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES AND OTHER SOURCES OF IGNITION

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, AND SMOKE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE

OF IN ACCORDANCE WITH ALL APPLICABLE  
FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. INCINERATE IN  
APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing  
this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.