

TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO) -- MIL-L-26087B(1) GR II
RECIPROCATING COMPRESSOR FL, A1412 -- 9150-00-753-4636

===== Product Identification =====

Product ID:MIL-L-26087B(1) GR II RECIPROCATING COMPRESSOR FL, A1412

MSDS Date:04/27/1994

FSC:9150

NIIN:00-753-4636

MSDS Number: BXSCB

=== Responsible Party ===

Company Name:TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO)

Address:3

365 E SLAUSON AVE

City:VERNON (FORMALLY IN LOS ANGELES)

State:CA

ZIP:90058

Country:US

Info Phone Num:213-581-2036

Emergency Phone Num:213-581-2036, CHEMTREC 800-424-9300

Preparer's Name:RICHARD J. EBERHARDT

CAGE:8Y842

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO

Address:8015 PARAMOUNT BLVD

Box:City:PICO RIVERA

State:CA

ZIP:90660-4811

Country:US

Phone:800-424-9300

CAGE:2X842

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

B

City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, ACID-TREATED HEAVY NAPHTHENIC

CAS:64742-18-3

RTECS #:PY8032000

Fraction by Wt: 617F,>325C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATERFOG.

Fire Fighting Procedures:DO NOT ENTER NAY ENCLOSED OR CONFINED AREA

WITHOUT PROPER PROTECTIVE EQUMPT AND SELF-CONTAINED BREATHING
APPARATUS.

U

Unusual Fire/Explosion Hazard:SLIGHTLY COMBUSTIBLE WHEN HEATED
>FPT.WILL RELEASE FLAMM VAP WHICH CAN BURN IN OPEN OR BE EXPLOSIVE
IN CONFINED SPACES IF EXPOSED TO SOURCE OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW.WIPE/MOP UP/ABSORB W/DIATOMACEOUS
EARTH OR OTHER INERT MATL.STORE IN APPROPRIATE CNTNR FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautio

ns:AVOID STORAGE NEAR OPEN FLAME/OTHER
SOURCES OF IGNITION.EXCESSIVE MISTING MAY CAUSE SLIPPERY
FLOORS.PROPER FOOTWEAR REQUIRED.

Other Precautions:WASH/TAKE SHOWERS IF GENERAL CONTACT OCCURS.REMOVE
OIL-SOAKED CLOTHING;LAUNDRER BEF REUSE.DISCARD CONTAMIN LETAHER
GLOVES/SHOES.EMPTY CNTNRS RETAIN RESIDUE(LIQ/VAP);CAN BE
DANGEROUS-DO NOT PRESS/CUT/WE LD/BRAZE/DRILL/ETC/EXPO TO
FLAME/HEAT.

===== Exposure Controls/Personal Protection =====

Respiratory Protecti

on:NONE NORMALLY REQUIRED.

Ventilation:SUFFICIENT TO MAINTAIN ATMOSPHERE BELOW TLV LIMIT.

Protective Gloves:RECOMMENDED.

Eye Protection:REQUIRED.

Other Protective Equipment:CHEMICALLY RESISTANT BOOTS & APRONS
RECOMMENDED.

Work Hygienic Practices:WASH HANDS AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>617F,>325C

Vapor Pres:AIR

Spec Gravity:0.906

Evaporation Rate & Reference:LESS THAN ETHE

R

Solubility in Water:INSOLUBLE

Appearance and Odor:BROWN, OILY LIQUID, PETROLEUM ODOR.

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:DO NOT HEAT ABOVE FLASH POINT.

Hazardous Decomposition Products:CARBON MONOXIDE AND ASPHYXIANTS.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH LOCA

L, STATE AND FEDERAL

REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.