View NSN Online: https://aerobasegroup.com/nsn/6850-01-387-6558

EASTMAN KODAK COMPANY -- 818 0481 400 GRAMS HX TONER, YELLOW -- 6850-01-387-6558

Product ID:818 0481 400 GRAMS HX TONER, YELLOW

MSDS Date: 10/05/1994

FSC:6850

NIIN:01-387-6558

MSDS Number: BXTPV === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-477-3194 MSDS:800-

242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

====== Composition/Information on Ingredients ========

Ingred Name:STYRENE ACRYLATE COPLOYMER (BUTYL ACRYLATE-P-DIVINYLBENZENE-STYRENE POLYMER)

CAS:57516-68-4

Fraction by Wt: 85-90%

Other REC Limits: NONE RECOMMENDE

D

Ingred Name: STYRENE BUTYLACRYLATE COPOLYMER (ACRYLIC ACID BUTYL ESTER

POLYMER WITH STYRENE)

CAS:25767-47-9 Fraction by Wt: 5-10%

Other REC Limits: NONE RECOMMENDED

Ingred Name: YELLOW AZO PIGMENT

CAS:5567-15-7 Fraction by Wt: 1-5%

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification =============

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: EXPECTED TO

BE LOW HAZARD FOR RECOMMENDED HANDLING FOR SKIN CONTACT, INGESTION OR INHALATION. NO SPECIFIC HAZARD KNOWN FOR RECOMMENDED HANDLING; MAY CAUSE TRANSIENT EYE IRRITATION. CHRONIC: NON E SPECIFIED BY MANUFACTURER.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN. Effects of Overexposure:EYES-REDNESS, TEARING, DISCOMFORT. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================

First Aid:INHALATION-IF SYMPTOMATIC, REMOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES-FLUSH IMMEDIATELY WITH WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN-WASH WITH SOAP & WATER. GET MEDCIAL ATTENTION IF SYMPTOMS OCCUR. INGESTED-IF CONSCIOUS, DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION.

=========== Fire Fighting Measures ===============

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:NONE.

Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST-AIR MIXTURES.

======== Accidental Release Measures ===========

Spill Release Procedures:DO NOT USE A VACUUM CLEANER TO CLEAN SPILLS OF PWDERED TONERS. THE VERY FINE PARTICLES CAN CAUSE A FIRE OR EXPLOSION. SWEEP MATERIAL ONTO PAPER AND PLACE IN A FIBER CARTON. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

==== Handling and Storage ===========

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION. KEEP CONTAINER CLOSED. KEEP FROM CONTACT WITH OXIDIZING MATERIALS. MINIMIZE DUST GENERATION AND ACCUMULATION.

Other Precautions:AVOID BREATHING DUST. WASH THOROUGHLY AFTER HANDLING.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE NORMALLY REQUIRED.

Ventilation: GOOD VENTILATION (4-6 ROOM VOLUMES PER HOUR) SHOULD BE USED. VE

NTILATION RATES SHOULD BE MATCHED TO CONDITIONS. Protective Gloves:IMPERVIOUS-RUBBER, PVC, NITRILE, NEOPRENE.. Eye Protection: DLA-HMIS: SAFETY GLASSES W/SIDE SHIELDS. Other Protective Equipment: WASHING FACILITIES. Work Hygienic Practices: GOOD INDUSTRIAL HYGIENE PRACTICES SHOULD BE FOLLOWED WHICH INCLUDES PREVENTING SKIN/EYE CONTACT AND INHALATION. Supplemental Safety and Health ECOLOGICAL INFORMATION: THIS MATERIAL HAS NOT BEEN TESTED FOR ENVIRONMENTAL EFFETCS. IN A SPILL SITUATION THIS MAT **ERIAL MAY BE** VISUALLY UNPLEASANT; HOWEVER, IT IS NOT EXPECTED TO CAUSE ADVERS ENVIRONM ENTAL EFFECTS. MSDS PROVIDED BY CAGE 19139 FOR CONTRACT SP0450-95-R-0754. ======== Physical/Chemical Properties ============ HCC:N1 Vapor Pres:NEGLIGIBLE Evaporation Rate & Description Rate & Reference: NEGLIGIBLE Solubility in Water: NEGLIGIBLE Appearance and Odor:YELLOW SOLID-POWDER; SLIGHT ODOR. Percent Volatiles by Volume:NIL ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE. Conditions to Avoid Polymerization: WILL NOT OCCUR. ======= Disposal Considerations =============================

Waste Disposal Methods: INCINERATE OR LANDFILL. CAN BE INCINERATED WHEN IN COMPLIANCE WITH LOCAL REGULATIONS. DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL

, STATE, OR LOCAL LAWS. NO SARA III/40 CFR PART 372 MA TERIALS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever. expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility

for the suitability of this information to their particular situation.	