

EASTMAN KODAK COMPANY -- 834 5928, HX TONER, RED -- 6850-01-387-6657

=====  
Product Identification  
=====

Product ID:834 5928, HX TONER, RED

MSDS Date:10/05/1994

FSC:6850

NIIN:01-387-6657

MSDS Number: BXTPW

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194 MSDS: 800-242-2424

Emergency Phone

Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====  
Composition/Information on Ingredients  
=====

Ingred Name:BUTYL ACRYLATE-P-DIVINYLBENZENE-STYRENE POLYMER

CAS:57516-68-4

Fraction by Wt: 85-90%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ACRYLIC ACID BUTYL ESTER POLYMER WITH STYRE

NE

CAS:25767-47-9

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MONOAZO PIGMENT (RED)

CAS:7023-61-2

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:YELLOW AZO PIGMENT

CAS:5567-15-7

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN:EXPECTED TO BE LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION:EXPECTED TO BE A LOW INGESTION HAZARD. INHALATION:EXPECTED TO BE A LOW HAZARD FOR RECOMMENDED HANDLING.

Explanation of Carcinogenicity:IN ADDITION TO THE ABOVE, PRODUCT IS NEGATIVE W/REGARD TO:ACGIH CANCER, CALIFORNIA CANCER & REPRODUCTIVE EFFECTS.

Effects of Overexposure:EYE:TRANSIENT IRRITATION.

Medical Cond Aggravated by Exposure:MFR GAVE NO INFORMATION ON MSDS.

=====  
===== First Aid Measures =====

First Aid:IF ANY SYMPTOMS OCCUR, GET IMMEDIATE MEDICAL ATTENTION.  
INHALATION:IF SYMPTOMATIC,MOVE TO FRESH AIR. EYE:FLUSH W/PLENTY OF WATER FOR 15 MIN. SKIN:FLUSH W/WATER 15 MIN. REMOVE CONTAMINATED CLOTHING & LAUNDRY BEFORE REUSE. INGESTION:DRINK 1-2 GLASSES OF WATER. GET IMMEDIATE MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point:COMBUSTIBLE SOLID  
Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE.  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST-AIR MIXTURES.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:DO NOT USE VACUUM CLEANER TO CLEAN UP SPILLS OF POWDERED TONERS. THE VERY FINE PARTICLES CAN CAUSE A FIRE OR EXPLOSION. SWEEP MATERIAL ONTO PAPER & PLACE IN A FIBER CARTON.  
CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION.  
Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED.  
Other Precautions:AVOID BREATHING DUST. USE WADEQUATE VENTILATION.  
WASH THOROUGHLY AFTER HANDLING.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.  
Ventilation:USE G

OOD GENERAL VENTILATION (10 CHANGES/HR). MATCH  
VENTILATION RATES TO CONDITIONS.

Protective Gloves:FOR PROLONGED &/OR REPEATED SKIN CONTACT

Eye Protection:MINIMIZE EYE CONTACT

Other Protective Equipment:EYE BATH, SAFETY SHOWER, WASHING FACILITIES

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICES INCLUDING  
PREVENTING EYE CONTACT & MINIMIZING SKIN CONTACT & INHALATION.

Supplemental Safety and Health

KAN 471121, J-0002.950. \*NOTE\* THIS MSDS WAS RECEIVED DIRECTLY FROM  
KODAK FO

R A NEW PURCHASE. HOW THE P/N IND A WAS RECEIVED OR WHY IT  
HAS A MORE RECENT DATE IS NOT KNOWN.

===== Physical/Chemical Properties =====

HCC:N1

NRC/State Lic Num:NONE

Vapor Pres:NEGLIGIBLE

Vapor Density:NEGLIGIBLE

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:SOLID (POWDER), RED, SLIGHT ODOR

Percent Volatiles by Volume:NEGLIG

===== Stability and Reactivity Data =====

Stability Indicator

/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:MFR GAVE NO INFORMATION ON MSDS.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR LANDFILL. CAN BE INCINERATED WHEN  
IN COMPLIANCE W/LOCAL REGULATIONS. DISCHARGE, TREATMENT, OR  
DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS.

Dis

claimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.