

PENRECO -- PENRECO AMBER -- 9150-00-250-0926

=====
===== Product Identification =====

Product ID: PENRECO AMBER

MSDS Date: 10/14/1994

FSC: 9150

NIIN: 00-250-0926

MSDS Number: BXVCG

=== Responsible Party ===

Company Name: PENRECO

Address: 106 SOUTH MAIN STREET

City: BUTLER

State: PA

ZIP: 16000

Info Phone Num: 412-756-0110

Emergency Phone Num: 412-756-0110

CAGE: 86549

=== Contractor Identification ===

Company Name: P

ENRECO

Address: 700 MILIAM ST PENNZOIL PL

Box: 2967

City: HOUSTON

State: TX

ZIP: 77252

Country: US

CAGE: 86549

=====
===== Composition/Information on Ingredients =====

Ingred Name: PETROLATUM, GREASE

CAS: 8009-03-8

Fraction by Wt: 100%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: EYE-MINIMALLY IRRITATING TO EYES.

SKIN-MI

NIMALLY IRRITATING TO THE SKIN. INHALATION-LOW VAPOR PRESSURE & IS NOT EXPECTED TO PRESENT AN INHALATION HAZARD. INGESTION-PRACTICALLY NONTOXIC BY INGESTION.

Explanation of Carcinogenicity:THIS PRODUCT IS NOT CARCINOGENIC ACCORDING TO THE OSHA HAZARD COMMUNICATION STANDARD.

Effects of Overexposure:INGESTION: LAXATIVE PROPERTIES, ABDOMINAL CRAMPS, & DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====
=====

First Aid:EYE-IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS & TAKE TO HOSPITAL. SKIN-WASH AREA THOROUGHLY WITH SOAP & WATER. IF HOT SUBMERGE AREA IN COLD WATER. TAKE TO HOSPITAL. INHALATION-IF MATERIAL IS HEATED OR HANDLED, REMOVE VICTIM FROM EXPOSURE. INGESTION-DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:COC

Flash Point:400F,204C

Extinguishing Me

dia:USE DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE USED WHEN USING WATER OR FOAM AS FROTHING MAY OCCUR.

Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE GENERATED WHILE BURNING, CO, CO2 AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OF COMBUSTION.

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL

TO ENTER SEWERS OR WATERCOURSES. REMOVE ALL SOURCES OF IGNITION. ABSORB WITH INERT MATERIAL SUCH AS SAND, CLAY, ETC. LARGE SPILLS MAY BE PICKED UP USING VACUUM PUMPS, SHOVELS, BUCKETS & PALCED IN DRUMS.

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:DON'T TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS & OPEN FLAME OR OXIDIZING MATERIALS.

Other Precautio

ns:THIS PRODUCT IS NOT CLASSIFIED AS HAZARDOUS UNDER DOT REGULATIONS. FIRE EXTINGUISHERS SHOULD BE KEPT READILY AVAILABLE. SEE NFPA 30 AND OSHA 1910.106--FLAMMABLE AND COMBUSTIBLE LIQUIDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATORY PROTECTION IS NOT REQUIRED UNDER CONDITIONS OF NORMAL USE. IF VAPOR/MIST IS GENERATED WHEN THE MATERIAL IS HEATED/HANDLED. USE AN ORGANIC VAPOR RESPIRATOR W/DUST/MIST FILTER. ALL RESPIRATORS MUST BE NIOSH CERTIFIED.

Ventilation:PROVIDE ADEQUATE VENTILATION IN ACCORDANCE W/GOOD ENGINEERING PRACTICE TO KEEP