

SHELL OIL COMPANY -- CAPRINUS(R) U OIL 40 -- 9150-01-399-8593

===== Product Identification =====

Product ID:CAPRINUS(R) U OIL 40

MSDS Date:04/29/1997

FSC:9150

NIIN:01-399-8593

MSDS Number: BXV FV

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Address:HEALTH, SAFETY AND ENVIRONMENT

Box:4320

City:HOUSTON

State:TX

ZIP:77210

Country:US

Info Phone Num:713-241-4819/4141/2252 FAX -6511

Emergenc

y Phone Num:713-473-9461

Resp. Party Other MSDS Num.:66535-00

Chemtrec Ind/Phone:(800)424-9300

CAGE:54527

=== Contractor Identification ===

Company Name:EQUILON ENTERPRISES LLC PRODUCT STEWARDSHIP

Address:1111 BAGBY RD RM 4325D

Box:674414

City:HOUSTON

State:TX

ZIP:77267-4414

Country:US

Phone:877-276-7285

Contract Num:SP0450-99-M-B099

CAGE:3N254

Company Name:SHELL OIL (800-535-2104)

Address:309 JEFFERSON HWY

Box:UNKNOWN

City:NEW ORLEANS

State:LA

ZIP:70121

Country:US

Phone:800-535-2104

CAGE:4Y429

C

Company Name:SHELL OIL COMPANY
Address:Box:2463
City:HOUSTON
State:TX
ZIP:77210
Country:US
Phone:800-231-6950
CAGE:54527

===== Composition/Information on Ingredients =====

Ingred Name:CAPRINUS U OIL 40 (THE FOLLOWING 5 INGREDIENTS ARE THE
COMPONENTS OF THIS PRODUCT)

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL OIL,HYDROTREATED (SEVERE), HEAVY NAPHTHENIC
DISTILLATE

CAS:64742-52-5

RTECS #:PY8035001

Fraction by Wt: 50-60%

Other REC Limits:NO

NE RECOMMENDED

Ingred Name:DISTILLATES, ACID-TREATED HEAVY NAPHTHENIC

CAS:64742-18-3

RTECS #:PY8032000

Fraction by Wt: 20-30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:MINERAL OIL,HYDROTREATED (SEVERE), PETROLEUM DISTILLATE,
HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035501

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ADDITIVES

Fraction by Wt: 10-15%

Other REC Limits:NONE RECOMMENDED

Ingred Name:CHLORINATED PARAFFIN WAX

CAS:63

449-39-8

RTECS #:RV0450000

Fraction by Wt: 5.0 G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT IS MINIMALLY IRRITATING TO BODY TISSUES. PROLONGED OR REPEATED SKIN CONTACT MAY YIELD DERMATITIS, FOLLICULITIS OR OIL ACNE. INHALATION IS UNLIKELY UNLESS PRODUCT IS IN MIST OR HEATED. INGESTION: BASED ON COMPONENT INFORMATION THIS PRODUCT IS NO MORE THAN SLIGHTLY TOXIC IF SWALLOWED.

Explanation of Carcinogenicity:NTP LISTS CHLORINATED PARAFFIN (INGREDIENT 7) AS HAVING SOME POTENTIAL WITH MALE RATS IN LARGE INGESTED DOSES.

Effects of Overexposure:IRRITATION AS NOTED ABOVE.

Medical Cond Aggravated by Exposure:PREEXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER FOR 15 MIN. GET MEDICAL ATTENTION.

SKIN: REMOVE CLOTHING & WASH

WASH OFF EXCESS. WASH WITH SOAP & WATER OR

WATERLESS CLEANER THEN SOAP & WATER. INHALATION: REMOVE TO FRESH AIR, GIVE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING. NO TREATMENT USUALLY NECESSARY, BUT GET MEDICAL ADVICE.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:~240.6C, 465.F

Extinguishing Media:USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE DIRECT WATER STREAM

. PRODUCT WILL FLOAT AND CAN REIGNITE ON WATER.

Fire Fighting Procedures:MATERIAL W/NOT BURN UNLESS PREHEATED. DO NOT ENTER FIRE-SPACE W/O FULL BUNKER GEAR (HELMET, BUNKER COAT, GLOVES, BOOTS) INCLUDING POSITIVE-PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS W/WATER.

Unusual Fire/Explosion Hazard:NONE SPECIFIED.

===== Accidental Release Measures =====

Spill Release Procedures:MAY BURN BUT NOT READILY IGNITABLE

LE. USE PROPER

PERSONAL PROTECTION. STOP LEAK IF W/O RISK. DIKE AND CONTAIN.
REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE VESSELS. ABSORB
REMAINDER WITH CLAY, SAND, ETC . FLUSH AREA WITH WATER TO REMOVE
TRACERESIDUE.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE WITH ADEQUATE
VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPEARTURES.
MIN
IMIZE SKIN CONTACT.

Other Precautions:PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES,
INCLUDING SHOES, THAT CANNOT BE DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF EXPOSURE MAY OR DOES EXCEED TLV/PEL, USE
NIOSH APPROVED RESPIRATOR, EITHER ATMOSPHERE SUPPLYING OR AIR
PURIFYING FOR ORGANIC VAPOR. SEE 29 CFR 1910.134 FOR DETAILS OF
RESPIRATOR REGULATIONS. USE EI THER AN ATMOSPHERE-SUPPLYING
RESPIRATOR OR AN AIR
-PURIFYING RESPIRATOR FOR ORGANIC VAPORS AND
PARTCULATES.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:WEAR SAFETY GOGGLES.

Other Protective Equipment:OTHER PROTECTIVE CLOTHING AS REQUIRED TO
MINIMIZE SKIN CONTACT.

Work Hygienic Practices:MINIMIZE SKIN CONTACT. WASH W/SOAP & WATER
BEFORE EATING,DRINKING,SMOKING OR USING TOILET. LAUNDER CLOTHING
BEFORE REUSE

Supplemental Safety and Health

TEST DATA FROM PUBLISHED LITERATUR

E AND/OR GLOVE/CLOTHING MANUFACTURERS

INDICATE THE BEST PROTECTION IS PROVIDED BY NITRILE GLOVES.

===== Physical/Chemical Properties =====

HCC:V6

Melt/Freeze Pt:=-26.1C, -15.F

Vapor Pres:(MM HG):