

N/P -- GAGE BLOCK PRESERVATIVE (AEROSOL) -- 8030-01-014-5065

Product ID:GAGE BLOCK PRESERVATIVE (AEROSOL)

MSDS Date:01/01/1987

FSC:8030

NIIN:01-014-5065

MSDS Number: BXWLT

=== Responsible Party ===

CAGE:02637

=== Contractor Identification ===

Company Name:DOALL COMPANY

Address:254 N LAUREL AVE

City:DES PLAINES

State:IL

ZIP:60016-4321

Country:US

CAGE:02637

=====
===== Composition/Information on Ingredients =====
=====

Ingre
d Name:PETROLEUM GAS (LIQUEFIED); (LIQUEFIED PETROLEUM GAS)
CAS:68476-85-7
RTECS #:SE7545000
Fraction by Wt: 50%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

Ingred Name:PENTANE
CAS:109-66-0
RTECS #:RZ9450000
Fraction by Wt: 20%
OSHA PEL:1000 PPM;750 STEL
ACGIH TLV:600 PPM;750 STEL

Ingred Name:VM&P NAPHTHA; (ISOPARAFFINIC SOLVENT)
CAS:64742-48-9
Fraction by Wt: 20%
ACGIH TLV:SIMPLE ASPHYXIAN

Ingred Name:MINERAL SPIRITS; (ALIPHATIC PETROLEUM DISTILLATE)
CAS:64742-88-7
Fraction by Wt: 4%

Ingred Name:

MINERAL OIL, PETROLEUM DISTILLATES

CAS:64742-65-0

RTECS #:PY8038501

Fraction by Wt: 4%

Ingred Name:ZINC SOAP

CAS:68918-69-4

Fraction by Wt: 2%

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50:(ORAL,RAT)5 MG/KG

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: DEFATTING,
AND/OR IRRITATION. SKIN ABSORTIONP: NOT EXPECTED TO OCCUR.

Explan

ation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:INHALATION-BREATHING DIFFICULTY.

INGESTION-NAUSEA, AND/OR DIARRHEA.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALE: REMOVE TO FRESH AIR. IF NECESSARY, SUPPORT BRTHG. GET
MEDICAL AID. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. IF
IRRITATION PERSISTS, GET MEDICAL AID. SKIN: WASH EXPOSED AREA WITH
MILD SOAP A ND W

ARM WATER ONLY. DO NOT USE HARSH SOAP OR SOLVENT.

SKIN ABSORPTION: GET MEDICAL ATTENTION. INGEST: KEEP WARM AND
QUIET. GET MEDICAL ATTENTION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SM SPILLS: USE ABSORBANT MATERIAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE DRY IN A CLOSED CONTAINER IN A
COOL PLACE AWAY FROM ANY

FIRE SOURCE.

Other Precautions:DO NOT INGEST. AVOID BREATHING VAPORS. DO NOT SMOKE WHILE USING/USE NEAR AN OPEN FLAME.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:GENERAL MECHANICAL VENTILATION SHOULD BE ADEQUATE. PROVIDE LOCAL VENTILATION IF VAPOR BUILDUP BECOMES EXCESSIVE.

Protective Gloves:NEOPRENE GLOVES THAT ARE IMPERMAEBLE.

Eye Protection:SAFETY GOGGLES OR FACE SHIELD.

Other Protective Equi

ipment:AN EMERGENCY SHOWER & EYEWASH SHOULD BE AVAILBLE IN WORK AREA.

Work Hygienic Practices:PRACTICE REASONABLE PERSONAL HYGIENE. WASH EXPOSED SKIN W/MILD SOAP & WARM WATER ONLY.

Supplemental Safety and Health

OIL SOAKED CLOTHING SHOULD BE CHANGED PROMPTLY AND LAUNDERED BEFORE RE-WEARING.

=====
===== Stability and Reactivity Data =====

Hazardous Decomposition Products:OXIDES OF CARBON.

=====
===== Disposal Considerations =====

Waste

Disposal Methods:TREAT AS AN OILY WASTE AND DISPOSE OF I/A/W LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.