

VELCRO USA INC -- VELCRO 45D ADHESIVE -- 1560-01-138-8825

=====
Product Identification
=====

Product ID:VELCRO 45D ADHESIVE

MSDS Date:08/24/1987

FSC:1560

NIIN:01-138-8825

Kit Part:Y

MSDS Number: BXYTJ

=== Responsible Party ===

Company Name:VELCRO USA INC

Address:406 BROWN AVE

Box:5218

City:MANCHESTER

State:NH

ZIP:03108

Country:US

Info Phone Num:603-669-4880

Emergency Phone Num:603-669-4880

Prepar

er's Name:P. KING-MULLEN

CAGE:11153

=== Contractor Identification ===

Company Name:UNITED TECHNOLOGIES INC. SIKORSKY AIRCRAFT DIV.

Address:6900 MAIN STREET

Box:7016

City:STRATFORD

State:CT

ZIP:06601-1381

Country:US

Phone:203-386-3791

CAGE:78286

Company Name:VELCRO USA INC

Address:406 BROWN AVE

Box:5218

City:MANCHESTER

State:NH

ZIP:03108

Country:US

Phone:603-669-4880

CAGE:11153

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS

#:AL3150000
Fraction by Wt: 42.8%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 28.1%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ACETATE
CAS:141-78-6
RTECS #:AH5425000
Fraction by Wt: 3.3%
Other REC Limits:NO
NE RECOMMENDED
ACGIH TLV:400 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PHENOL
CAS:108-95-2
RTECS #:SJ3325000
Fraction by Wt: 3.1%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:5 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 200-1000 MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chr

onic:HAZARDOUS IF INGESTED. HAZARDOUS IF INHALED. INGREDIENTS CAUSES EYE IRRITATION. INGREDIENTS CAUSES POSSIBLY IRREVERSIBLE EYE BURNS.

Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS PRODUCT ARE ON THE IARC, NTP OR OSHA LISTS OF CARCINOGENIC HAZARDS.

Effects of Overexposure:IRRITATION OF EYES, NOSE AND THROAT, HEADACHE, HIGH EXPOSURE - NARCOSIS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====
=====

First Aid:INGESTION: IF SWALLOWED, CALL A PHYSICIAN. THE ATTENDING PHYSICIAN MUST DECIDE WHETHER OR NOT TO INDUCE VOMITING BASED ON HIS EVALUATION OF THE PATIENT. INHALATION: IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO- MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. CONTACT: IMMEDIATELY FLUSH W/PLENTY OF WATER-15 MIN. CALL A PHYSICIAN

=====
===== Fire Fighting Measur
es =====

Flash Point Method:OC

Flash Point:17.0F,-8.3C

Lower Limits:2.04

Upper Limits:12.31

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP LIQUID W/ABSORBENT MATERIAL-SAND, EARTH, SWEEPING COMPOUND OR SOME OTHER ABSORBENT MATERIAL. PACKAGE

ABSORBENT MATERIAL OR SOLID PRODUCT IN STEEL DRUMS WHICH ARE IN GOOD CONDITION. THOROUGHLY CLEAN AREA WHERE SPILL OCCURRED.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL LOCATION (60-80 F) AWAY FROM SUNLIGHT AND ANY SOURCE OF HEAT, SPARKS OR FLAME. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT USED.

Other Precautions:USE WITH ADEQUATE VENTILATION, AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. AVOID SKIN CON

TACT. USE IN AN AREA
FREE FROM FLAME AND SPARKS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.
Ventilation:LOCAL EXHAUST IS PREFERRED, MECHANICAL EXHAUST IS
ACCEPTABLE.
Protective Gloves:NEOPRENE RUBBER, NITRILE, IMPERVIOUS
Eye Protection:SAFETY GLASSES OR FULL FACE SHIELD
Other Protective Equipment:SAFETY SHOWER AND EYE BATH
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health
h

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:=56.1C, 133.F
B.P. Text:133 TO 212F
Vapor Pres:135 MM HG
Vapor Density:2.23
Spec Gravity:0.87
Evaporation Rate & Reference:NA
Solubility in Water:51.3%
Appearance and Odor:A DARL AMBER LIQUID WITH KETONE ODOR.
Percent Volatiles by Volume:81

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS.
Stability Condition to Avoid:NONE
SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:FUMES MAY INCLUDE CARBON DIOXIDE,
CARBON MONOXIDE, WATER VAPOR, OXIDES OF NITROGEN, TOXIC FUMES,
CYANIDE MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF PER FEDERAL, STATE & LOCAL REGS. BE
AWARE THAT STATE & LOCAL REQUIREMENTS MAY DIFFER WIDELY DEPENDING
ON LOCATION & IN MANY CASES BE DIFFERENT FROM FEDERAL RULES. THIS
PRODUCT WOULD BE CLAS SIFIE

D A HAZARDOUS WASTE UNDER FEDERAL REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.